

Efficiency in Automation

Cable • Connectivity • Cabinet • Control

Compact Series Power Supplies



Suitable for industrial applications especially where high inrush power is required, as well as when compact housing or extended reliability are desired.

Specifications:

- 30 to 2400 Watts
- Output current ranges: 1.2-100 Amps
- 150% over nominal, 5 sec. during overload
- High efficiency > 95%
- Low heat dissipation
- Extremely compact footprint
- 1, 2 and 3-phase input units
- Wide input voltage ranges: AC90-550V
- Low ripple and noise: < 100mV

- DIN Rail mountable
- Short circuit protection
- Parallel & redundant features
- Screw or pluggable screw
- UL 508 listed
- 4 year warranty

Ask about our electronic
dc circuit protection device
LOCC-Box!



LUTZE Inc. 13330 South Ridge Dr., Charlotte, NC 28273
1-800-447-2371 info@lutze.com www.lutze.com

LUTZE 
SYSTEMATIC TECHNOLOGY

Efficiency in Automation

Cable • Connectivity • Cabinet • Control

Delta Series Power Supplies



Suitable for industrial applications for standard specifications, providing an economical and reliable solution.

Specifications:

- 10 to 960 Watts
- Output current ranges: 0.42-40 Amps
- High efficiency: > 93%
- Output voltage range: 5 - 48 Vdc
- Wide input voltage ranges: AC85-576V
- Low ripple and noise: < 100mV
- Short circuit protection
- Parallel and redundant features
- DIN Rail mountable
- Spring, screw or pluggable screw terminals
- UL 508 listed
- Class 1 Div.2
- 1 year warranty



LUTZE Inc. 13330 South Ridge Dr., Charlotte, NC 28273
1-800-447-2371 info@lutze.com www.lutze.com

