

EMEA Tripp Lite series

Providing your customers with the full solution



Powering Business Worldwide

Table of Contents

IT Infrastructure	5-54
Server Racks & Cabinets	6-16
Floor-Standing Enclosures	6
Open-Frame Racks	7
Wall-Mount Enclosures	8-9
Aisle Containment Systems	10
Rack Accessories	11-16
KVM Switches & Console Servers	17-22
Console KVMs	17
Rackmount KVM Switches	18
Secure NIAP KVM Switches	19
Console Servers	20
KVM Accessories	21-22
Copper Networks	23-34
Copper Patch Panels	23
Copper Couplers	24
Cat5e Copper Cables	25-26
Cat6 Copper Cables	27-30
Cat6a Copper Cables	31-32
Cat8 Copper Cables	33
Cisco Console Rollover Cables	34
Fiber Networks	35-50
Fiber Patch Panels	35
Fiber Cassette Enclosures & Sleeves	36
Fiber Cassettes	36
Fiber Patch Panels	37
OS2 Singlemode Patch Cables	38-39
OM1 Multimode Fiber Patch Cables	40-41
OM2 Multimode Fiber Patch Cables	42
OM3 Multimode Fiber Patch Cables	43-44
OM4 Multimode Fiber Patch Cables	45-46
OM5 Multimode Fiber Patch Cables	46
MTP/MTO Cables	47-49
Fiber Couplers	49
Mode Conditioning	50
Network Adapters	50
Media Converters	51
Transceiver Modules	52
Direct Attach Cables (DACs)	53
Power Cords	54
Work from anywhere (WFA), Retail & Education	55-77
Docking Station, Hubs & Switches	56-59
Docking Stations	56
Hubs & Switches	57
Multiport Adapters	58-59
Display Mounts	60-61
Height-Adjustable Workstations	60
Desktop Monitor Mounts	61
Power solutions	62-63
Desktop Charging Stations	62
Desktop KVM Switches	63

USB Cables	64-72
USB-A 2.0 Cables	64
USB-A 2.0 Reversible Cables	65
USB-A 2.0 Extension Cables	66
USB-C 2.0 Cables	67
Lightning Cables	68
USB 3.1 Gen 1 Cables	69
USB 3.2 Gen 2 Cables	70
USB-C 3.0 Extension Cables	71
Thunderbolt Cables	72
USB Couplers	72
USB Adapters	73-76
USB Adapters	73-75
USB Panel Mounts	76
USB Extenders	77
Pro AV & Digital signage	78-109
Video Splitters & Multiviewers	79-82
VGA Splitters	79
DVI Splitters	79
DisplayPort Splitters	80
HDMI Splitters	80
VGA Switches	81
DisplayPort Switches	81
HDMI Switches	82
Video Extenders	83-86
Wireless Video Extenders	83
VGA Extenders	83
DisplayPort Extenders	84
HDMI Extenders	85-86
Display mounts	87-91
Wall Mounts	87-88
TV Stands and Carts	89
Tablet & Smartphone Mounts	90
Ceiling Mount	90
Mobile Workstations	91
Rolling Desks	91
Audio Video Cables	92-98
Audio Cables	92
VGA Cables	93
DVI Cables	94
DisplayPort Cables	95
HDMI Cables	96-98
Audio Video Adapter Cables	99-103
Audio Adapter Cables	99
HDMI Adapter Cables	100
DVI Adapter Cables	101
DisplayPort Adapter Cables	102-103
Video Adapters	104-107
DVI Adapters	104
DisplayPort Adapters	105-106
HDMI Adapters	107
Video Couplers	108
Audio Video Panel Mount	109
Patch Panels & Accessories	109

Industrial-Grade IT Solutions	110-123
Server Racks & Cabinets	111
SmartRack Industrial Enclosures	111
Copper Network Cables	112-114
Cat5e Copper Cables	112
Cat6 Copper Cables	112
M12 X-Code Cat6 Copper Cables	113
M12 X-Code Cat6a Copper Cables	114
Fiber Network Cables	115
OM3 Multimode Fiber Patch Cables	115
Industrial Network Switches	116
Transceivers	117
PoE Injectors	117
USB Cables	118-121
USB 3.1 Gen 1 Cables	118
USB Adapters	118
USB Hubs	119
USB Extenders	120
AV Solutions	121
HDMI Cables	121
Couplers	121
Power over Ethernet (PoE)	122-123
PoE Injectors & Extenders	122
WAP Enclosures	123
Healthcare	124-131
Power Solutions	125-126
UPS Systems	125
Isolation Transformers	125
Power Inverter/Chargers	126
Safe-IT Cables	127-129
Cat6a Safe-IT Copper Cables	127
Safe-IT USB Cables	128
Safe-IT Audio Video Cables	129
Display Mounts	130-131
Rolling TV Stands and Carts	130
Desktop Monitor Mounts	130
Workstations	131
Clamp-On Monitor Risers	131

A photograph of two men in a server room. One man is seen from the back, wearing a dark blue shirt. The other man, wearing glasses and a dark sweater, is looking at a device held in his hands. The background is filled with server racks and bright overhead lights, creating a blue-toned industrial atmosphere.

IT Infrastructure

Server Racks & Cabinets

KVM Switches & Console Servers

Copper Networks

Fiber Networks

Media Converters

Transceiver Modules

Direct Attach Cables (DACs)

Power Cords

Floor-Standing Enclosures

Eaton's premium-grade floor and wall mount server racks and cabinets organize and secure IT equipment wherever it is located, from high-density data centers to the tightest of spaces at the edge of your network.



Key points:

- Compatible designs
- Tool-less mounting / Essential equipment included
- Vertical cable management bars
- Fully assembled

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Dimensions (cm)				Static load (Kg)	Doors		Mounting rails	Color	
	Height		Width (cm)	Depth		Type	Side panels			
	U	(cm)		Rack Depth						
SR12UB	12U	64 cm	60 cm	Mid	85 cm	454 kg	Vented	Yes	Square	Black
SR14UBDP	14U	72 cm	60 cm	Standard	111 cm	454 kg	Vented	Yes	Square or 10-32 holess	Black
SR18UB	18U	90 cm	60 cm	Mid	85 cm	454 kg	Vented	Yes	Square	Black
SR24UB	24U	116 cm	60 cm	Mid	85 cm	454 kg	Vented	Yes	Square	Black
SR25UB	25U	124 cm	60 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR42UBSD	42U	199 cm	60 cm	Shallow	83 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR42UBMD	42U	199 cm	60 cm	Mid	91 cm	1361 kg	Vented	Yes	Square	Black
SR42UB	42U	199 cm	60 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR42UBEXP	42U	199 cm	60 cm	Standard	109 cm	1361 kg	Vented	-	Square or 10-32 holes	Black
SR42UBG	42U	199 cm	60 cm	Standard	109 cm	1361 kg	Acrylic	Yes	Square or 10-32 holes	Black
SR42UBDP48	42U	199 cm	60 cm	Extra Deep	120 cm	1361 kg	Vented	Yes	Square	Black
SR42UBDP	42U	199 cm	60 cm	Deep	123 cm	1361 kg	Vented	Yes	Square	Black
SR42UBWD	42U	199 cm	75 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR42UBWDVRT	42U	199 cm	75 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR42UBDPWD	42U	199 cm	75 cm	Deep	123 cm	1361 kg	Vented	Yes	Square	Black
SR45UBSD	45U	213 cm	60 cm	Shallow	83 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR45UB	45U	213 cm	60 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR45UBDPWD	45U	213 cm	75 cm	Deep	123 cm	1361 kg	Vented	Yes	Square	Black
SR48UB	48U	226 cm	60 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR48UBEXPND	48U	226 cm	60 cm	Standard	109 cm	1361 kg	-	-	Square or 10-32 holes	Black
SR48UBWD	48U	226 cm	75 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR48UBDPWD	48U	226 cm	75 cm	Deep	123 cm	1361 kg	Vented	Yes	Square	Black
Rack on a Shock Pallet										
SR25UBSP1	25U	124 cm	60 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR42UBSP1	42U	199 cm	60 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
SR48UBSP1	48U	226 cm	60 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
Knock-Down (Ships unassembled)										
SR42UBKD	42U	199 cm	60 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
Seismic-Certified										
SR42UBZ4	42U	199 cm	60 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black
Quiet Racks										
SRQP42UB	42U	199 cm	60 cm	Standard	109 cm	1088 kg	Solid	Yes	Square or 10-32 holes	Black
Co-Location										
SR42UBCL	42U	199 cm	60 cm	Standard	109 cm	1361 kg	Vented	Yes	Square or 10-32 holes	Black

Open-Frame Racks

Free-standing open-frame-post rack stores and organizes U of 19-inch rack equipment in labs, test setups, network closets and other secure IT areas with limited floor space where you need easy access to equipment.



Key points:

- Compatible designs
- Tool-less mounting / Essential equipment included
- Fully assembled

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Dimensions (cm)					Number of Vertical Mounting Rails	Static load (Kg)	Mounting rails	Color
	Height		Width (cm)	Depth					
	U	(cm)		Rack Depth	(cm)				
SR2POST12	12U	8 cm	9 cm	Standard	63 cm	2	50 kg	M6 square	Black
SR2POST13	13U	71 cm	52 cm	Extra Deep	12 cm	2	363 kg	12-24 threaded	Black
SR2POST25	25U	124 cm	51 cm	Extra Deep	12 cm	2	363 kg	12-24 threaded	Black
SR2POST	45U	213 cm	52 cm	Extra Deep	12 cm	2	363 kg	12-24 threaded	Black
SR4POST13	13U	71 cm	51 cm	Standard	56-91 cm	4	454 kg	M6 square	Black
SR4POST25	25U	125 cm	51 cm	Standard	56-91 cm	4	454 kg	M6 square	Black
SR4POST	45U	214 cm	51 cm	Standard	56-91 cm	4	454 kg	M6 square	Black
SR4POST48HD	48U	229 cm	61 cm	Standard	90 cm	4	1360 kg	M6 square	Black
SR4POST50HD	50U	236 cm	61 cm	Standard	90 cm	4	1360 kg	M6 square	Black
SR4POST52HD	52U	246 cm	61 cm	Standard	90 cm	4	1360 kg	M6 square	Black
Expandable									
SR42BMDEXPNDR3	42U	201 cm	66 cm	Mid	91 cm	4	1 360 kg	10 - 32 hole	Black
SR42UBEXPND	42U	199 cm	66 cm	Standard	105 cm	4	1 360 kg	10 - 32 hole	Black
Expandable & Knock-Down (Ships unassembled)									
SR12UBEXPNDKD	12U	65 cm	51 cm	Standard	91 cm	4	454 kg	Square	Black

Wall-Mount Enclosures

Connects a PC or server to a PDU or UPS system in a data rack or cabinet.



Key points:

- Fully assembled
- Horizontal and Vertical mounting system
- Wide selection of sizes

Ideal for:

- Fully assembled
- Horizontal and Vertical mounting system
- Wide selection of sizes

Part number	Dimensions (cm)					Static load (Kg)	Doors		Side panels	Mounting rails	Cable entry	Color	
	Height		Width (cm)	Depth			Front	Rear					
	U	(cm)		Rack Depth	(cm)								
Horizontal-Mount													
SRW6U	6U	37 cm	60 cm	Shallow	45 cm	91 kg	Vented	Static	Yes	Square or 12-24 holess	Top and bottom routing ports	Black	
SRW6UDP	6U	37 cm	60 cm	Shallow	45 cm	91 kg	Vented	Static	Yes			Black	
SRW6UG	6U	37 cm	60 cm	Shallow	45 cm	91 kg	Acrylic	Static	Yes			Black	
SRW6UW	6U	37 cm	60 cm	Shallow	45 cm	91 kg	Vented	Static	Yes			White	
SRW6UWG	6U	37 cm	60 cm	Shallow	45 cm	91 kg	Acrylic	Static	Yes			White	
SRW9U	9U	51 cm	60 cm	Shallow	45 cm	91 kg	Vented	Static	Yes			Black	
SRW9UDP	9U	51 cm	60 cm	Shallow	45 cm	91 kg	Vented	Static	Yes	Black	Square or 12-24 holess	Top and bottom routing ports	Black
SRW9UDPW	9U	51 cm	60 cm	Shallow	45 cm	91 kg	Vented	Static	Yes	White			
SRW9UG	9U	51 cm	60 cm	Shallow	45 cm	91 kg	Acrylic	Static	Yes	Black			
SRW9UDPVRT	9U	51 cm	75 cm	Shallow	45 cm	91 kg	Vented	Static	Yes	Black			
SRW10US	10U	55 cm	60 cm	Shallow	55 cm	91 kg	Vented	Hinged	Yes	Square or 12-24 holess	Top and bottom routing ports	Black	
SRW10USG	10U	55 cm	60 cm	Shallow	60 cm	91 kg	Acrylic	Hinged	Yes			Black	
SRW012UBRKTSHL	12U	63 cm	50 cm	Shallow	38 cm	68 kg	Open	Hinged	-			Black	
SRW12U	12U	64 cm	60 cm	Shallow	45 cm	91 kg	Vented	Static	Yes			Black	
SRW12U13	12U	64 cm	60 cm	Shallow	33 cm	91 kg	Vented	Static	Yes			Black	
SRW12U13G	12U	64 cm	60 cm	Shallow	33 cm	91 kg	Acrylic	Static	Yes			Black	
SRW12UDP	12U	64 cm	60 cm	Shallow	55 cm	91 kg	Vented	Static	Yes			Black	
SRW12UG	12U	64 cm	60 cm	Shallow	45 cm	91 kg	Acrylic	Static	Yes			Black	
SRW12UHD	12U	67 cm	63 cm	Mid	92 cm	227 kg	Vented	Static	Yes			Black	
SRW12US	12U	64 cm	60 cm	Shallow	55 cm	91 kg	Vented	Hinged	Yes	Square or 12-24 holess	Top and bottom routing ports	Black	
SRW12US33	12U	64 cm	60 cm	Mid	85 cm	113 kg	Vented	Hinged	Yes			Black	
SRW12US33G	12U	64 cm	60 cm	Mid	85 cm	113 kg	Acrylic	Hinged	Yes			Black	
SRW12USDP	12U	64 cm	60 cm	Shallow	65 cm	91 kg	Vented	Hinged	Yes			Black	
SRW12USDPG	12U	64 cm	60 cm	Shallow	65 cm	91 kg	Acrylic	Hinged	Yes			Black	
SRW12USG	12U	64 cm	60 cm	Shallow	55 cm	91 kg	Acrylic	Hinged	Yes			Black	
SRW15US	15U	77 cm	60 cm	Shallow	55 cm	91 kg	Vented	Hinged	Yes			Black	
SRW15USG	15U	77 cm	60 cm	Shallow	55 cm	91 kg	Acrylic	Hinged	Yes			Black	

Part number	Dimensions (cm)					Static load (Kg)	Doors		Side panels	Mounting rails	Cable entry	Color		
	Height		Width (cm)	Depth			Front	Rear						
	U	(cm)		Rack Depth	(cm)									
Open-frame														
SRW012UHD	12U	63 cm	51 cm	Shallow	46 cm	91 kg	Open	-	-	12-24 holess	Top and bottom routing ports	Black		
SRW012US	12U	78 cm	50 cm	Shallow	52 cm	68 kg	Open	-	-			Black		
SRW012UBRKTSHEL	12U	63 cm	50 cm	Shallow	38 cm	68 kg	Open	Hinged	-	Square or 12-24 holess	Top and bottom routing ports	Black		
SRW18UHD	18U	94 cm	63 cm	Mid	92 cm	227 kg	Vented	Static	Yes	Square holess / 12-24 threaded holes	Top and bottom routing ports Side	Black		
SRW18US	18U	90 cm	60 cm	Shallow	55 cm	113 kg	Vented	Hinged	Yes			Black		
SRW18US13	18U	90 cm	60 cm	Shallow	33 cm	113 kg	Vented	Hinged	Yes			Black		
SRW18USDP	18U	90 cm	60 cm	Shallow	66 cm	113 kg	Vented	Hinged	Yes			Black		
SRW18USDPG	18U	90 cm	60 cm	Shallow	66 cm	113 kg	Acrylic	Hinged	Yes			Black		
SRW18USG	18U	90 cm	60 cm	Shallow	55 cm	113 kg	Acrylic	Hinged	Yes			Black		
SRW21U	21U	104 cm	60 cm	Shallow	45 cm	91 kg	Vented	Static	Yes			Black		
SRW26US	26U	100 cm	60 cm	Shallow	45 cm	91 kg	Vented	Static	Yes			Black		
SRW26USDP	26U	126 cm	60 cm	Shallow	65 cm	113 kg	Vented	Hinged	Yes			Black		
Expandable 8/12/22U														
SRW08U22	8U		51 cm	Shallow	46 cm	68 kg	Open	Static	-	Threaded 12-24 holes	Top and bottom routing ports	Black		
SRW08U22DP	8U	45 cm (8U) 63 cm (12U)	51 cm	Shallow	61 cm	68 kg	Open	Static	-			Black		
SRW08U22MD	8U	107 cm (22U)	51 cm	Shallow	30 cm	68 kg	Open	Static	-			Black		
SRW08U22SD	8U		51 cm	Shallow	45 cm	68 kg	Open	Static	-			Black		
SRW08UBRKTSHELF	8U	44 cm	50 cm	Shallow	38 cm	68 kg	Open	Hinged	-			Black		
Knock-Down (Ships unassembled)														
SRW6UKD	6U	37 cm	60 cm	Shallow	45 cm	91 kg	Vented	Static	Yes			Black		
Vertical-Mount														
SRWF2U	2U	73 cm	65 cm	Shallow	11 cm	68 kg	Vented	Static	Yes	Supports M6 and 12-24 mounting	Top and bottom routing ports Side	Black		
SRWF2U36	2U	109 cm	65 cm	Standard	11 cm	68 kg	Vented	Static	Yes			Black		
SRWF6UMOD	3U	90 cm	51 cm	Shallow	18 cm	68 kg	Vented	Static	Yes			Black		
SRWF4U	4U	73 cm	65 cm	Shallow	20 cm	68 kg	Vented	Static	Yes			Black		
SRWF4U36	4U	109 cm	65 cm	Standard	20 cm	68 kg	Vented	Static	Yes			Black		
SRWF5U	5U	81 cm	74 cm	Shallow	33 cm	68 kg	Vented	Static	Yes			Black		
SRWF5U36	5U	110 cm	65 cm	Shallow	25 cm	68 kg	Vented	Static	Yes			Black		
SRWF6U	6U	73 cm	65 cm	Shallow	29 cm	68 kg	Vented	Static	Yes			Black		
SRWF6U36	6U	110 cm	68 cm	Standard	30 cm	68 kg	Vented	Static	Yes			Black		
SRWF12U38	12U	97 cm	50 cm	Standard	41 cm	181 kg	Vented	Static	Yes			Black		
SRWF16U38	16U	97 cm	50 cm	Standard	59 cm	181 kg	Vented	Static	Yes			Black		
SRW02UBRKT	2U	54 cm	51 cm	Shallow	11 cm	34 kg	Vented	Static	Yes			Square holes	Open top and bottom	Black
SRW04UBRKT	4U	54 cm	51 cm	Shallow	20 cm	34 kg	Vented	Static	Yes			Square holes		Black

Aisle Containment System

Keeps hot and cool air separated for better temperature control and equipment performance in hot aisle/cold aisle configurations.



Key points:

- Self standing structure
- Flexible and expandable
- Fast assembly







Ideal for:






- Network Closet
- Server Room
- Data Center
- White Space










	Part number	Description	Enclosure
			Floor Standing Open-Frames
	SRCTMTCVR300	Roof Panel Kit for Hot/Cold Aisle Containment System - Standard 300 mm Rack Coolers	Yes
	SRCTMTCVR600	Roof Panel Kit for Hot/Cold Aisle Containment System - Standard 600 mm Racks	Yes
	SRCTMTCVR750	Roof Panel Kit for Hot/Cold Aisle Containment System - Wide 750 mm Racks	Yes
	SRCTMTRFM	Frame End Kit for Hot/Cold Aisle Containment System	Yes
	SRCTMTR300SH	Short Riser Panels for Hot/Cold Aisle Containment System - Standard 300 mm Rack Coolers, Set of 2	Yes
	SRCTMTR300TL	Tall Riser Panels for Hot/Cold Aisle Containment System - Standard 300 mm Rack Coolers, Set of 2	Yes
	SRCTMTR600SH	Short Riser Panels for Hot/Cold Aisle Containment System - Standard 600 mm Racks, Set of 2	Yes
	SRCTMTR600TL	Tall Riser Panels for Hot/Cold Aisle Containment System - Standard 600 mm Racks, Set of 2	Yes
	SRCTMTR750SH	Short Riser Panels for Hot/Cold Aisle Containment System - Wide 750 mm Racks, Set of 2	Yes
	SRCTMTR750TL	Tall Riser Panels for Hot/Cold Aisle Containment System - Wide 750 mm Racks, Set of 2	Yes
	SRCTMTSDD	Sliding Double-Door Kit for Hot/Cold Aisle Containment System	Yes











Rack Accessories

Accessories for your rack for a tidy and professional look

	Part number	Description	Enclosure	
			Floor-Standing Open-Frames	Wall-Mount
Cable management				
	NCM-JHW08-25	J-Hook Cable Support - 3/4", Wall Mount, Galvanized Steel, 25 Pack	-	-
	NCM-JHW40-25	J-Hook Cable Support - 4", Wall Mount, Galvanized Steel, 25 Pack	-	-
	P350-10N-10	Hook-and-Loop Cable Ties, 10" L x 5/8" W - 10-Pack	Yes	Yes
	P352-07N-100	7.5" Nylon Cable Ties - 100-Pack	Yes	Yes
	SRCABLEDUCT1U	SmartRack 1U Horizontal Cable Manager - Finger duct with cover	Yes	Yes
	SRCABLEDUCT1UHD	SmartRack 1U High Capacity Horizontal Cable Manager - Finger duct with dual-hinge cover	Yes	Yes
	SRCABLEDUCT2UHD	SmartRack 2U High Capacity Horizontal Cable Manager - Finger duct with dual-hinge cover	Yes	Yes
	SRCABLEDUCTVRT	SmartRack 6 ft. (1.83 m) Vertical Cable Manager - Double finger duct with cover & toolless mounting	Yes	-
	SRCABLERING1U	SmartRack 1U Horizontal Cable Manager - Flexible ring type	Yes	Yes
	SRCABLERING2U	SmartRack 2U Horizontal Cable Manager - Flexible ring type	Yes	Yes
	SRCABLERINGLG	Cable Management D-Rings for Rack Enclosures - Button Mount, Large, 3 x 4 in., 12 Pack	Yes	Yes
	SRCABLERINGSM	Cable Management Rings for Rack Enclosures - Button Mount, Small, 2 x 4 in., 12 Pack	Yes	Yes
	SRCABLERINGVRT	SmartRack 6 ft. (1.83 m) Vertical Cable Manager - Flexible ring type & toolless mounting	Yes	-
	SRCABLETRAY1U	SmartRack 1U Horizontal Cable Management Tray	Yes	Yes
	SRCABLEVRT12	SmartRack 12-in. (30.48 cm) Width High Capacity Vertical Cable Manager - Double finger duct with cover	Yes	-
	SRCABLEVRT3	SmartRack 3-in. (7.62 cm) Wide High Capacity Vertical Cable Manager - Double finger duct	Yes	-
	SRCABLEVRT6	SmartRack 6-in. (15.24 cm) Wide High Capacity Vertical Cable Manager - Double finger duct with cover	Yes	-
	SRVRTBAR	SmartRack 42U Vertical Cable Management Bars	Yes	-
	SRVRTBAR45	SmartRack 45U Vertical Cable Management Bars	Yes	-
	SRVRTBAR48	SmartRack 48U Vertical Cable Management Bars	Yes	-

	Part number	Description	Enclosure	
			Floor-Standing Open-Frames	Wall-Mount
Roof Mounted Cable Routing				
	SR LADDERATTACH	SmartRack Hardware Kit - Connects SRCABLELADDER to a wall or Open Frame Rack	Yes	
Locking System				
	SR HANDLE1	Replacement Lock for SmartRack Server Rack Cabinets - Front and Back Doors, 2 Keys, Version 1	Yes	-
	SR HANDLE2	Replacement Lock for SmartRack Server Rack Cabinets - Front and Back Doors, 2 Keys, Version 2	Yes	-
	SR HANDLE3	Replacement Lock for SmartRack Server Rack Cabinets - Front and Back Doors, 2 Keys, Version 3	Yes	-
	SR HANDLE4	Replacement Lock for SmartRack Server Rack Cabinets - Front and Back Doors, 2 Keys, Version 4	Yes	-
	SR RAILDPTH1U	SmartRack 1U Mounting Rail Deep Adapter Kit for Server Racks, 4 in. (10.2 cm)	Yes	-
	SR RAILDPTH2U	SmartRack 2U Mounting Rail Deep Adapter Kit for Server Racks, 4 in. (10.2 cm)	Yes	-
	SR SWITCH	SmartRack Magnetic Door Switch Kit for front and rear doors; requires ENVIROSENSE, TLNETEM, E2MTHDI or E2MTDI	Yes	-
	SR SWITCH	SmartRack Magnetic Door Switch Kit for front and rear doors; requires ENVIROSENSE, TLNETEM, E2MTHDI or E2MTDI	Yes	-
	SR WCOMBO	Replacement Combination Lock for SmartRack Wall-Mount Server Rack Cabinets - Front Door	-	Yes
	SR COMBO	SmartRack Door Handles with Combination Lock - 2-pack for front and rear doors with bypass key	Yes	-
	SR GP1KO	SmartRack Cable Gland Plate for NEMA-Rated Enclosure Cabinets, 6 Ports	-	Yes
	SR GP2KO	SmartRack Cable Gland Plate for NEMA-Rated Enclosure Cabinets, 3 Ports	-	Yes
	SR GP3RM	SmartRack Cable Entry Gland Plate for NEMA-Rated Enclosure Cabinets, 21-Port Membrane	-	Yes
	SR GP4PLASTIC	SmartRack Cable Entry Gland Plate for NEMA-Rated Enclosure Cabinets, Waterproof	-	Yes

	Part number	Description	Enclosure	
			Floor-Standing Open-Frames	Wall-Mount
Airflow Management				
	SRXFAN3U	SmartRack 3U Fan Panel - 3 208-240V high-performance fans; 315 CFM; C14 inlet	Yes	Yes
	SRXFANROOF	SmartRack Roof-Mounted Fan Panel - 6 208/240V high-performance fans; 420 CFM; C14 inlet	Yes	-
	SRXFANWM	Wall-Mount Roof Fan Kit - Dual 230V High-Performance Fans, 210 CFM, 3 ft. (0.91 m) Cord, C14 Input	-	Yes
	SR1UBRUSH	1U Cable Pass-Through Panel with Brush Strip	Yes	Yes
	SR1UPANEL10	1U Blanking Panel Kit, Toolless-Mounting, 10 pieces	Yes	Yes
	SR1UPANEL50	1U Blanking Panel Kit, Toolless-Mounting, 50 pieces	Yes	Yes
	SR1UPANEL200	1U Blanking Panel Kit, Toolless-Mounting, 200 pieces	Yes	Yes
	SRBRUSHWM	SmartRack Brush Strip Plate for Wall-Mount Racks	Yes	Yes
	SRXUPANEL	19 in. Blanking Panel Kit, 4 Pieces	Yes	Yes
	SRCOOLMVKIT	SmartRack Magnetic Vinyl Kit for Rack Airflow Management	Yes	-
	SRDUCTN7009	9U Air Inlet Duct Kit - Nexus 7000-Series Switches and Tripp Lite Wide Racks	Yes	-
	SRFILTER	SmartRack Enclosure Filter Kit	Yes	-
	SRSKIRT	SmartRack Enclosure Skirt Kit	Yes	-
	SRSKIRT3	SmartRack Enclosure Skirt Kit - use with 3 in. casters	Yes	-
	SRSKIRTEU	SmartRack Enclosure Skirt Kit for Euro-Series Wide Server Rack, 800 mm Width	Yes	-
	SRSWITCHDUCT	SmartRack Side Airflow Ducting Kit for Network Switches	Yes	-


	Part number	Description	Enclosure	
			Floor-Standing Open-Frames	Wall-Mount
Mounting Options				
	B018-000-1P5	1U Rack-Mount Device Rack Extension Bracket, 1.5 in.	Yes	Yes
	SR2319ADAPT	Adapter Kit for Mounting 19 in. Rack Equipment in 23 in. Racks	Yes	-
	SRBOLTDOWN	SmartRack Bolt-Down Kit - Secures stabilizing brackets or plates to facility floor	Yes	Yes
	SRCAGENUTSMM	SmartRack Square Hole Hardware Kit with 50 M5 screws and washers	Yes	Yes
	SRCAGENUTS	SmartRack Square Hole Hardware Kit with 50 M6 screws and washers	Yes	Yes
	SRCAGENUTS1224	SmartRack Square Hole Hardware Kit with 50 pcs 12-24 screws and washers	Yes	Yes
	SRCASTER	SmartRack Rolling Caster Kit, 4 pack	Yes	-
	SRCASTERHDKIT	SmartRack Heavy-Duty Rolling Caster Kit, 4 pack	Yes	-
	SRDINRAIL2U	Adjustable Rack-Mount DIN Rail Kit – Top Hat, Mini Top Hat and G-Style Rails	Yes	Yes
	SREXTENDER	SmartRack Rack Enclosure Extension Frame - Increases rack external & maximum mounting depth	Yes	-
	SRSCREWS	SmartRack Threaded Hole Hardware Kit - 50 each #12-24 screws	Yes	Yes
	SRSTABILIZE	SmartRack Anti-Tip Stabilizing Plate Kit - Provides extra stability for standalone enclosures	Yes	-
	SRVTRAIL23	SmartRack 23 in. Wide Mounting Rail Kit		

Part number	Description	Enclosure	
		Floor-Standing Open-Frames	Wall-Mount


Shelves

	SR16SHELF	3U Rack-Mount Configurable Storage Shelf for Personal Electronics	Yes	Yes
	SRDRAWER2U	SmartRack 2U Locking Rack-Mount Storage Drawer	Yes	Yes
	SRDRAWER4U	SmartRack 4U Locking Rack-Mount Storage Drawer	Yes	Yes
	SRSHELF2P	SmartRack 2U Cantilever Fixed Shelf (60 lbs / 27.2 kgs capacity; 18-in. / 457 mm depth.)	Yes	Yes
	SRSHELF2P1U	SmartRack 1U Cantilever Fixed Shelf (40 lbs / 18.1 kgs capacity; 12-in. / 305 mm depth.)	Yes	Yes
	SRSHELF2P1USHRT	SmartRack Cantilever Fixed Steel Rack Shelf - 1U, Vented, 7 in. (17.8 cm) Deep, Holds up to 40 lb. (18 kg)	Yes	Yes
	SRSHELF2P1UTM	SmartRack 1U Cantilever Toolless Mount Fixed Shelf (30 lbs / 13.6 kgs capacity; 12 in./305 mm depth)	Yes	Yes
	SRSHELF2PCENTER	SmartRack Center-Mounted Steel Rack Shelf - 2U, Vented, 21.5 in. Deep, Holds up to 100 lb. (45 kg)	Yes	Yes
	SRSHELF2PDP	2U Cantilever Fixed Shelf (60 lbs / 27.2 kgs capacity; 21 in. / 533.4 mm depth.)	Yes	-
	SRSHELF2PTM	SmartRack 2U Cantilever Toolless Mount Fixed Shelf (50 lbs /22.7 kgs capacity; 18 in./457 mm depth)	Yes	-
	SRSHELF2PUNIV	SmartRack Universal-Mount Steel Rack Shelf - 2U, Vented, 21.7 in. Deep, Holds up to 100 lb. (45 kg)	Yes	Yes
	SRSHELF2PX2	SmartRack 2U Cantilever Double-sided Fixed Shelf (60 lbs / 27.2 kgs capacity each side; 36 in./914 mm depth)	Yes	-
	SRSHELF4PHD	SmartRack Heavy-Duty Fixed Shelf (250 lbs / 113.4 kgs capacity; 26 in/660 mm depth)	Yes	-
	SRSHELF4PHDTM	SmartRack Fixed Heavy-Duty Toolless Mount Shelf (250 lbs / 113.4 kgs capacity; 26 in./660 mm depth)	Yes	-
	SRSHELF4PHDVENT	SmartRack Adjustable-Deep Steel Rack Shelf - 1U, Vented, 250 lb. (113 kg) Capacity	Yes	-
	SRSHELF4PKYBD	SmartRack Keyboard Shelf (25 lbs / 11.3 kgs capacity; 16 in / 406 mm depth)	Yes	-
	SRSHELF4PSL	SmartRack Standard Sliding Shelf (50 lbs / 22.7 kgs capacity; 28.3 in/719 mm depth)	Yes	-
SRSHELF4PSLHD	SmartRack Heavy-Duty Sliding Shelf (200 lbs / 90.7 kgs capacity; 28.3 in/719 mm depth.)	Yes	-	
SRSHELF4PSLVENT	SmartRack Sliding Steel Rack Shelf - 1U, Vented, 28.3 in. Deep, Holds up to 50 lb. (23 kg)	Yes	-	
SRWSHELF4P1U	Cantilevered Steel Rack Shelf - 1U, Vented, Integrated Cable Rings, 14.2 in. Deep, Holds up to 50 lbs (22.2 kgs)	Yes	Yes	
	SRWO4UBRKTSHLF	4U Wall-Mount Bracket with Shelf for Small Switches and Patch Panels, Hinged	-	Yes


Cooling

Part number	Description	
	SRXCOOL12KEU	Portable Air Conditioning Unit for Server Rooms - 12,000 BTU (3.5kW), 230V, R290, Schuko CEE7 Input
	SRXCOOL12KEUB	Portable Air Conditioning Unit for Server Rooms 12,000 BTU (3.5kW), 230V, R290, British Input
	SRCOOLNET2LX	LX Platform SNMP/Web Interface Module - Remote Cooling Management for Select Models


Wall Brackets

	Part number	Description	Enclosure	
			Floor-Standing Open-Frames	Wall-Mount
	SRWALLBRKT2U	SmartRack 2U Vertical Wall-Mount Rack Bracket	-	Yes
	SRWALLBRKT4U	SmartRack 4U Vertical Wall-Mount Rack Bracket	-	Yes
	SRWALLBRKT6U	SmartRack 6U Vertical Wall-Mount Rack Bracket	-	Yes


Fiber Routing System

	Part number	Description
	SRFC10CAP	Toolless End Cap for Fiber Routing System, 240 mm
	SRFC10CPL10	Toolless Coupler for Fiber Routing System, 240 mm
	SRFC10JUNT	Toolless Horizontal 90-Degree T-Junction for Fiber Routing System, 240 mm
	SRFC10STR48	Toolless Straight Channel Section for Fiber Routing System, 240 x 120 x 1220 mm
	SRFC4WTRFL	Toolless Movable Waterfall Adapter Kit for Fiber Routing System, 130 mm
	SRFC4WTRFL36	Toolless Movable Waterfall Adapter Kit with 36 in. Pipe for Fiber Routing System, 130 mm


Roof Mounted Cable Routing

	Part number	Description	Enclosure	
			Floor-Standing Open-Frames	Wall-Mount
	SRCABLELADDER	SmartRack 10-ft. x 1-ft. (3 m x 0.3 m) Cable Ladder, 2 sections - SRCABLETRAY/SRLADDERATTACH needed	Yes	-
	SRCABLETRAY	SmartRack Roof-Mounted Cable Trough - Provides cable routing and power/data cable segregation	Yes	-
	SRCABLETRAY1U	SmartRack 1U Horizontal Cable Management Tray	Yes	-
	SRCABLETRAYEXP	SmartRack Roof-Mounted Cable Trough Vertical Expansion Plates - Requires SRCABLETRAY	Yes	-

Shipping Cases

	Part number	Description
	SRCASE10U	10U ABS Server Rack Equipment Shipping Case
	SRCASE2U	2U ABS Server Rack Equipment Shipping Case
	SRCASE4U	4U ABS Server Rack Equipment Shipping Case
	SRCASE6U	6U ABS Server Rack Equipment Shipping Case

PDU Accessories

	Part number	Description	Enclosure	
			Floor-Standing Open-Frames	Wall-Mount
	SRPDU2PBRKT	Vertical PDU Mounting Bracket Accessory Kit for 2-Post and 4-Post Open Frame Racks		

Console KVMs

Control and Manage Multiple PCs and Servers from a Single Keyboard/Video/Mouse.
Increase efficiency. Prevent downtime. Save rack space and money.



Key points:

- Keyboard, Touchpad and color LDC monitor in 1U
- 8 or 16 KVM ports
- Multi-platform - VGA/HDMI/DisplayPort
- With or without built-in IP Remote Access
- English, French and German keyboard support

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	KVM ports	Concurrent Users	PC/Server Connections	Video Supported	LCD	Peripheral Sharing	Cables/Cable Kits/SIUs
With a KVM Switch							
B020-U08-19-IP	8	1	VGA, USB	LCD: 1280x1024 Remote: 1920x1080	19"	-	P778-XXX
B020-U08-19-K	8	1	VGA, USB	1280x1024	19"	-	Included
B020-U16-19-IP	16	1	VGA, USB	LCD: 1280x1024 Remote: 1920x1080	19"	-	P778-XXX
B020-U16-19-IPF	16	1	VGA, USB French KB	LCD: 1280x1024 Remote: 1920x1080	19"	-	P778-XXX
B020-U16-19-IPG	16	1	VGA, USB German KB	LCD: 1280x1024 Remote: 1920x1080	19"	-	P778-XXX
B020-U16-19-K	16	1	VGA, USB	LCD: 1280x1024 External: 2048x1536	19"	-	(x8) P778-006 included
B020-U16-19-KF	16	1	VGA, USB French KB	LCD: 1280x1024 External: 2048x1536	19"	-	(x8) P778-006 included
B020-U16-19-KG	16	1	VGA, USB German KB	"LCD: 1280x1024 External: 2048x1536"	19"	-	(x8) P778-006 included
B030-008-17-IP	8	1	HDMI, USB	1920x1080	17"	-	P782-XXX-DH; U022-XXX
B030-DP08-17D	8	1	DisplayPort, USB	1920x1080	17"	-	P580-XXX; U022-XXX
B030-DP08-17DIP	8	1	DisplayPort, USB	1920x1080	17"	-	P580-XXX; U022-XXX
B030-DP16-17D	16	1	DisplayPort, USB	1920x1080	17"	-	P580-XXX; U022-XXX
B030-DP16-17DIP	16	1	DisplayPort, USB	1920x1080	17"	-	P580-XXX; U022-XXX
B040-008-19	8	1	VGA, USB, PS/2	1366x768	19"	-	P780-XXX
B040-016-19	16	1	VGA, USB, PS/2	1366x768	19"	-	P780-XXX
B070-008-19	8	1	VGA, USB, PS/2	1366x768	19"	-	B078-101-USB-1
B070-016-19	16	1	VGA, USB, PS/2	1366x768	19"	-	B078-101-USB-1
Without a KVM Switch							
B021-000-19	-	1	VGA, USB, PS/2	1366x768	19"	-	Included
B021-000-19-HD2	-	1	VGA/DVI, USB	1920x1080	19"	Yes Pass-through	Included
B021-SWHD-K	-	1	HDMI, USB	1920x1080	18.5"	Yes Pass-through	Included

Rackmount KVM Switches

Control and Manage Multiple PCs and Servers from a Single Keyboard/Video/Mouse. Increase efficiency. Prevent downtime. Save rack space and money.



Key points:

- 1U Rack-Mount
- 8/16/32 KVM ports
- Multi-platform - VGA/DVI/HDMI/DisplayPort
- With or without built-in IP Remote Access

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	KVM ports	Concurrent Users	PC/Server Connections	Video Supported	LCD	Peripheral Sharing	Cables/Cable Kits/SIUs
With Remote Access over IP							
B064-008-01-IPG	8	2 (1 Local + 1 Remote)	VGA, USB	1920x1200	-	Yes	B055-001-XXX
B064-016-01-IPG	16	2 (1 Local + 1 Remote)	VGA, USB	1920x1200	-	Yes	B055-001-XXX
B064-016-02-IPG	16	3 (1 Local + 2 Remote)	DVI, VGA, Serial, USB	1600x1200	-	Yes	B055-001-XXX
B064-016-04-IPG	16	5 (1 Local + 4 Remote)	DVI, VGA, Serial, USB	1600x1200	-	Yes	B055-001-XXX
B064-032-01-IPG	32	2 (1 Local + 1 Remote)	DVI, VGA, Serial, USB	1600x1200	-	Yes	B055-001-XXX
B064-032-02-IPG	32	3 (1 Local + 2 Remote)	DVI, VGA, Serial, USB	1600x1200	-	Yes	B055-001-XXX
B064-000-STN	1 port Remote-User Console Station	1	HDMI, USB	1920 x 1200 @60Hz	-	Yes	
Without Remote Access over IP							
B024-DPU08	8	1	DisplayPort, USB	4K	-	Yes	ADD P312-006
B024-DPU16	16	1	DisplayPort, USB	4K	-	Yes	P312-006
B024-H4U08	8	1	HDMI, USB	4K	-	Yes	P312-006
B024-H4U16	16	1	HDMI, USB	4K	-	Yes	P312-006

Secure NIAP KVM Switches

Lets you access multiple computers from a single console while protecting data from accidental or unauthorized transfer between them.



Key points:

- Physically separates the data channels passing through the KVM
- Requires physical access to push buttons on the KVM to switch
- Disables itself if the housing is opened (tamper-evident seals)
- Continuously clears keyboard buffer to prevent memory mining

Ideal for:

- Government
- Military
- Healthcare
- Private sector

Part number	KVM ports	Concurrent Users	PC/Server Connections	Video Supported	LCD	Peripheral Sharing	Cables/Cable Kits/SIUs
With Remote Access over IP							
B002-DP1A4-N4	4	1	DisplayPort, USB, Audio	4K	-	-	P783-XXX
B002-DP1AC4-N4	4	1	DisplayPort, USB, Audio, CAC	4K	-	Yes - only CAC	P783-XXX
B002-DP1AC8-N4	8	1	DisplayPort, USB, Audio, CAC	4K	-	Yes - only CAC	P783-XXX
B002-DP2A2-N4	2	1	DisplayPort, USB, Audio	4K	-	-	P783-XXX
B002-DP2A4-N4	4	1	DisplayPort, USB, Audio	4K	-	-	P783-XXX
B002-DP2AC2-N4	2	1	DisplayPort, USB, Audio, CAC	4K	-	-	P783-XXX
B002-DP2AC4-N4	2	1	DisplayPort, USB, Audio, CAC	4K	-	-	P783-XXX
B002-DV1A2-N4	2	1	DVI-I, USB, Audio	1560 X 1600	-	-	P560-XXX /U022-XXX
B002-DV1AC8-N4	8	1	DVI-I, USB, Audio, CAC	1561 X 1600	-	Yes - only CAC	P560-XXX/ U022-XXX
B002-DV2A4-N4	4	1	DVI-I, USB, Audio	1562 X 1600	-	-	P560-XXX/ U022-XXX
B002-DV2AC4-N4	4	1	DVI-I, USB, Audio, CAC	1563 X 1600	-	Yes - only CAC	P560-XXX/ U022-XXX
B002-H2A2-N4	2	1	HDMI, USB, Audio	4K	-	Yes - only CAC	P782-XXX/ U022-XXX
B002-H2A4-N4	4	1	HDMI, USB, Audio	4K	-	Yes - only CAC	P782-XXX/ U022-XXX
B002-H2AC2-N4	2	1	HDMI, USB, Audio, CAC	4K	-	Yes - only CAC	P782-XXX/ U022-XXX
B002-H2AC4-N4	4	1	HDMI, USB, Audio, CAC	4K	-	Yes - only CAC	P782-XXX/ U022-XXX
B002-HD1AC4-N4	4	1	HDMI, USB, Audio, CAC	4K	-	-	P782-XXX/ U022-XXX

CAC: Common Access Card



Looking for Desktop KVM Switches?

Go to the Work from anywhere (WFA), Retail & Education section, page 63.

Console Servers

Secure in-band and out-of-band remote access to serial- and network-connected devices.



Key points:

- Manage routers, UPS systems and other serial-based equipment from anywhere 24/7
- Validated to meet FIPS 140-2 standards to ensure utmost protection of private data
- Dual Gigabit Ethernet ports for primary network connection and automatic failover
- Designed for standard Cat5e/6 patch cable when connecting to Cisco devices



Ideal for:




- Network Closet
- Server Room
- Data Center
- White Space

Part number	Number of Ports	Concurrent Users	Connections		Network Compatibility	Memory	Port Selection	Built-in Modem
			Connector A	Connector B				
B093-004-2E4U	4	Multi-users	2x RJ45 (F)	RJ45 (F) USB-A (F)	1 Gbps	4 Gbps	GUI	-
B093-008-2E4U	8	Multi-users	2x RJ45 (F)	2x RJ45 (F) 4x USB-A (F)	1 Gbps	4 Gbps	GUI	-
B093-008-2E4U-M	8	Multi-users	RJ11 (F) 2x RJ45 (F) 2x SFP+ (F)	8x RJ45 (F) 4x USB-A (F)	1 Gbps	4 Gbps	GUI	-
B097-016	16	Multi-users	RJ45 (F) 2x USB-A (F)	16x RJ45 (F) 2x RJ45 (F)	1 Gbps	4 Gbps	CLI/GUI	-
B097-048	48	Multi-users	RJ45 (F) 2x USB-A (F)	48x RJ45 (F) 2x RJ45 (F)	1 Gbps	4 Gbps	CLI/GUI	-
B098-016	16	Multi-users	2x USB-A (F) RJ45 (F) SD (F) RJ11 (F)	16x RJ45 (F) 2x RJ45 (F) 2x SFP (F)	1 Gbps	16 Gbps	CLI/GUI	Yes
B098-048	48	Multi-users	2x USB-A (F) RJ45 (F) SD (F) RJ11 (F)	48x RJ45 (F) 2x RJ45 (F) 2x SFP (F)	1 Gbps	16 Gbps	CLI/GUI	Yes

KVM Accessories

Accessories to connect a KVM to a server , PC or AV kit

	Part number	Description
KVM accessories and cables		
	B019-000	2-Post Rack-Mount Bracket, B020, B021, B040, and B070 Consoles & KVM Consoles
	B015-000	USB to PS/2 Adapter for Keyboard and Mouse
B002 Series Secure KVM cables/kits		
	P782-006-DH	HDMI/DVI/USB KVM Cable Kit,1.83 m
	P782-006-HA	HDMI KVM Cable Kit - 4K HDMI, USB 2.0, 3.5 mm Audio (M/M), Black, 1.83 m
	P782-010-DH	HDMI/DVI/USB KVM Cable Kit, 3.05 m - USB 2.0, 4K 60Hz
	P782-010-HaA	HDMI KVM Cable Kit - 4K HDMI, USB 2.0, 3.5 mm Audio (M/M), Black, 3.05 m
	P783-006	DisplayPort KVM Cable Kit, 3 in 1 - 4K DisplayPort, USB, 3.5 mm Audio (3xM/3xM), 4:4:4, 1.83 m, Black
	P783-006-DP	Dual DisplayPort KVM Cable Kit - DP, USB, 3.5 mm Audio (3xM/3xM) + DP (M/M), 4K, 4:4:4, 1.83 m, Black
	P783-006-DPU	DisplayPort KVM Cable Kit - DP, USB, 3.5 mm Audio (3xM/3xM) + USB (M/M) + DP (M/M), 4K, 1.83 m, Black
	P783-006-U	DisplayPort KVM Cable Kit - DP, USB, 3.5 mm Audio (3xM/3xM) + USB (M/M), 4K, 4:4:4, 1.83 m, Black
	P560-006	DVI Dual Link Cable, Digital TMDS Monitor Cable (DVI-D M/M), 1.83 m
	P560-010	DVI Dual Link Cable, Digital TMDS Monitor Cable (DVI-D M/M), 3.05 m
	U022-006	USB 2.0 A/B Cable (M/M), 1.83 m
	U022-010	USB 2.0 A/B Cable (M/M), 3.05 m
	B005 Series KVM cable kits	
	P785-DPKIT06	DisplayPort KVM Cable Kit for Tripp Lite B005-DPUA2-K and B005-DPUA4 KVM, 4K DP, USB 3.2, 3.5 mm, 1.83 m
	P785-DPKIT10	DisplayPort KVM Cable Kit for Tripp Lite B005-DPUA2-K and B005-DPUA4 KVM, 4K DP, USB 3.2, 3.5 mm, 3.05 m
	P785-HKIT06	HDMI KVM Cable Kit for Tripp Lite B005-HUA2-K and B005-HUA4 KVM, 4K HDMI, USB 3.2 Gen 1, 3.5 mm, 1.83 m
	P785-HKIT10	HDMI KVM Cable Kit for Tripp Lite B005-HUA2-K and B005-HUA4 KVM, 4K HDMI, USB 3.2 Gen 1, 3.5 mm, 3.05 m
B020 Series KVM Cable Kits		
	P772-015	Daisy Chain Cable for NetDirector KVM Switch B020-Series and KVM B022-Series, 4.57 m
	P778-006	USB/PS2 Combo Cable for NetDirector KVM Switches B020-U08/U16, 1.83 m
	P778-006-DP	VGA to DisplayPort and USB-A Adapter Cable Kit for Tripp Lite B020-U KVM, 1.8 m
	P778-010	USB/PS2 Combo Cable for NetDirector KVM Switch B020-U08/U16, 3.05 m
	P778-015	USB/PS2 Combo Cable for NetDirector KVM Switches B020-U08/U16 , 4.57 m
B024 Series KVM Cables		
	P580-006	DisplayPort Cable with Latches, 4K @ 60 Hz, (M/M), 1.83 m
	P580-010	DisplayPort Cable with Latches, 4K @ 60 Hz, (M/M), 3.05 m
	P569-006	High Speed HDMI Cable with Ethernet, UHD 4K, Digital Video with Audio (M/M),1.83 m
	P569-010	High Speed HDMI Cable with Ethernet, UHD 4K, Digital Video with Audio (M/M), 3.05 m
	P312-001	3.5mm Mini Stereo Audio Cable for Microphones, Speakers and Headphones (M/M), 0.31 m
	P312-006	3.5mm Mini Stereo Audio Cable for Microphones, Speakers and Headphones (M/M), 1.83 m
	U022-006	USB 2.0 A/B Cable (M/M), 1.83 m
	U022-010	USB 2.0 A/B Cable (M/M), 3.05 m

	Part number	Description
B040 Series KVM Cable Kits		
	P780-006	USB/PS2 Combo Cable Kit for NetController KVM Switches B040-Series , 1.83 m
	P780-010	USB/PS2 Combo Cable Kit for NetController KVM Switches B040-Series, 3.05 m
	P780-015	USB/PS2 Combo Cable Kit for NetController KVM Switches B040-Series, 4.57 m
	P781-010	Daisy Chain Cable for NetController KVM Switches B040-Series, 3.05 m
B064 Series KVM Server Interface Units (SIU)		
	B055-001-C	NetDirector USB-C Server Interface Unit with Virtual Media Support (B064 Series)
	B055-001-PS2	NetDirector PS/2 Server Interface Unit (B064-Series)
	B055-001-SER	NetDirector PS/2 Server Interface Unit (B064-Series)
	B055-001-UDP	NetDirector DisplayPort USB Server Interface Unit with Virtual Media and CAC Support (B064-IPG Series)
	B055-001-UDV	NetDirector DVI USB Server Interface Unit with Virtual Media and CAC Support (B064-IPG Series), USB and DVI
	B055-001-UHD	NetDirector HDMI USB Server Interface Unit with Virtual Media and CAC Support (B064-IPG Series), USB and HDMI
	B055-001-USB	NetDirector USB Server Interface Unit (B064-Series)
	B055-001-USB-V2	NetDirector USB Server Interface Unit with Virtual Media Support (B064-Series)
	B055-001-USB-VA	NetDirector USB Server Interface Unit with Virtual Media Support and Audio (B064-IPG Series)
	B055-001-UV2CAC	NetDirector USB Server Interface Unit with Virtual Media & CAC Support (B064-Series)
B070 & B072 Series KVM Server Interface Units (SIU)		
	B078-101-PS2	NetCommander PS/2 Server Interface Unit (SIU)
	B078-101-USB-1	NetCommander USB Server Interface Unit (SIU) - Single
	B078-101-USB2	NetCommander USB Server Interface Unit (SIU) with Virtual Media up to 12Mbps

Copper Patch Panels

PoE+-compliant patch panel manages and organizes data/power cable connections in your high-density network.



Key points:

- 12,24 & 48 port options
- 1U & 2U options
- Punchdown, Feed-through, Keystone
- POE options

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Number of Ports	Height (U)	Product Type	Technology				Cable		PoE Type
				Cat5/5e	Cat6	Cat6a	Cat8	Connector A (Front)	Connector B (Rear)	
Wall-Mount										
N050-012	12	0U	-	Yes	-	-	-	RJ45 (F)	110 IDC	Type 2 PoE+ (30W)
N250-012	12	0U	Punchdown	Yes	Yes	-	-	RJ45 (F)	110 IDC	Type 2 PoE+ (30W)
N250-P12	12	0U	Punchdown	Yes	Yes	-	-	RJ45 (F)	110 IDC	Type 4 PoE++ (100W)
Rack-Mount										
N052-024	24	1U	Punchdown	Yes	-	-	-	RJ45 (F)	110 IDC	Type 2 PoE+ (30W)
N052-P24	24	1U	Punchdown	Yes	-	-	-	RJ45 (F)	110 IDC	Type 4 PoE++ (100W)
N052-048	48	2U	Punchdown	Yes	-	-	-	RJ45 (F)	110 IDC	Type 2 PoE+ (30W)
N062-012-KJ	12	1U	Blank	Keystone Jack Cutout						-
N062-016-KJ	16	1U	Blank	Keystone Jack Cutout						-
N062-024-KJ	24	2U	Blank	Keystone Jack Cutout						-
N252-012	12	1U	Punchdown	Yes	Yes	-	-	RJ45 (F)	110 IDC	Type 2 PoE+ (30W)
N252-024	24	1U	Punchdown	Yes	Yes	-	-	RJ45 (F)	110 IDC	Type 2 PoE+ (30W)
N252-P24	24	1U	Punchdown	Yes	Yes	-	-	RJ45 (F)	110 IDC	Type 4 PoE++ (100W)
N252-048-1U	48	1U	Punchdown	Yes	Yes	-	-	RJ45 (F)	110 IDC	Type 2 PoE+ (30W)
N252-048	48	2U	Punchdown	Yes	Yes	-	-	RJ45 (F)	110 IDC	Type 2 PoE+ (30W)
N252-024-6A	24	1U	Punchdown	Yes	Yes	Yes	-	RJ45 (F)	110 IDC	Type 4 PoE++ (100W)
N054-024	24	1U	Feed-Through	Yes	-	-	-	RJ45 (F)	RJ45 (F)	Type 4 PoE++ (100W)
N254-024	24	1U	Feed-Through	Yes	Yes	-	-	RJ45 (F)	RJ45 (F)	Type 4 PoE++ (100W)
N254-024-6A	24	1U	Feed-Through	Yes	Yes	Yes	-	RJ45 (F)	RJ45 (F)	Type 4 PoE++ (100W)
Shielding										
N062-024-KJ-SH	24	1U	Blank	Keystone Jack Cutout						-
N252-024-6A-SH	24	1U	Punchdown	Yes	Yes	Yes	-	RJ45 (F)	110 IDC	Type 4 PoE++ (100W)
N254-024-SH	24	1U	Feed-Through	Yes	Yes	-	-	RJ45 (F)	RJ45 (F)	Type 4 PoE++ (100W)
N254-024-SH-6A	24	1U	Feed-Through	Yes	Yes	Yes	-	RJ45 (F)	RJ45 (F)	Type 4 PoE++ (100W)
N254-048-SH-6A	48	1U	Feed-Through	Yes	Yes	Yes	-	RJ45 (F)	RJ45 (F)	Type 4 PoE++ (100W)
Offset										
N254-024-6A-OF	24	1U	Feed-Through	Yes	Yes	Yes	-	RJ45 (F)	RJ45 (F)	Type 4 PoE++ (100W)

Accessories



Part number	Description	Height (U)
N060-001	SmartRack 1U Hinged Wall-Mount Patch Panel Bracket	1U
N060-004	SmartRack 4U Hinged Wall-Mount Patch Panel Bracket, TAA	4U

Copper Couplers

Extend the length of copper patch cords.



Key points:

- Backwards compatible
- Gold contacts
- Protective shielded housing reduces EMI/RFI interference

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Technology				Cable		Angled	Color		PoE Type
	Cat5/5e	Cat6	Cat6a	Cat8	Connector A (Front)	Connector B (Rear)		Connector	Connector	
N234-001-WH	Yes	Yes	-	-	RJ45 (F)	RJ45 (F)	-	White	-	Type 4 PoE++ (100W)
N235-001	Yes	Yes	-	-	RJ45 (F)	RJ45 (F)	-	Black	Black	Type 4 PoE++ (100W)
N235-001-6A	Yes	Yes	Yes	-	RJ45 (F)	RJ45 (F)	-	White	White	Type 4 PoE++ (100W)
Shielding										
N032-001	Yes	-	-	-	RJ45 (F)	RJ45 (F)	-	Silver	Silver	
N235-001-SH-6A	Yes	Yes	Yes	-	RJ45 (F)	RJ45 (F)	-	Silver	Silver	Type 4 PoE++ (100W)
N235-001-SH-D	Yes	Yes	-	-	RJ45 (F)	RJ45 (F)	90° down	Silver	Silver	
N235-001-WH	Yes	Yes	-	-	RJ45 (F)	RJ45 (F)	-	White	White	Type 4 PoE++ (100W)
N235-001-WH-6AD	Yes	Yes	Yes	-	RJ45 (F)	RJ45 (F)	90° down	White	White	

Cat5e Copper Cables

Used for 1000Base-T (1Gbps Ethernet) networks and can distribute data, video and telephone signals.



Key points:

- Provides EMI/RFI shielding in Ethernet networks
- Shielded RJ45 connectors with gold-plated contacts
- Molded boot for extra strain-relief and durability
- Type 2 PoE+

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Shielding		Length	Network compatibility	Conductor material	Color
	Yes /	Type				
Snagless Molded						
N001-001-BL	No	UTP	31 cm	1 Gbps	Stranded Copper	Blue
N001-002-BL	No	UTP	61 cm	1 Gbps	Stranded Copper	Blue
N001-003-BL	No	UTP	91 cm	1 Gbps	Stranded Copper	Blue
N001-004-BL	No	UTP	1,22 m	1 Gbps	Stranded Copper	Blue
N001-006-BL	No	UTP	1,83 m	1 Gbps	Stranded Copper	Blue
N001-007-BL	No	UTP	2,13 m	1 Gbps	Stranded Copper	Blue
N001-007-GY	No	UTP	2,13 m	1 Gbps	Stranded Copper	Gray
N001-008-BL	No	UTP	2,43 m	1 Gbps	Stranded Copper	Blue
N001-010-BL	No	UTP	3,05 m	1 Gbps	Stranded Copper	Blue
N001-012-GY	No	UTP	3,66 m	1 Gbps	Stranded Copper	Gray
N001-014-BL	No	UTP	4,27 m	1 Gbps	Stranded Copper	Blue
N001-015-BL	No	UTP	4,57 m	1 Gbps	Stranded Copper	Blue
N001-020-BL	No	UTP	6,09 m	1 Gbps	Stranded Copper	Blue
N001-025-BL	No	UTP	7,62 m	1 Gbps	Stranded Copper	Blue
N001-030-GY	No	UTP	9,14 m	1 Gbps	Stranded Copper	Gray
N001-040-BL	No	UTP	12,19 m	1 Gbps	Stranded Copper	Blue
N001-050-BL	No	UTP	15,24 m	1 Gbps	Stranded Copper	Blue
N001-075-BL	No	UTP	22,86 m	1 Gbps	Stranded Copper	Blue
N001-100-BL	No	UTP	30,5 m	1 Gbps	Stranded Copper	Blue
N001-150-GY	No	UTP	45,72 m	1 Gbps	Stranded Copper	Gray

* Other colors available on demand. Please contact your local Eaton expert to get more details.

Part number	Shielding		Length	Network compatibility	Conductor material	Color
	Yes / No	Type				
Molded						
N002-001-BL	No	UTP	31 cm	1 Gbps	Stranded Copper	Blue
N002-001-GY	No	UTP	31 cm	1 Gbps	Stranded Copper	Gray
N002-002-BL	No	UTP	61 cm	1 Gbps	Stranded Copper	Blue
N002-002-GY	No	UTP	61 cm	1 Gbps	Stranded Copper	Gray
N002-003-BL	No	UTP	91 cm	1 Gbps	Stranded Copper	Blue
N002-003-GY	No	UTP	91 cm	1 Gbps	Stranded Copper	Gray
N002-004-BL	No	UTP	1,22 m	1 Gbps	Stranded Copper	Blue
N002-004-GY	No	UTP	1,22 m	1 Gbps	Stranded Copper	Gray
N002-005-BL	No	UTP	1,52 m	1 Gbps	Stranded Copper	Blue
N002-005-GY	No	UTP	1,52 m	1 Gbps	Stranded Copper	Gray
N002-006-BL	No	UTP	1,83 m	1 Gbps	Stranded Copper	Blue
N002-007-BL	No	UTP	2,13 m	1 Gbps	Stranded Copper	Blue
N002-007-GY	No	UTP	2,13 m	1 Gbps	Stranded Copper	Gray
N002-010-BL	No	UTP	3,05 m	1 Gbps	Stranded Copper	Blue
N002-010-GY	No	UTP	3,05 m	1 Gbps	Stranded Copper	Gray
N002-012-GY	No	UTP	3,66 m	1 Gbps	Stranded Copper	Gray
N002-014-BL	No	UTP	4,27 m	1 Gbps	Stranded Copper	Blue
N002-020-BL	No	UTP	6,09 m	1 Gbps	Stranded Copper	Blue
N002-020-GY	No	UTP	6,09 m	1 Gbps	Stranded Copper	Gray
N002-025-GY	No	UTP	7,62 m	1 Gbps	Stranded Copper	Gray
N002-030-BL	No	UTP	9,14 m	1 Gbps	Stranded Copper	Blue
N002-050-GY	No	UTP	15,24 m	1 Gbps	Stranded Copper	Gray
N002-075-GY	No	UTP	22,86 m	1 Gbps	Stranded Copper	Gray
N105-007-GY	Yes	STP	2,13 m	1 Gbps	Stranded Copper	Gray
N105-025-GY	Yes	STP	7,62 m	1 Gbps	Stranded Copper	Gray
N105-050-GY	Yes	STP	15,24 m	1 Gbps	Stranded Copper	Gray
N105-100-GY	Yes	STP	30,5 m	1 Gbps	Stranded Copper	Gray
Outdoor-Rated						
N007-150-GY	No	UTP	45,72 m	1 Gbps	Solid Copper	Gray
Crossover						
N010-007-GY	No	UTP	2,13 m	1 Gbps	Stranded Copper	Gray
N010-010-GY	No	UTP	3,05 m	1 Gbps	Stranded Copper	Gray

Cat6 Copper Cables

Ideal for connecting high-speed network components, such as computers, printers, video game systems, Blu-ray™ players, copy machines, routers and modems, in a home or office Cat5/5e/6 application.



Key points:

- Shielding
- Stranded or Solid Copper
- Various colors in standard*
- From 15 up to +60m

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Shielding		Length	Network compatibility	Conductor material	Color
	Yes / No	Type				
Molded						
N200-001-BK	No	UTP	31 cm	1 Gbps	Stranded Copper	Black
N200-001-BL	No	UTP	31 cm	1 Gbps	Stranded Copper	Blue
N200-002-GY	No	UTP	61 cm	1 Gbps	Stranded Copper	Gray
N200-003-BK	No	UTP	91 cm	1 Gbps	Stranded Copper	Black
N200-003-BL	No	UTP	91 cm	1 Gbps	Stranded Copper	Blue
N200-003-GY	No	UTP	91 cm	1 Gbps	Stranded Copper	Gray
N200-005-BK	No	UTP	1,52 m	1 Gbps	Stranded Copper	Black
N200-005-BL	No	UTP	1,52 m	1 Gbps	Stranded Copper	Blue
N200-006-BK	No	UTP	1,83 m	1 Gbps	Stranded Copper	Black
N200-006-BL	No	UTP	1,83 m	1 Gbps	Stranded Copper	Blue
N200-006-GY	No	UTP	1,83 m	1 Gbps	Stranded Copper	Gray
N200-007-BK	No	UTP	2,13 m	1 Gbps	Stranded Copper	Black
N200-007-BL	No	UTP	2,13 m	1 Gbps	Stranded Copper	Blue
N200-010-BK	No	UTP	3,05 m	1 Gbps	Stranded Copper	Black
N200-010-BL	No	UTP	3,05 m	1 Gbps	Stranded Copper	Blue
N200-010-GY	No	UTP	3,05 m	1 Gbps	Stranded Copper	Gray
N200-014-BL	No	UTP	4,27 m	1 Gbps	Stranded Copper	Blue
N200-015-BL	No	UTP	4,57 m	1 Gbps	Stranded Copper	Blue
N200-020-BK	No	UTP	6,09 m	1 Gbps	Stranded Copper	Black
N200-035-GY	No	UTP	10,67 m	1 Gbps	Stranded Copper	Gray
N200-075-BL	No	UTP	22,86 m	1 Gbps	Stranded Copper	Blue
N200-100-BK	No	UTP	30,5 m	1 Gbps	Stranded Copper	Black
N125-007-GY	Yes	FTP	2,13 m	1 Gbps	Stranded Copper	Gray
N125-050-GY	Yes	FTP	15,24 m	1 Gbps	Stranded Copper	Gray
Molded Ultra-Slim						
N200-UR6N-BL	No	UTP	15,24 cm	1 Gbps	Stranded Copper	Blue
N200-UR01-BL	No	UTP	31 cm	1 Gbps	Stranded Copper	Blue
N200-UR03-BL	No	UTP	91 cm	1 Gbps	Stranded Copper	Blue
N200-UR05-BL	No	UTP	1,52 m	1 Gbps	Stranded Copper	Blue
N200-UR07-BL	No	UTP	2,13 m	1 Gbps	Stranded Copper	Blue

Molded - Angled

N204-001-BL-LA	No	UTP	31 cm	Left	1 Gbps	Stranded Copper	Blue
N204-001-BL-RA	No	UTP	31 cm	Right	1 Gbps	Stranded Copper	Blue
N204-001-BL-UD	No	UTP	31 cm	Up/Down	1 Gbps	Stranded Copper	Blue
N204-003-BL-DN	No	UTP	91 cm	Down	1 Gbps	Stranded Copper	Blue
N204-003-BL-LA	No	UTP	91 cm	Left	1 Gbps	Stranded Copper	Blue
N204-003-BL-RA	No	UTP	91 cm	Right	1 Gbps	Stranded Copper	Blue
N204-003-BL-UD	No	UTP	91 cm	Up/Down	1 Gbps	Stranded Copper	Blue
N204-003-BL-UP	No	UTP	91 cm	Up	1 Gbps	Stranded Copper	Blue
N204-005-BL-DN	No	UTP	1,52 m	Down	1 Gbps	Stranded Copper	Blue
N204-005-BL-LA	No	UTP	1,52 m	Left	1 Gbps	Stranded Copper	Blue
N204-005-BL-RA	No	UTP	1,52 m	Right	1 Gbps	Stranded Copper	Blue
N204-005-BL-UP	No	UTP	1,52 m	Up	1 Gbps	Stranded Copper	Blue
N204-010-BL-DN	No	UTP	3,05 m	Down	1 Gbps	Stranded Copper	Blue
N204-010-BL-LA	No	UTP	3,05 m	Left	1 Gbps	Stranded Copper	Blue
N204-010-BL-RA	No	UTP	3,05 m	Right	1 Gbps	Stranded Copper	Blue
N204-010-BL-UP	No	UTP	3,05 m	Up	1 Gbps	Stranded Copper	Blue
N204-015-BL-DN	No	UTP	4,57 m	Down	1 Gbps	Stranded Copper	Blue
N204-015-BL-RA	No	UTP	4,57 m	Right	1 Gbps	Stranded Copper	Blue
N204-015-BL-UP	No	UTP	4,57 m	Up	1 Gbps	Stranded Copper	Blue
N204-020-BL-RA	No	UTP	6,09 m	Right	1 Gbps	Stranded Copper	Blue

Molded Slim - Angled

N204-S01-BL-DN	No	UTP	31 cm	Down	1 Gbps	Stranded Copper	Blue
N204-S01-BL-RA	No	UTP	31 cm	Right	1 Gbps	Stranded Copper	Blue
N204-S01-BL-UD	No	UTP	31 cm	Up/Down	1 Gbps	Stranded Copper	Blue
N204-S01-BL-UP	No	UTP	31 cm	Up	1 Gbps	Stranded Copper	Blue
N204-S02-BL-DN	No	UTP	61 cm	Down	1 Gbps	Stranded Copper	Blue
N204-S02-BL-RA	No	UTP	61 cm	Right	1 Gbps	Stranded Copper	Blue
N204-S02-BL-UP	No	UTP	61 cm	Up	1 Gbps	Stranded Copper	Blue
N204-S03-BL-DN	No	UTP	91 cm	Down	1 Gbps	Stranded Copper	Blue
N204-S03-BL-LA	No	UTP	91 cm	Left	1 Gbps	Stranded Copper	Blue
N204-S03-BL-RA	No	UTP	91 cm	Right	1 Gbps	Stranded Copper	Blue
N204-S03-BL-UD	No	UTP	91 cm	Up/Down	1 Gbps	Stranded Copper	Blue
N204-S03-BL-UP	No	UTP	91 cm	Up	1 Gbps	Stranded Copper	Blue
N204-S05-BL-DN	No	UTP	1,52 m	Down	1 Gbps	Stranded Copper	Blue
N204-S05-BL-LA	No	UTP	1,52 m	Left	1 Gbps	Stranded Copper	Blue
N204-S05-BL-RA	No	UTP	1,52 m	Right	1 Gbps	Stranded Copper	Blue
N204-S05-BL-UP	No	UTP	1,52 m	Up	1 Gbps	Stranded Copper	Blue
N204-S07-BL-RA	No	UTP	2,13 m	Right	1 Gbps	Stranded Copper	Blue
N204-S07-BL-UP	No	UTP	2,13 m	Up	1 Gbps	Stranded Copper	Blue
N204-S10-BL-DN	No	UTP	3,05 m	Down	1 Gbps	Stranded Copper	Blue
N204-S10-BL-LA	No	UTP	3,05 m	Left	1 Gbps	Stranded Copper	Blue
N204-S10-BL-RA	No	UTP	3,05 m	Right	1 Gbps	Stranded Copper	Blue
N204-S10-BL-UD	No	UTP	3,05 m	Up/Down	1 Gbps	Stranded Copper	Blue
N204-S10-BL-UP	No	UTP	3,05 m	Up	1 Gbps	Stranded Copper	Blue
N204-S15-BL-LA	No	UTP	4,57 m	Left	1 Gbps	Stranded Copper	Blue
N204-S15-BL-UD	No	UTP	4,57 m	Up/Down	1 Gbps	Stranded Copper	Blue
N204-S20-BL-DN	No	UTP	6,09 m	Down	1 Gbps	Stranded Copper	Blue
N204-S20-BL-UP	No	UTP	6,09 m	Up	1 Gbps	Stranded Copper	Blue

Part number	Shielding		Length	Network compatibility	Conductor material	Color
	Yes / No	Type				
Snagless Molded						
N201-06N-BK	No	UTP	15,24 cm	1 Gbps	Stranded Copper	Black
N201-06N-BL	No	UTP	15,24 cm	1 Gbps	Stranded Copper	Blue
N201-001-BK	No	UTP	31 cm	1 Gbps	Stranded Copper	Black
N201-001-BL	No	UTP	31 cm	1 Gbps	Stranded Copper	Blue
N201-001-GY	No	UTP	31 cm	1 Gbps	Stranded Copper	Gray
N201-002-BK	No	UTP	61 cm	1 Gbps	Stranded Copper	Black
N201-002-BL	No	UTP	61 cm	1 Gbps	Stranded Copper	Blue
N201-002-GY	No	UTP	61 cm	1 Gbps	Stranded Copper	Gray
N201-003-BK	No	UTP	91 cm	1 Gbps	Stranded Copper	Black
N201-003-BL	No	UTP	91 cm	1 Gbps	Stranded Copper	Blue
N201-003-GY	No	UTP	91 cm	1 Gbps	Stranded Copper	Gray
N201-004-BL	No	UTP	1,22 m	1 Gbps	Stranded Copper	Blue
N201-005-BK	No	UTP	1,52 m	1 Gbps	Stranded Copper	Black
N201-005-BL	No	UTP	1,52 m	1 Gbps	Stranded Copper	Blue
N201-005-GY	No	UTP	1,52 m	1 Gbps	Stranded Copper	Gray
N201-006-BK	No	UTP	1,83 m	1 Gbps	Stranded Copper	Black
N201-006-BL	No	UTP	1,83 m	1 Gbps	Stranded Copper	Blue
N201-006-GY	No	UTP	1,83 m	1 Gbps	Stranded Copper	Gray
N201-007-BK	No	UTP	2,13 m	1 Gbps	Stranded Copper	Black
N201-007-BL	No	UTP	2,13 m	1 Gbps	Stranded Copper	Blue
N201-007-GY	No	UTP	2,13 m	1 Gbps	Stranded Copper	Gray
N201-008-BL	No	UTP	2,43 m	1 Gbps	Stranded Copper	Blue
N201-010-BK	No	UTP	3,05 m	1 Gbps	Stranded Copper	Black
N201-010-BL	No	UTP	3,05 m	1 Gbps	Stranded Copper	Blue
N201-010-GY	No	UTP	3,05 m	1 Gbps	Stranded Copper	Gray
N201-012-BL	No	UTP	3,66 m	1 Gbps	Stranded Copper	Blue
N201-014-BK	No	UTP	4,27 m	1 Gbps	Stranded Copper	Black
N201-014-BL	No	UTP	4,27 m	1 Gbps	Stranded Copper	Blue
N201-015-BK	No	UTP	4,57 m	1 Gbps	Stranded Copper	Black
N201-015-BL	No	UTP	4,57 m	1 Gbps	Stranded Copper	Blue
N201-015-GY	No	UTP	4,57 m	1 Gbps	Stranded Copper	Gray
N201-020-BK	No	UTP	6,09 m	1 Gbps	Stranded Copper	Black
N201-020-BL	No	UTP	6,09 m	1 Gbps	Stranded Copper	Blue
N201-020-GY	No	UTP	6,09 m	1 Gbps	Stranded Copper	Gray
N201-025-BK	No	UTP	7,62 m	1 Gbps	Stranded Copper	Black
N201-025-BL	No	UTP	7,62 m	1 Gbps	Stranded Copper	Blue
N201-030-BK	No	UTP	9,14 m	1 Gbps	Stranded Copper	Black
N201-030-BL	No	UTP	9,14 m	1 Gbps	Stranded Copper	Blue
N201-030-GY	No	UTP	9,14 m	1 Gbps	Stranded Copper	Gray
N201-035-BL	No	UTP	10,67 m	1 Gbps	Stranded Copper	Blue
N201-035-GY	No	UTP	10,67 m	1 Gbps	Stranded Copper	Gray
N201-050-BK	No	UTP	15,24 m	1 Gbps	Stranded Copper	Black
N201-050-BL	No	UTP	15,24 m	1 Gbps	Stranded Copper	Blue
N201-100-GY-P	No	UTP	30,5 m	1 Gbps	Solid Copper	Gray

Part number	Shielding		Length	Network compatibility	Conductor material	Color
	Yes / No	Type				
Flat						
N201-025-BL-FL	No	UTP	7,62 m	1 Gbps	Stranded Copper	Blue
Pack of 50 units						
N201-001-BL50BP	No	UTP	31 cm	1 Gbps	Stranded Copper	Blue
N201-002-BL50BP	No	UTP	61 m	1 Gbps	Stranded Copper	Blue
N201-003-BK50BP	No	UTP	91 cm	1 Gbps	Stranded Copper	Black
N201-003-BL50BP	No	UTP	91 cm	1 Gbps	Stranded Copper	Blue
N201-005-BL50BP	No	UTP	1,52 m	1 Gbps	Stranded Copper	Blue
N201-007-BK50BP	No	UTP	2,13 m	1 Gbps	Stranded Copper	Black
N201-007-BL50BP	No	UTP	2,13 m	1 Gbps	Stranded Copper	Blue
Snagless Molded Slim - Right-Angled						
N201-SR1-BL	No	UTP	31 cm	1 Gbps	Stranded Copper	Blue
N201-SR2-BK	No	UTP	61 cm	1 Gbps	Stranded Copper	Black
N201-SR2-BL	No	UTP	61 cm	1 Gbps	Stranded Copper	Blue
Snagless Slim						
N201-S6N-BL	No	UTP	15,24 cm	1 Gbps	Stranded Copper	Blue
N201-S6N-BK	No	UTP	15,24 cm	1 Gbps	Stranded Copper	Black
N201-S8N-BK	No	UTP	20,32 cm	1 Gbps	Stranded Copper	Black
N201-S01-BK	No	UTP	31 cm	1 Gbps	Stranded Copper	Black
N201-S01-BL	No	UTP	31 cm	1 Gbps	Stranded Copper	Blue
N201-S03-BL	No	UTP	91 cm	1 Gbps	Stranded Copper	Blue
N201-S05-BK	No	UTP	1,52 m	1 Gbps	Stranded Copper	Black
N201-S05-BL	No	UTP	1,52 m	1 Gbps	Stranded Copper	Blue
N201-S06-BK	No	UTP	1,83 m	1 Gbps	Stranded Copper	Black
N201-S07-BL	No	UTP	2,13 m	1 Gbps	Stranded Copper	Blue
Snagless						
N202-075-BL	No	UTP	22,86 m	1 Gbps	Stranded Copper	Blue
N202-100-BL	No	UTP	30,5 m	1 Gbps	Stranded Copper	Blue
N202-175-BL	No	UTP	53,34 m	1 Gbps	Stranded Copper	Blue
N202-200-BL	No	UTP	60,96 m	1 Gbps	Stranded Copper	Blue

Cat6a Copper Cables

Ethernet cable with Power over Ethernet (PoE) connects critical components, such as servers, switches, routers and hubs, in high-density 10Gbps networks.



Key points:

- Ideal for Your High-Density 10 Gbps Ethernet Network
- Premium Protection from EMI/RFI Line Noise
- Snagless RJ45 Male Connectors Add Extra Protection
- Type 2 PoE+ (30W)
- Shielding models available

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Shielding		Length	Network compatibility	Conductor material	Color
	Yes / No	Type				
Snagless Molded						
N261-06N-BL	No	UTP	15 cm	10 Gbps	Stranded Copper	Blue
N261-001-BL	No	UTP	31 cm	10 Gbps	Stranded Copper	Blue
N261-002-BL	No	UTP	61 cm	10 Gbps	Stranded Copper	Blue
N261-003-BL	No	UTP	91 cm	10 Gbps	Stranded Copper	Blue
N261-005-BL	No	UTP	1,52 m	10 Gbps	Stranded Copper	Blue
N261-005-BK	No	UTP	1,52 m	10 Gbps	Stranded Copper	Black
N261-006-BL	No	UTP	1,83 m	10 Gbps	Stranded Copper	Blue
N261-007-BL	No	UTP	2,13 m	10 Gbps	Stranded Copper	Blue
N261-010-BL	No	UTP	3,05 m	10 Gbps	Stranded Copper	Blue
N261-010-BK	No	UTP	3,05 m	10 Gbps	Stranded Copper	Black
N261-014-BK	No	UTP	4,27 m	10 Gbps	Stranded Copper	Black
N261-015-BL	No	UTP	4,57 m	10 Gbps	Stranded Copper	Blue
N261-020-BL	No	UTP	6,10 m	10 Gbps	Stranded Copper	Blue
N261-025-BL	No	UTP	7,62 m	10 Gbps	Stranded Copper	Blue
N261-025-BK	No	UTP	7,62 m	10 Gbps	Stranded Copper	Black
N261-050-BL	No	UTP	15,24 m	10 Gbps	Stranded Copper	Blue
N261-100-BL	No	UTP	30,49 m	10 Gbps	Stranded Copper	Blue
N261P-006-BL	Yes	F/UTP	1,83 m	10 Gbps	Solid Copper	Blue
Snagless Molded Slim						
N261-S6N-BL	No	UTP	15 cm	10 Gbps	Stranded Copper	Blue
N261-S07-BL	No	UTP	2,13 m	10 Gbps	Stranded Copper	Blue
Snagless Slim						
N262-S01-BL	Yes	STP	31 cm	10 Gbps	Stranded Copper	Blue
N262-S03-BL	Yes	STP	91 cm	10 Gbps	Stranded Copper	Blue
N262-S05-BL	Yes	STP	1,52 m	10 Gbps	Stranded Copper	Blue
N262-S06-BL	Yes	STP	1,83 m	10 Gbps	Stranded Copper	Blue
N262-S07-BL	Yes	STP	2,13 m	10 Gbps	Stranded Copper	Blue
N262-S10-BL	Yes	STP	3,05 m	10 Gbps	Stranded Copper	Blue
N262-S15-BL	Yes	STP	4,57 m	10 Gbps	Stranded Copper	Blue
N262-S25-BL	Yes	STP	7,62 m	10 Gbps	Stranded Copper	Blue

Part number	Shielding		Length	Network compatibility	Conductor material	Color
	Yes / No	Type				
Snagless						
N262-001-GY	Yes	STP	31 cm	10 Gbps	Stranded Copper	Gray
N262-001-BK	Yes	STP	31 cm	10 Gbps	Stranded Copper	Black
N262-002-GY	Yes	STP	61 cm	10 Gbps	Stranded Copper	Gray
N262-002-BK	Yes	STP	61 cm	10 Gbps	Stranded Copper	Black
N262-003-BL	Yes	STP	91 cm	10 Gbps	Stranded Copper	Blue
N262-003-GY	Yes	STP	91 cm	10 Gbps	Stranded Copper	Gray
N262-003-BK	Yes	STP	91 cm	10 Gbps	Stranded Copper	Black
N262-004-BK	Yes	STP	1,22 m	10 Gbps	Stranded Copper	Black
N262-005-BL	Yes	STP	1,52 m	10 Gbps	Stranded Copper	Blue
N262-005-GY	Yes	STP	1,52 m	10 Gbps	Stranded Copper	Gray
N262-005-BK	Yes	STP	1,52 m	10 Gbps	Stranded Copper	Black
N262-006-GY	Yes	STP	1,83 m	10 Gbps	Stranded Copper	Gray
N262-006-BK	Yes	STP	1,83 m	10 Gbps	Stranded Copper	Black
N262-007-GY	Yes	STP	2,13 m	10 Gbps	Stranded Copper	Gray
N262-007-BK	Yes	STP	2,13 m	10 Gbps	Stranded Copper	Black
N262-008-GY	Yes	STP	2,43 m	10 Gbps	Stranded Copper	Gray
N262-008-BK	Yes	STP	2,43 m	10 Gbps	Stranded Copper	Black
N262-010-BL	Yes	STP	3,05 m	10 Gbps	Stranded Copper	Blue
N262-010-GY	Yes	STP	3,05 m	10 Gbps	Stranded Copper	Gray
N262-010-BK	Yes	STP	3,05 m	10 Gbps	Stranded Copper	Black
N262-012-BK	Yes	STP	3,66 m	10 Gbps	Stranded Copper	Black
N262-014-BL	Yes	STP	4,27 m	10 Gbps	Stranded Copper	Blue
N262-014-BK	Yes	STP	4,27 m	10 Gbps	Stranded Copper	Black
N262-015-GY	Yes	STP	4,57 m	10 Gbps	Stranded Copper	Gray
N262-015-BK	Yes	STP	4,57 m	10 Gbps	Stranded Copper	Black
N262-020-BL	Yes	STP	6,10 m	10 Gbps	Stranded Copper	Blue
N262-020-BK	Yes	STP	6,10 m	10 Gbps	Stranded Copper	Black
N262-025-GY	Yes	STP	7,62 m	10 Gbps	Stranded Copper	Gray
N262-025-BK	Yes	STP	7,62 m	10 Gbps	Stranded Copper	Black
N262-030-BL	Yes	STP	9,14 m	10 Gbps	Stranded Copper	Blue
N262-030-BK	Yes	STP	9,14 m	10 Gbps	Stranded Copper	Black
N262-035-BK	Yes	STP	10,67 m	10 Gbps	Stranded Copper	Black

Cat8 Copper Cables

Shielded Cat8 cable connects 25G/40G equipment in your top-of-the-line 40GBase-T data center.



Key points:

- Up to 4 Times Faster Than Cat6a
- Supports Power over Ethernet (PoE) to Cut Down on Power Supplies
- Premium Protection from EMI/RFI Line Noise

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Shielding		Length	Network compatibility	Conductor material	Color
	Yes / No	Type				
Snagless						
N272-003-WH	Yes	S/FTP	91 cm	40 Gbps	Solid Copper	White
N272-006-WH	Yes	S/FTP	1,83 m	40 Gbps	Solid Copper	White
N272-010-WH	Yes	S/FTP	3,05 m	40 Gbps	Solid Copper	White
N272-015-WH	Yes	S/FTP	4,57 m	40 Gbps	Solid Copper	White
N272-020-WH	Yes	S/FTP	6,09 m	40 Gbps	Solid Copper	White
N272-025-WH	Yes	S/FTP	7,62 m	40 Gbps	Solid Copper	White

Cisco Console Rollover Cables

Converts a standard Ethernet cable into a serial rollover cable for connecting to Cisco or other hardware that requires rolled cables.



Key points:

- Recommended for Cisco modems, routers, switches and other serial devices
- Internally rolls the pins to convert straight-through cable to rollover cable
- Narrow male RJ45 plug connects to device without blocking adjacent ports

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Technology				Connectors		Data Rate	Length	Cable Jacket Material	Colors	
	Cat5/5e	Cat6	Cat6a	Cat8	Connector 1	Connector 2				Cable Jacket	Connector
N034-05N-BL	Yes	Yes	-	-	RJ45 (M)	RJ45 (M)	-	Pigtail	-	Blue	Blue
N205-006-BL-FCR	Yes	Yes	-	-	RJ45 (M)	RJ45 (M)	1 Gbps	1,83 m	PVC	Blue	Blue
N205-010-BL-FCR	Yes	Yes	-	-	RJ45 (M)	RJ45 (M)	1 Gbps	3,05 m	PVC	Blue	Blue
U009-006-RJ45-X	Yes	-	-	-	USB-A (M)	RJ45 (M)	Up to 12 Mbps	1,83 m	PVC	Black	Black
U009-010-RJ45-X	Yes	-	-	-	USB-A (M)	RJ45 (M)	Up to 12 Mbps	3,05 m	PVC	Black	Black
U009-015-RJ45-X	Yes	-	-	-	USB-A (M)	RJ45 (M)	Up to 12 Mbps	4,57 m	PVC	Black	Black

Fiber Patch Panels

PoE+-compliant patch panel manages and organizes data/power cable connections in your high-density network.



Key points:

- 8 to 64 ports
- Single and Multimode
- LC,ST,SC connectors

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Number of Ports	Height (U)	Product Type	Technology		Cable		Fiber Type	Endface Polish
				Singlemode	Multimode	Connector A (Front)	Connector B (Rear)		
N48LSM-16X16	32	1U	Spine-Leaf	-	Yes	16x 12-STRAND MTP/MPO	16x 12-STRAND MTP/MPO	50/125	PC
N48LSM-32X32	64	1U	Spine-Leaf	-	OM4	32x 12-STRAND MTP/MPO	32x 12-STRAND MTP/MPO	50/125	PC
N48LSS-16X16	32	1U	Spine-Leaf	OS2	-	16x 12-STRAND MTP/MPO	16x 12-STRAND MTP/MPO	9/125	APC
N48LSS-32X32	64	1U	Spine-Leaf	OS2	-	32x 12-STRAND MTP/MPO	32x 12-STRAND MTP/MPO	9/125	APC
N490-016-LCLC	16	1U	Feed-Through	Yes	Yes	LC (F)	LC (F)	-	-
N490-016-SCSC	16	1U	Feed-Through	Yes	Yes	SC (F)	SC (F)	-	-
N492-036-LCLC-E	36	1U	Feed-Through	Yes	Yes	LC (F)	LC (F)	-	-
Adapter									
N492-08D-LC	8	-	-	Yes	Yes	LC (F)	LC (F)	-	-
N492-08S-ST	8	-	-	Yes	Yes	ST (F)	ST (F)	-	-

Fiber Cassette Enclosures & Sleeves

Cost-Effective, Space-Saving Solution for Adding a Fiber Cassette to Your System.



Key points:

- Helps you interconnect any combo of 10 Gb, 40 Gb and 100/120 Gb network equipment
- Made from heavy-duty cold-rolled steel
- No added heat or cooling load

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Technology	Accessory Type	Number of U	Cassette Capacity
N482-00U	Multimode	Sleeve/ Pass-Through Panel	0U	1
N482-01U	Singlemode/Multimode	Rackmount	1U	5
N482-02U	Singlemode/Multimode	Rackmount	2U	14
N482-04U	Singlemode/Multimode	Rackmount	4U	28
N484-01U	Cat5/5e, Cat6/Cat6a, Multimode	Pass-Through Panel	1U	4

Fiber Cassettes

Installs in select fiber enclosure panels to connect fiber cables with MTP/MPO connections in high-density network applications



Key points:

- Install N482-Series chassis
- Helps You Monitor and Analyze Network Data
- Easy to Install with Compatible Enclosure

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Technology	Optical mode	Connectors		Number of ports	Number of fibers	Network compatibility
			Input Ports	Output Ports			
N482-3M8L12S-B	Singlemode		3x 8 MTP/MPO	12x LC (F)	12	-	40/100Gb
N482TAP-4SM73LC	Singlemode		4x LC (F)	4x LC (F)	-	8	
N482TAP-4SM73M8	Singlemode		12x MTP/MPO	12x MTP/MPO		32	
N482-2M12-LC12	Multimode	OM4	2x MTP/MPO (M)	12x LC (F)		12	40Gb to 10Gb
N482-3M8-LC12	Multimode	OM4	3x 8 MTP/MPO (M)	LC (F)		12	40/100Gb
N482TAP-4MM73LC	Multimode	OM4	4x LC	4x LC		4	40/100Gb
N482TAP-4MM73M8	Multimode	OM4	12x MTP/MPO	12x MTP/MPO		32	40/100Gb
N484-12LC	Multimode		LC (F)	LC (F)	12	-	10Gb
N484-12M12	-		12x MTP/MPO (F)	12x MTP/MPO (F)			40Gb
N484-1M24-LC12	Multimode	OM4	24x STRAND MTP/MPO (M)	LC (F)	12	-	100Gb/120Gb to 10Gb
N484-3M8L12S	Singlemode		8x STRAND MTP/MPO (M)	LC (F)	12	-	40/100Gb
N484-3M8-LC12	Multimode		8x STRAND MTP/MPO (M)	LC (F)	12	-	40/100Gb

Fiber Patch Panel

Patch panel comes with spools of multimode fiber cable that allow you to extend the exact length required and store the excess out of sight.



Key points:

- LC and MTP options
- Single and multimode
- All necessary cabling is included.
- Use only as much cabling as you need

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Height (U)	Optical Mode		Cable		Panel cable		Fiber Type	Endface Polish
				Connector A (Front)	Connector B (Rear)	Number	Length (m)		
Singlemode									
N48S-24M8L4-10	3U	OS2	-	24x MTP/MPO (F)	96x LC (F)	24	10 m	9/125	APC/UPC
N48S-2L24L-10	1U	OS2	-	12x LC (M)	12x LC (M)	2	10 m	9/125	UPC
N48S-2L24L-20	1U	OS2	-	12x LC (M)	12x LC (M)	2	20 m	9/125	UPC
N48S-2M24L12-10	1U	OS2	-	MTP/MPO (F)	12x LC (M)	2	10 m	9/125	APC/UPC
N48S-2M24L12-20	1U	OS2	-	MTP/MPO (F)	12x LC (M)	2	20 m	9/125	APC/UPC
N48S-2M3X8M-20	1U	OS2	-	3x MTP/MPO (F)	3x MTP/MPO (F)	2	20 m	9/125	APC
N48S-2M8L4-20	1U	OS2	-	MTP/MPO (F)	4x LC (M)	2	20 m	9/125	APC/UPC
N48S-32M8L4-03	2U	OS2	-	32x MTP/MPO (F)	128x LC (F)	32	3 m	9/125	APC/UPC
N48S-48M8L4-05	3U	OS2	-	48x MTP/MPO (F)	192x LC (F)	48	5 m	9/125	APC/UPC
N48S-4L16L-10	1U	OS2	-	8x LC (M)	8x LC (M)	4	10 m	9/125	UPC
N48S-4M3X8M-10	1U	OS2	-	3x MTP/MPO (F)	3x MTP/MPO (F)	4	10 m	9/125	APC
N48S-4M8L4-10	1U	OS2	-	MTP/MPO (F)	4x LC	4	10 m	9/125	APC/UPC
N48S-64M8L4-03	1U	OS2	-	64x MTP/MPO (F)	256x LC	64	3 m	9/125	APC/UPC
N48S-6L8L-10	1U	OS2	-	4x LC (M)	4x LC (M)	6	10 m	9/125	UPC
N48S-8L2L-10	1U	OS2	-	LC (M)	LC (M)	8	10 m	9/125	UPC
Multimode									
N48M-24M8L4-10	3U	-	OM4	24x MTP/MPO (M)	96x LC (M)	24	10 m	50/125	PC
N48M-2L24L-10	1U	-	OM4	12x LC (M)	12x LC (M)	2	10 m	50/125	PC
N48M-2L24L-20	1U	-	OM4	12x LC (M)	12x LC (M)	2	20 m	50/125	PC
N48M-2M24L12-10	1U	-	OM4	MTP/MPO (F)	12x LC (M)	2	10 m	50/125	PC
N48M-2M24L12-20	1U	-	OM4	MTP/MPO (F)	12x LC (M)	2	20 m	20/125	PC
N48M-2M3X8M-20	1U	-	OM4	3x MTP/MPO (F)	3x MTP/MPO (F)	2	20 m	50/125	PC
N48M-2M8L4-20	1U	-	OM4	MTP/MPO (F)	4x LC (M)	2	20 m	50/125	PC
N48M-32M8L4-03	2U	-	OM4	32x MTP/MPO (F)	128x LC (F)	32	3 m	50/125	PC
N48M-48M8L4-05	3U	-	OM4	48x MTP/MPO (F)	192x LC (F)	48	5 m	50/125	PC
N48M-4L16L-10	1U	-	OM4	8x LC (M)	8x LC (M)	4	10 m	50/125	PC
N48M-4M3X8M-10	1U	-	OM4	3x MTP/MPO (F)	3x MTP/MPO (F)	4	10 m	50/125	PC
N48M-4M8L4-10	1U	-	OM4	MTP/MPO (F)	4x LC (M)	4	10 m	50/125	PC
N48M-64M8L4-03	3U	-	OM4	64x MTP/MPO (F)	256x LC (F)	64	3 m	50/125	PC
N48M-6L8L-10	1U	-	OM4	4x LC (M)	4x LC (M)	6	10 m	50/125	PC
N48M-8L2L-10	1U	-	OM4	LC (M)	LC (M)	8	10 m	50/125	PC
N48K-15M8L60-B	1U	-	OM4	MTP/MPO (F)	LC (F)		2 m	50/125	

OS2 Singlemode Fiber Patch Cables

Duplex Singlemode 9/125 Fiber Patch Cable (LC/LC).



Key points:

- OS2 - Manufactured from 9/125 duplex (zipcord) fiber
- Yellow Jacket Helps Avoid Misidentification That Can Cause Costly Downtime
- Fiber made from glass (not a polymer)

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
N352-01M	ST	ST	1 m	Yellow	Black	LSZH	OFNR	2	9/125	UPC
N352-03M	ST	ST	2 m	Yellow	Black	LSZH	OFNR	2	9/125	UPC
N352-05M	ST	ST	5 m	Yellow	Black	LSZH	OFNR	2	9/125	UPC
N352-09M	ST	ST	9 m	Yellow	Black	LSZH	OFNR	2	9/125	UPC
N354-02M	SC	ST	2 m	Yellow	Black/Blue	LSZH	OFNR	2	9/125	UPC
N354-09M	SC	ST	9 m	Yellow	Black/Blue	LSZH	OFNR	2	9/125	UPC
N354-15M	SC	ST	15 m	Yellow	Black/Blue	LSZH	OFNR	2	9/125	UPC
N356-01M	SC	SC	1 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N356-02M	SC	SC	2 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N356-05M	SC	SC	5 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N356-06M	SC	SC	6 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N356-09M	SC	SC	9 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N356-15M	SC	SC	15 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N356-30M	SC	SC	30 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N366-01M	LC	SC	1 m	Yellow	Blue/Blue/White	LSZH	OFNR	2	9/125	UPC
N366-02M	LC	SC	2 m	Yellow	Blue/Blue/White	LSZH	OFNR	2	9/125	UPC
N366-03M	LC	SC	3 m	Yellow	Blue/Blue/White	LSZH	OFNR	2	9/125	UPC
N366-03M-AP	LC	SC	3 m	Yellow	Green/Blue/White	LSZH	OFNR	2	9/125	APC/ UPC
N366-05M	LC	SC	5 m	Yellow	Blue/Blue/White	LSZH	OFNR	2	9/125	UPC
N366-07M	LC	SC	7 m	Yellow	Blue/Blue/White	LSZH	OFNR	2	9/125	UPC
N366-10M	LC	SC	10 m	Yellow	Blue/Blue/White	LSZH	OFNR	2	9/125	UPC
N366-25M	LC	SC	25 m	Yellow	Blue/Blue/White	LSZH	OFNR	2	9/125	UPC
N368-01M	LC	ST	1 m	Yellow	Black/Blue/White	LSZH	OFNR	2	9/125	UPC
N368-03M	LC	ST	3 m	Yellow	Black/Blue/White	LSZH	OFNR	2	9/125	UPC
N368-05M-P	LC	ST	5 m	Yellow	Black/Blue/White	PVC	OFNR	2	9/125	UPC
N368-10M	LC	ST	10 m	Yellow	Black/Blue/White	LSZH	OFNR	2	9/125	UPC
N368-20M	LC	ST	20 m	Yellow	Black/Blue/White	LSZH	OFNR	2	9/125	UPC
N370-01M	LC	LC	1 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-02M	LC	LC	2 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-03M	LC	LC	3 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-05M	LC	LC	5 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-06M	LC	LC	6 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-10M	LC	LC	10 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-15M	LC	LC	15 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-50M	LC	LC	50 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
Push/Pull Tabs										
N370-02M-T	LC	LC	2 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-03M-T	LC	LC	3 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-05M-T	LC	LC	5 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
100 Gbps CABLES										
N370-15M-AR	LC	LC	15 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-30M-AR	LC	LC	30 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-50M-AR	LC	LC	50 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-75M-AR	LC	LC	75 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N370-100M-AR	LC	LC	100 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
40/100/400 Gbps CABLES										
N370X-01M	LC	LC	1 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N370X-02M	LC	LC	2 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N370X-03M	LC	LC	3 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N370X-04M	LC	LC	4 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N370X-05M	LC	LC	5 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N370X-06M	LC	LC	6 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N370X-07M	LC	LC	7 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N370X-08M	LC	LC	8 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N370X-10M	LC	LC	10 m	Yellow	Blue	LSZH	OFNR	2	9/125	UPC
N378-02M	LC	FC	2 m	Yellow	Yellow/Blue/White	LSZH	OFNR	2	9/125	UPC
N383L-01M	SN	LC	1 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N383L-02M	SN	LC	2 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N383L-03M	SN	LC	3 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N383L-05M	SN	LC	5 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N383S-01M	SN	SN	1 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N383S-02M	SN	SN	2 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N383S-03M	SN	SN	3 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC
N383S-05M	SN	SN	5 m	Yellow	Blue/White	LSZH	OFNR	2	9/125	UPC

OM1 Multimode Fiber Patch Cables

Duplex Multimode 62.5/125 Fiber Patch Cable.



Key points:

- Commonly used in LAN applications where links are typically 3m or less.
- Glass fiber composition
- Fiber optic distributed data interface (FDDI) rated

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
N302-06M	ST	ST	6 m	Orange	Black	LSZH	OFNR	2	62.5/125	PC
N302-08M	ST	ST	8 m	Orange	Black	LSZH	OFNR	2	62.5/125	PC
N302-10M	ST	ST	10 m	Orange	Black	LSZH	OFNR	2	62.5/125	PC
N302-15M	ST	ST	15 m	Orange	Black	LSZH	OFNR	2	62.5/125	PC
N304-003	SC	ST	1 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N304-004	SC	ST	1,2 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N304-006	SC	ST	2 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N304-008	SC	ST	2,4 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N304-010	SC	ST	3 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N304-025	SC	ST	8 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N304-06M	SC	ST	6 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N304-15M	SC	ST	15 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N306-001	SC	SC	31 cm	Orange	White	LSZH	OFNR	2	62.5/125	PC
N306-002	SC	SC	61 cm	Orange	White	LSZH	OFNR	2	62.5/125	PC
N306-003	SC	SC	1 m	Orange	White	LSZH	OFNR	2	62.5/125	PC
N306-006	SC	SC	2 m	Orange	White	LSZH	OFNR	2	62.5/125	PC
N306-010	SC	SC	3 m	Orange	White	LSZH	OFNR	2	62.5/125	PC
N306-04M	SC	SC	4 m	Orange	White	LSZH	OFNR	2	62.5/125	PC
N306-09M	SC	SC	9 m	Orange	White	LSZH	OFNR	2	62.5/125	PC
N306-12M	SC	SC	12 m	Orange	White	LSZH	OFNR	2	62.5/125	PC
N306-23M	SC	SC	23 m	Orange	White	LSZH	OFNR	2	62.5/125	PC
N306-25M	SC	SC	25 m	Orange	White	LSZH	OFNR	2	62.5/125	PC
N308-003	MTRJ	ST	91 cm	Orange	Black	LSZH	OFNR	2	62.5/125	PC
N308-006	MTRJ	ST	2 m	Orange	Black	LSZH	OFNR	2	62.5/125	PC
N308-010	MTRJ	ST	3 m	Orange	Black	LSZH	OFNR	2	62.5/125	PC
N308-05M	MTRJ	ST	5 m	Orange	Black	LSZH	OFNR	2	62.5/125	PC
N308-08M	MTRJ	ST	8 m	Orange	Black	LSZH	OFNR	2	62.5/125	PC
N308-15M	MTRJ	ST	15 m	Orange	Black	LSZH	OFNR	2	62.5/125	PC
N310-003	MTRJ	SC	1 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N310-010	MTRJ	SC	3 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N310-05M	MTRJ	SC	5 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N310-08M	MTRJ	SC	8 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N310-30M	MTRJ	SC	30 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N312-01M	MTRJ	MTRJ	1 m	Orange	Black	PVC	OFNR	2	62.5/125	PC
N312-05M	MTRJ	MTRJ	5 m	Orange	Black	PVC	OFNR	2	62.5/125	PC

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
N314-01M	MTRJ	LC	1 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N314-02M	MTRJ	LC	2 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N314-03M	MTRJ	LC	3 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N314-05M	MTRJ	LC	5 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N314-15M	MTRJ	LC	15 m	Orange	White/Black	LSZH	OFNR	2	62.5/125	PC
N316-02M	LC	SC	2 m	Orange	White/Beige	LSZH	OFNR	2	62.5/125	PC
N316-10M	LC	SC	10 m	Orange	White/Beige	LSZH	OFNR	2	62.5/125	PC
N316-13M	LC	SC	13 m	Orange	White/Beige	LSZH	OFNR	2	62.5/125	PC
N316-20M	LC	SC	20 m	Orange	White/Beige	LSZH	OFNR	2	62.5/125	PC
N316-25M	LC	SC	25 m	Orange	White/Beige	LSZH	OFNR	2	62.5/125	PC
N318-06M	LC	ST	6 m	Orange	Black/Gray	LSZH	OFNR	2	62.5/125	PC
N318-09M	LC	ST	9 m	Orange	Black/Gray	LSZH	OFNR	2	62.5/125	PC
N318-10M	LC	ST	10 m	Orange	Black/Gray	LSZH	OFNR	2	62.5/125	PC
N318-20M	LC	ST	20 m	Orange	Black/Gray	LSZH	OFNR	2	62.5/125	PC
N320-001	LC	LC	31 cm	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-01M	LC	LC	1 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-01M-RD	LC	LC	1 m	Red	Gray	LSZH	OFNR	2	62.5/125	PC
N320-02M	LC	LC	1 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-03M	LC	LC	1 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-03M-RD	LC	LC	3 m	Red	Gray	LSZH	OFNR	2	62.5/125	PC
N320-05M	LC	LC	5 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-05M-RD	LC	LC	5 m	Red	Gray	LSZH	OFNR	2	62.5/125	PC
N320-06M	LC	LC	6 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-07M	LC	LC	7 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-10M	LC	LC	10 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-10M-RD	LC	LC	10 m	Red	Gray	LSZH	OFNR	2	62.5/125	PC
N320-15M	LC	LC	15 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-15M-RD	LC	LC	15 m	Red	Gray	LSZH	OFNR	2	62.5/125	PC
N320-20M	LC	LC	20 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-21M	LC	LC	21 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N320-30M	LC	LC	30 m	Orange	Gray	LSZH	OFNR	2	62.5/125	PC
N318-01M	LC	ST	1 m	Orange	Black/Gray	LSZH	OFNR	2	62.5/125	PC
N318-02M	LC	ST	2 m	Orange	Black/Gray	LSZH	OFNR	2	62.5/125	PC
N318-03M	LC	ST	3 m	Orange	Black/Gray	LSZH	OFNR	2	62.5/125	PC

OM2 Multimode Fiber Patch Cables

Duplex Multimode 50/125 Fiber Patch Cables.



Key points:

- Higher bandwidth, optimized for gigabit and 10Gbps networks
- Glass fiber composition
- Fiber optic distributed data interface (FDDI) rated

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
N504-02M	SC	ST	2 m	Orange	Beige/Black	LSZH	OFNR	2	50/125	PC
N504-05M	SC	ST	5 m	Orange	Beige/Black	LSZH	OFNR	2	50/125	PC
N506-01M	SC	SC	1 m	Orange	Beige	LSZH	OFNR	2	50/125	PC
N506-02M	SC	SC	2 m	Orange	Beige	LSZH	OFNR	2	50/125	PC
N506-03M	SC	SC	3 m	Orange	Beige	LSZH	OFNR	2	50/125	PC
N506-05M	SC	SC	5 m	Orange	Beige	LSZH	OFNR	2	50/125	PC
N506-09M	SC	SC	9 m	Orange	Beige	LSZH	OFNR	2	50/125	PC
N506-10M	SC	SC	10 m	Orange	Beige	LSZH	OFNR	2	50/125	PC
N506-15M	SC	SC	15 m	Orange	Beige	LSZH	OFNR	2	50/125	PC
N506-30M	SC	SC	30 m	Orange	Beige	LSZH	OFNR	2	50/125	PC
N516-01M	LC	SC	1 m	Orange	White/Beige	LSZH	OFNR	2	50/125	PC
N516-02M	LC	SC	2 m	Orange	White/Beige	LSZH	OFNR	2	50/125	PC
N516-05M	LC	SC	5 m	Orange	White/Beige	LSZH	OFNR	2	50/125	PC
N516-07M	LC	SC	7 m	Orange	White/Beige	LSZH	OFNR	2	50/125	PC
N516-20M	LC	SC	20 m	Orange	White/Beige	LSZH	OFNR	2	50/125	PC
N518-05M	LC	ST	5 m	Orange	Gray/Red/Black	LSZH	OFNR	2	50/125	PC
N518-10M	LC	ST	10 m	Orange	Gray/Red/Black	LSZH	OFNR	2	50/125	PC
N518-15M	LC	ST	15 m	Orange	Gray/Red/Black	LSZH	OFNR	2	50/125	PC
N518-20M	LC	ST	20 m	Orange	Gray/Red/Black	LSZH	OFNR	2	50/125	PC
N520-01M	LC	LC	1 m	Orange	Gray	LSZH	OFNR	2	50/125	PC
N520-03M	LC	LC	3 m	Orange	Gray	LSZH	OFNR	2	50/125	PC
N520-05M	LC	LC	5 m	Orange	Gray	LSZH	OFNR	2	50/125	PC
N520-12M	LC	LC	12 m	Orange	Gray	LSZH	OFNR	2	50/125	PC
N520-15M	LC	LC	15 m	Orange	Gray	LSZH	OFNR	2	50/125	PC
N520-20M	LC	LC	20 m	Orange	Gray	LSZH	OFNR	2	50/125	PC
N520-25M	LC	LC	25 m	Orange	Gray	LSZH	OFNR	2	50/125	PC
N520-30M	LC	LC	30 m	Orange	Gray	LSZH	OFNR	2	50/125	PC
N520-30M-P	LC	LC	30 m	Orange	Gray	PVC	OFNR	2	50/125	PC
N520-50M	LC	LC	50 m	Orange	Gray	LSZH	OFNR	2	50/125	PC
N520-100M	LC	LC	100 m	Orange	Gray	LSZH	OFNR	2	50/125	PC

OM3 Multimode Fiber Patch Cables

Duplex Multimode 50/125 OM3 Fiber Patch Cables



Key points:

- Low-Smoke, Zero Halogen (LSZH) Aqua jacket
- Backward compatible with existing 50/125 fiber

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
For 10 Gbps applications										
N806-01M	SC	SC	1 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N806-02M	SC	SC	2 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N806-03M	SC	SC	3 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N806-05M	SC	SC	5 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N806-10M	SC	SC	10 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N816-01M	SC	LC	1 m	Aqua	White/Beige	LSZH	OFNR	2	50/125	PC
N816-02M	SC	LC	2 m	Aqua	White/Beige	LSZH	OFNR	2	50/125	PC
N816-03M	SC	LC	3 m	Aqua	White/Beige	LSZH	OFNR	2	50/125	PC
N816-05M	SC	LC	5 m	Aqua	White/Beige	LSZH	OFNR	2	50/125	PC
N816-10M	SC	LC	10 m	Aqua	White/Beige	LSZH	OFNR	2	50/125	PC
N818-01M	LC	ST	1 m	Aqua	White/Black	LSZH	OFNR	2	50/125	PC
N818-02M	LC	ST	2 m	Aqua	White/Black	LSZH	OFNR	2	50/125	PC
N818-05M	LC	ST	5 m	Aqua	White/Black	LSZH	OFNR	2	50/125	PC
N818-10M	LC	ST	10 m	Aqua	White/Black	LSZH	OFNR	2	50/125	PC
N820-20N	LC	LC	50 cm	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-01M	LC	LC	1 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-02M	LC	LC	2 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-03M	LC	LC	3 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-04M	LC	LC	4 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-05M	LC	LC	5 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-06M	LC	LC	6 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-07M	LC	LC	7 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-08M	LC	LC	8 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-10M	LC	LC	10 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-15M	LC	LC	15 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-20M	LC	LC	20 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-25M	LC	LC	25 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-30M	LC	LC	30 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N820-50M	LC	LC	50 m	Aqua	White	LSZH	OFNR	2	50/125	PC
N836-01M	LC	Mini LC	1 m	Aqua	White/Beige	LSZH	OFNR	2	50/125	PC
N836-02M	LC	Mini LC	2 m	Aqua	White/Beige	LSZH	OFNR	2	50/125	PC
N836-10M	LC	Mini LC	10 m	Aqua	White/Beige	LSZH	OFNR	2	50/125	PC
Push/Pull Tabs										
N820-02M-T	LC	LC	2 m	Aqua	White/Aqua	LSZH	OFNR	2	50/125	PC
N820-05M-T	LC	LC	5 m	Aqua	White/Aqua	LSZH	OFNR	2	50/125	PC

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
For 400 Gbps applications										
N820X-01M	LC	LC	1 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N820X-02M	LC	LC	2 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N820X-03M	LC	LC	3 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N820X-04M	LC	LC	4 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N820X-05M	LC	LC	5 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N820X-06M	LC	LC	6 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N820X-07M	LC	LC	7 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N820X-08M	LC	LC	8 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC
N820X-10M	LC	LC	10 m	Aqua	Beige	LSZH	OFNR	2	50/125	PC

OM4 Multimode Fiber Patch Cables

Duplex Multimode 50/125 OM4 Fiber Optic Cable



Key points:

- Push/pull tab connectors install/remove with one hand
- Slim, space-saving uniboot design for neat cable management
- Premium-grade ceramic ferrules designed for fast applications
- Backward Compatible with existing 50/125 fiber

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
For 10 Gbps applications										
Push/Pull Tabs										
N821-02M-MG-T	LC	LC	2 m	Magenta	White/Aqua	LSZH	OFNR	2	50/125	PC
N821-04M-MG-T	LC	LC	4 m	Magenta	White/Aqua	LSZH	OFNR	2	50/125	PC
For 40/100 Gbps applications										
N820-01M-OM4	LC	LC	1 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820-02M-OM4	LC	LC	2 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820-03M-OM4	LC	LC	3 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820-05M-OM4	LC	LC	5 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820-10M-OM4	LC	LC	10 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820-15M-OM4	LC	LC	15 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820-20M-OM4	LC	LC	20 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N845X-01M-8L-MG	12F MTP/MPO	4x LC	1 m	Magenta	Aqua/Magenta/Black	LSZH	OFNR	8	50/125	PC
N845X-02M-8L-MG	12F MTP/MPO	4x LC		Magenta	Aqua/Magenta/Black	LSZH	OFNR	8	50/125	PC
N845X-03M-8L-MG	12F MTP/MPO	4x LC		Magenta	Aqua/Magenta/Black	LSZH	OFNR	8	50/125	PC
N845X-05M-8L-MG	12F MTP/MPO	4x LC		Magenta	Aqua/Magenta/Black	LSZH	OFNR	8	50/125	PC
For 100 Gbps applications										
N821-15M-AQ-AR	LC	LC	15 m	Aqua	Aqua/White	LSZH	OFNR	2	50/125	PC
N821-30M-AQ-AR	LC	LC	30 m	Aqua	Aqua/White	LSZH	OFNR	2	50/125	PC
N821-50M-AQ-AR	LC	LC	50 m	Aqua	Aqua/White	LSZH	OFNR	2	50/125	PC
N821-75M-AQ-AR	LC	LC	75 m	Aqua	Aqua/White	LSZH	OFNR	2	50/125	PC
N821-100M-AQ-AR	LC	LC	100 m	Aqua	Aqua/White	LSZH	OFNR	2	50/125	PC
N845B-01M-12-MG	12F MTP/MPO	12F MTP/MPO	1 m	Magenta	Magenta/Black	LSZH	OFNR	12	50/125	PC
N845B-02M-12-MG	12F MTP/MPO	12F MTP/MPO	2 m	Magenta	Magenta/Black	LSZH	OFNR	12	50/125	PC
N845B-03M-12-MG	12F MTP/MPO	12F MTP/MPO	3 m	Magenta	Magenta/Black	LSZH	OFNR	12	50/125	PC
N845B-05M-12-MG	12F MTP/MPO	12F MTP/MPO	5 m	Magenta	Magenta/Black	LSZH	OFNR	12	50/125	PC
N845B-10M-12-MG	12F MTP/MPO	12F MTP/MPO	10 m	Magenta	Magenta/Black	LSZH	OFNR	12	50/125	PC
N845B-15M-12-MG	12F MTP/MPO	12F MTP/MPO	15 m	Magenta	Magenta/Black	LSZH	OFNR	12	50/125	PC
N845B-20M-12-MG	12F MTP/MPO	12F MTP/MPO	20 m	Magenta	Magenta/Black	LSZH	OFNR	12	50/125	PC
N845B-25M-12-MG	12F MTP/MPO	12F MTP/MPO	25 m	Magenta	Magenta/Black	LSZH	OFNR	12	50/125	PC
N823S-05M-MG	SN	SN	5 m	Magenta	Aqua/White	LSZH	OFNR	2	50/125	PC

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
For 400 Gbps applications										
N820X-01M-OM4	LC	LC	1 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820X-02M-OM4	LC	LC	2 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820X-03M-OM4	LC	LC	3 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820X-05M-OM4	LC	LC	5 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820X-07M-OM4	LC	LC	7 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N820X-10M-OM4	LC	LC	10 m	Aqua	Aqua	LSZH	OFNR	2	50/125	PC
N823L-01M-MG	SN	LC	1 m	Magenta	Aqua/White	LSZH	OFNR	2	50/125	PC
N823L-02M-MG	SN	LC	1 m	Magenta	Aqua/White	LSZH	OFNR	2	50/125	PC
N823L-03M-MG	SN	LC	1 m	Magenta	Aqua/White	LSZH	OFNR	2	50/125	PC
N823L-05M-MG	SN	LC	1 m	Magenta	Aqua/White	LSZH	OFNR	2	50/125	PC
N823S-01M-MG	SN	SN	1 m	Magenta	Aqua/White	LSZH	OFNR	2	50/125	PC
N823S-02M-MG	SN	SN	2 m	Magenta	Aqua/White	LSZH	OFNR	2	50/125	PC
N823S-03M-MG	SN	SN	3 m	Magenta	Aqua/White	LSZH	OFNR	2	50/125	PC
N823S-05M-MG	SN	SN	5 m	Magenta	Aqua/White	LSZH	OFNR	2	50/125	PC

OM5 Multimode Fiber Patch Cables

Rated OM5, this 50/125 multimode fiber cable with duplex LC connectors carries signals in 40/100 Gb Ethernet networks.



Key points:

- Laser-optimized for use with cost-effective VCSEL light sources
- Lime green jacket for easy OM5 identification
- Backward compatible with OM3 and OM4 applications

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
N820-01M-OM5	LC	LC	1 m	Lime Green	Aqua	LSZH	OFNR	2	50/125	PC
N820-02M-OM5	LC	LC	2 m	Lime Green	Aqua	LSZH	OFNR	2	50/125	PC
N820-03M-OM5	LC	LC	3 m	Lime Green	Aqua	LSZH	OFNR	2	50/125	PC
N820-05M-OM5	LC	LC	5 m	Lime Green	Aqua	LSZH	OFNR	2	50/125	PC
N820-10M-OM5	LC	LC	10 m	Lime Green	Aqua	LSZH	OFNR	2	50/125	PC

MTP/MTO Cables

Premium singlemode or multimode fiber optic cabling for transmitting 40/100/400 Gb data and voice signals over long distances.



Key points:

- Converts Singlemode to Multimode
- Available in a variety of connector combinations

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Optical mode	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
		Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
N390-02M-12-AP	OS2	MTP/MPO	MTP/MPO	2 m	Yellow	Green/Black	PVC	OFNP	12	9/125	APC
N390-02M-8LC-AP	OS2	MTP/MPO	8x LC	2 m	Yellow	Blue/Green/Black	PVC	OFNP	8	9/125	APC/UPC
N842-05M-12-MF	OM3	MTP/MPO	MTP/MPO	5 m	Aqua	Aqua/Black	PVC	OFNP	12	50/125	PC
N842-10M-12-MF	OM3	MTP/MPO	MTP/MPO	10 m	Aqua	Aqua/Black	PVC	OFNP	12	50/125	PC
N842B-05M-12-MF	OM3	MTP/MPO	MTP/MPO	5 m	Aqua	Black	LSZH	OFNR	12	50/125	PC
N842B-10M-12-MF	OM3	MTP/MPO	MTP/MPO	10 m	Aqua	Black	LSZH	OFNR	12	50/125	PC
N844-01M-12-P	OM3	MTP/MPO	MTP/MPO	1 m	Aqua	Aqua/Black	PVC	OFNP	12	50/125	PC
N844-02M-12-P	OM3	MTP/MPO	MTP/MPO	2 m	Aqua	Aqua/Black	PVC	OFNP	12	50/125	PC
N844-02M-8LC-P	OM3	MTP/MPO	8x LC	2 m	Aqua	Aqua/Black	PVC	OFNP	8	50/125	PC
N844-03M-12-P	OM3	MTP/MPO	MTP/MPO	3 m	Aqua	Aqua/Black	PVC	OFNP	12	50/125	PC
N844-03M-8LC-PT	OM3	MTP/MPO	8x LC	3 m	Aqua	Aqua/Black	PVC	OFNP	8	50/125	PC
N844-05M-12-P	OM3	MTP/MPO	MTP/MPO	5 m	Aqua	Aqua/Black	PVC	OFNP	12	50/125	PC
N844-10M-12-P	OM3	MTP/MPO	MTP/MPO	10 m	Aqua	Aqua/Black	PVC	OFNP	12	50/125	PC
N844B-01M-12-P	OM3	MTP/MPO	MTP/MPO	1 m	Aqua	Black	LSZH	OFNR	12	50/125	PC
N844B-02M-12-P	OM3	MTP/MPO	MTP/MPO	2 m	Aqua	Black	LSZH	OFNR	12	50/125	PC
N844B-03M-12-P	OM3	MTP/MPO	MTP/MPO	3 m	Aqua	Black	LSZH	OFNR	12	50/125	PC
N844B-05M-12-P	OM3	MTP/MPO	MTP/MPO	5 m	Aqua	Black	LSZH	OFNR	12	50/125	PC
N844B-10M-12-P	OM3	MTP/MPO	MTP/MPO	10 m	Aqua	Black	LSZH	OFNR	12	50/125	PC
N844X-01M-8L-P	OM3	MTP/MPO	4x LC	1 m	Aqua	Beige/Black	LSZH	OFNR	8	50/125	PC
N844X-02M-8L-P	OM3	MTP/MPO	4x LC	2 m	Aqua	Beige/Black	LSZH	OFNR	8	50/125	PC
N844X-03M-8L-P	OM3	MTP/MPO	4x LC	3 m	Aqua	Beige/Black	LSZH	OFNR	8	50/125	PC
N844X-05M-8L-P	OM3	MTP/MPO	4x LC	5 m	Aqua	Beige/Black	LSZH	OFNR	8	50/125	PC
N845-01M-12-MG	OM4	MTP/MPO	MTP/MPO	1 m	Magenta	Magenta/Black	PVC	OFNP	12	50/125	PC
N845-02M-12-MG	OM4	MTP/MPO	MTP/MPO	2 m	Magenta	Magenta/Black	PVC	OFNP	12	50/125	PC
N845-02M-8L-MG	OM4	MTP/MPO	8x LC	2 m	Magenta	Aqua/Magenta/Black	PVC	OFNP	8	50/125	PC
N845-03M-12-MG	OM4	MTP/MPO	MTP/MPO	3 m	Magenta	Magenta/Black	PVC	OFNP	12	50/125	PC
N845-05M-12-MG	OM4	MTP/MPO	MTP/MPO	5 m	Magenta	Magenta/Black	PVC	OFNP	12	50/125	PC
N845-10M-12-MG	OM4	MTP/MPO	MTP/MPO	10 m	Magenta	Magenta/Black	PVC	OFNP	12	50/125	PC
N845-15M-12-MG	OM4	MTP/MPO	MTP/MPO	15 m	Magenta	Magenta/Black	PVC	OFNP	12	50/125	PC

Part number	Optical mode	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
		Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
Push/Pull Tabs											
100 Gbps Cables											
N846-01M-24-P	OM3	24-STRAND MTP/MPO	24-STRAND MTP/MPO	1 m	Aqua	Aqua/Black/Blue	PVC	OFNP	24	50/125	PC
N846-03M-24-P	OM3	24-STRAND MTP/MPO	24-STRAND MTP/MPO	3 m	Aqua	Aqua/Black/Blue	PVC	OFNP	24	50/125	PC
40/100 Gbps Cables											
N846-08N-C2B	OM4	12-STRAND MTP/MPO	12-STRAND MTP/MPO (F)		Magenta	Magenta/Black/Gray	PVC	OFNP	12	50/125	PC
N858-15M-3X8-MG	OM4	3x8-STRAND MTP/MPO	3x8-STRAND MTP/MPO	15 m	Magenta	Magenta/Black	PVC	OFNP	24	50/125	PC
N858-23M-3X8-MG	OM4	3x8-STRAND MTP/MPO	3x8-STRAND MTP/MPO	23 m	Magenta	Magenta/Black	PVC	OFNP	24	50/125	PC
N858-61M-3X8-MG	OM4	3x8-STRAND MTP/MPO	3x8-STRAND MTP/MPO	61 m	Magenta	Magenta/Black	PVC	OFNP	24	50/125	PC
40/100/400 Gbps Cables											
N846B-01M-24-P	OM3	24-STRAND MTP/MPO	24-STRAND MTP/MPO	1 m	Aqua	Aqua/Black/Blue	LSZH	OFNR	24	50/125	PC
N846B-02M-24-P	OM3	24-STRAND MTP/MPO	24-STRAND MTP/MPO	2 m	Aqua	Aqua/Black/Blue	LSZH	OFNR	24	50/125	PC
N846B-03M-24-P	OM3	24-STRAND MTP/MPO	24-STRAND MTP/MPO	3 m	Aqua	Aqua/Black/Blue	LSZH	OFNR	24	50/125	PC
N846B-05M-24-P	OM3	24-STRAND MTP/MPO	24-STRAND MTP/MPO	5 m	Aqua	Aqua/Black/Blue	LSZH	OFNR	24	50/125	PC
N846B-10M-24-P	OM3	24-STRAND MTP/MPO	24-STRAND MTP/MPO	10 m	Aqua	Aqua/Black/Blue	LSZH	OFNR	24	50/125	PC
N846B-15M-24-P	OM3	24-STRAND MTP/MPO	24-STRAND MTP/MPO	15 m	Aqua	Aqua/Black/Blue	LSZH	OFNR	24	50/125	PC
N846B-20M-24-P	OM3	24-STRAND MTP/MPO	24-STRAND MTP/MPO	20 m	Aqua	Aqua/Black/Blue	LSZH	OFNR	24	50/125	PC
N846B-25M-24-P	OM3	24-STRAND MTP/MPO	24-STRAND MTP/MPO	25 m	Aqua	Aqua/Black/Blue	LSZH	OFNR	24	50/125	PC
N858B-10M-3X8MG	OM4	12-STRAND MTP/MPO	24-STRAND MTP/MPO	10 m	Magenta	Black/Magenta	LSZH	OFNR	24	50/125	PC
N858B-15M-3X8MG	OM4	12-STRAND MTP/MPO	24-STRAND MTP/MPO	15 m	Magenta	Black/Magenta	LSZH	OFNR	24	50/125	PC
N858B-23M-3X8MG	OM4	12-STRAND MTP/MPO	24-STRAND MTP/MPO	23 m	Magenta	Black/Magenta	LSZH	OFNR	24	50/125	PC
N858B-30M-3X8MG	OM4	12-STRAND MTP/MPO	24-STRAND MTP/MPO	30 m	Magenta	Black/Magenta	LSZH	OFNR	24	50/125	PC
N858B-38M-3X8MG	OM4	12-STRAND MTP/MPO	24-STRAND MTP/MPO	38 m	Magenta	Black/Magenta	LSZH	OFNR	24	50/125	PC
N858B-45M-3X8MG	OM4	12-STRAND MTP/MPO	24-STRAND MTP/MPO	45 m	Magenta	Black/Magenta	LSZH	OFNR	24	50/125	PC

Part number	Connectors		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector 1	Connector 2		Cable Jacket	Connector	Material	Rating			
40/100 Gbps Cables										
N390B-01M-12-AP	12F MTP/MPO	12F MTP/MPO	1 m	Yellow	Black	LSZH	OFNR	2	9/125	APC
N390B-02M-12-AP	12F MTP/MPO	12F MTP/MPO	2 m	Yellow	Black	LSZH	OFNR	2	9/125	APC
N390B-03M-12-AP	12F MTP/MPO	12F MTP/MPO	3 m	Yellow	Black	LSZH	OFNR	2	9/125	APC
N390B-05M-12-AP	12F MTP/MPO	12F MTP/MPO	5 m	Yellow	Black	LSZH	OFNR	2	9/125	APC
N390B-07M-12-AP	12F MTP/MPO	12F MTP/MPO	7 m	Yellow	Black	LSZH	OFNR	2	9/125	APC
N390-01M-4S-AP	12F MTP/MPO	4x SN	1 m	Yellow	Black/Blue Green/ White	LSZH	OFNR	12	9/125	APC/ UPC
N390-02M-4S-AP	12F MTP/MPO	4x SN	2 m	Yellow	Black/Blue Green/ White	LSZH	OFNR	12	9/125	APC/ UPC
N390-02M-8S-AP	12F MTP/MPO	4x SN	2 m	Yellow	Black/Blue Green/ White	LSZH	OFNR	16	9/125	APC/ UPC
N390-03M-4S-AP	12F MTP/MPO	4x SN	3 m	Yellow	Black/Blue Green/ White	LSZH	OFNR	12	9/125	APC/ UPC
N390-03M-8S-AP	12F MTP/MPO	4x SN	3 m	Yellow	Black/Blue Green/ White	LSZH	OFNR	16	9/125	APC/ UPC
N390X-01M-8L-AP	12F MTP/MPO	4x LC	1 m	Yellow	Blue/Green/Black	LSZH	OFNR	2	9/125	APC/ UPC
N390X-02M-8L-AP	12F MTP/MPO	4x LC	2 m	Yellow	Blue/Green/Black	LSZH	OFNR	2	9/125	APC/ UPC
N390X-03M-8L-AP	12F MTP/MPO	4x LC	3 m	Yellow	Blue/Green/Black	LSZH	OFNR	2	9/125	APC/ UPC
N390X-05M-8L-AP	12F MTP/MPO	4x LC	5 m	Yellow	Blue/Green/Black	LSZH	OFNR	2	9/125	APC/ UPC
Push/Pull Tabs										
N392B-10M-3X8AP	3x8F MTP/MPO	3x8F MTP/MPO	10 m	Yellow	Green/Black	LSZH	-	24	9/125	APC
N392B-15M-3X8AP	3x8F MTP/MPO	3x8F MTP/MPO	15 m	Yellow	Green/Black	LSZH	-	24	9/125	APC
N392B-23M-3X8AP	3x8F MTP/MPO	3x8F MTP/MPO	23 m	Yellow	Green/Black	LSZH	-	24	9/125	APC
N392B-30M-3X8AP	3x8F MTP/MPO	3x8F MTP/MPO	30 m	Yellow	Green/Black	LSZH	-	24	9/125	APC
N392B-45M-3X8AP	3x8F MTP/MPO	3x8F MTP/MPO	45 m	Yellow	Green/Black	LSZH	-	24	9/125	APC
N392B-61M-3X8AP	3x8F MTP/MPO	3x8F MTP/MPO	61 m	Yellow	Green/Black	LSZH	-	24	9/125	APC

Fiber Couplers

Provides a simple and easy way to link together two fiber optic cables.



Key points:

- High precision mating structure with low insertion loss
- Duplex adapter accepts two simplex connectors or one duplex connector

Ideal for:

- Server room
- Data Center
- IP room
- White space

Part number	Optical Mode		Cable		Number of Fibers	Color
			Connector A (Front)	Connector B (Rear)		
N452-000	-	Yes	SC (F)	SC (F)	2	Light Gray
N455-000	-	Yes	LC (F)	LC (F)	2	Light Gray
N455-000-PM	-	Yes	LC (F)	LC (F)	2	Light Gray
N455-000-S	Yes	-	LC (F)	LC (F)	2	Light Gray
N456-000	-	Yes	SC (F)	ST (F)	2	Light Gray

Mode Conditioning

Use Singlemode Transceivers on Multimode Fiber Backbones.



Key points:

- Converts Singlemode to Multimode
- Available in a variety of connector combinations

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Length	Number of Fibers	Optical Mode	Colors		Cable Jacket Rating		Fiber Type
	Connector 1	Connector 2				Cable Jacket	Connector	Material	Rating	
N422-01M	LC	ST	1 m	2	OM1	Orange/Yellow	Blue/Gray/Black			62.5/125
N422-02M	LC	ST	2 m	2	OM1	Orange/Yellow	Blue/Gray/Black			62.5/125
N422-03M	LC	ST	3 m	2	OM1	Orange/Yellow	Blue/Gray/Black			62.5/125
N425-02M	LC	SC	2 m	2	OM1	Orange/Yellow	Beige/White/Blue			62.5/125

Network Adapters

Connect between different platforms or connectors to keep your devices up and running at all times.



Key points:

- USB to Ethernet
- Fiber to fiber
- Serial to Ethernet

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Length	Number of Fibers	Optical Mode	Colors		Cable Jacket		Fiber Type (microns)
	Connector 1	Connector 2				Cable Jacket	Connector	Material	Rating	
Cat5										
N035-001	2x RJ45 (F)	RJ45 (M)	Pigtail	-	-	Gray	-	-	-	-
U436-06N-2P5	USB-C (M)	RJ45 (F)	Pigtail	-	-	-	-	-	-	-
Fiber										
N457-001-62	LC (M)	ST (F)	31 cm	2	Multimode	Orange	Beige	LSZH	OFNR	62.5 / 125
N458-001-62	LC (M)	SC (F)	31 cm	2	Multimode	Orange	Beige			62.5 / 125
N458-001-9	LC (M)	SC (F)	31 cm	2	Singlemode	Yellow	Blue			9 / 125
Serial										
P440-89FF	DB9 (F)	RJ45 (F)	-	-	-	Black	-	-	-	-
Wireless										
U263-AC600	USB-A (M) 2.0	-	1,9 m	-	-	-	-	-	-	-

Media Converters

Extends your 10/100/1000 Mbps Gigabit Ethernet connection up to 20 km using fast singlemode or multimode fiber optic cabling.



Key points:

- LEDs indicate Ethernet and fiber link status at a quick glance
- Supports Power over Ethernet to Save You Money and Give You More Installation Choices
- Completely Plug-and-Play with No Additional Software Required for Connection

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Data Transfer Rate			Working Mode	Transmission Distance	PoE Capability
	Connector 1	Connector 2	10/100 Mbps (no compatible with Gbps)	10/100/1000 Mbps (Up to 1 Gbps but compatible with 10 Mbps & 100 Mbps)	Gigabits (1.000 Mbps)			
Singlemode (long distance)								
N785-INT-SC-SM	RJ45 (F)	SC (F)	Yes	Yes	Yes	Full/Half Duplex	20 km	-
Multimode (short distance)								
N785-INT-LC-MM	RJ45 (F)	LC (F)	Yes	Yes	Yes	Full/Half Duplex	550 m	-
N785-INT-PLCMM1	RJ45 (F)	LC (F)	Yes	Yes	Yes	Full/Half Duplex	550 m	Type 1 PoE (15,4W) Type 2 PoE+ (30W)
N785-INT-PSCMM2	SC (F)	RJ45 (F)	Yes	Yes	Yes	Full/Half Duplex	2 km	Type 1 PoE (15,4W) Type 2 PoE+ (30W)
N785-INT-SC	RJ45 (F)	SC (F)	Yes	Yes	Yes	Full/Half Duplex	2 km	-
N785-INT-SC-MM	RJ45 (F)	SC (F)	Yes	Yes	Yes	Full/Half Duplex	550 m	-
SFP								
N785-INT-PSFP	RJ45 (F)	SFP (F)	-	-	-	Full/Half Duplex	-	Type 1 PoE (15,4W) Type 2 PoE+ (30W)

Transceiver Modules

Connects a single or multimode Gigabit Ethernet fiber optic network cable to a switch or server's SFP port.



Key points:

- Supports data transfer rates up to 400 Gbps
- 100% compatible with Arista, Cisco, Juniper, HP, networking hardware

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Data Transfer Rate	Optical mode	Transmission Distance	Brand Compatibility
	Connector 1	Connector 2				
Singlemode						
N286-01GLX-SLX	SFP+ (M)	LC (M)	1 Gbps	-	10 km	HP
Multimode						
N286-01GSX-MDLC	SFP+ (M)	LC (M)	1 Gbps	-	10 km	HP
N286-01G-SX-A	SFP (M)	LC (M)	1,25 Gbps	OM2	550 m	Arista
N286-01G-SX-C*	SFP (M)	LC (M)	1,25 Gbps	OM2	550 m	Cisco
N286-01G-SX-G	SFP (M)	LC (M)	1,25 Gbps	OM2	550 m	Cisco
N286-01G-SX-J	SFP (M)	LC (M)	1,25 Gbps	OM2	550 m	Juniper
N286-100G-SR4SA	QSFP28(M)	12 STRAND MTP/MPO (M)	100 Gbps	OM4	100 m	Arista
N286-100G-SR45C*	QSFP28(M)	12 STRAND MTP/MPO (M)	100 Gbps	OM4	100 m	Cisco
N286-100G-SR45G	QSFP28(M)	12 STRAND MTP/MPO (M)	100 Gbps	OM4	100 m	Cisco
N286-100G-SR45J	QSFP28(M)	12 STRAND MTP/MPO (M)	100 Gbps	OM4	100 m	Juniper
N286-10G-SR-A	SFP+ (M)	LC (M)	10 Gbps	OM4	400 m	Arista
N286-10G-SR-C*	SFP+ (M)	LC (M)	10 Gbps	OM4	400 m	Cisco
N286-10G-SR-G	SFP+ (M)	LC (M)	10 Gbps	OM4	400 m	Cisco
N286-10G-SR-J	SFP+ (M)	LC (M)	10 Gbps	OM4	400 m	Cisco
N286-25G-SRS-G	SFP28(M)	LC (F)	25 Gbps	OM4	100 m	Juniper
N286-400G-SR8-C*	QSFP-DD	16 STRAND MTP/MPO (F)	400 Gbps	OM4	100 m	Cisco
N286-400G-SR8-G	QSFP-DD	16 STRAND MTP/MPO (F)	400 Gbps	OM4	100 m	Cisco
N286-40G-ESR4-A	QSFP+(M)	16 STRAND MTP/MPO (M)	40 Gbps	OM4	400 m	Arista
N286-40G-ESR4-C*	QSFP+(M)	16 STRAND MTP/MPO (M)	40 Gbps	OM4	400 m	Cisco
N286-40G-ESR4-G	QSFP+(M)	16 STRAND MTP/MPO (M)	40 Gbps	OM4	400 m	Cisco
N286-40G-ESR4-J	QSFP+(M)	16 STRAND MTP/MPO (M)	40 Gbps	OM4	400 m	Juniper

* designed specifically to meet or exceed Cisco specification

Direct Attach Copper Cables (DACs)

Low Cost alternative to Fiber Optic cables.



Key points:

- Ergonomic pull tabs for fast hot-swap connections/disconnections in crowded networks
- Simpler alternative to fiber optics in short-range network connections

Ideal for:

- Network Closet
- Server Room
- Data Center
- White Space

Part number	Connectors		Length	Optical Mode	Number of Fibers	Network Compatibility	Cable Type	Colors		Cable Jacket		Compatible Brand
	Connector 1	Connector 2						Cable Jacket	Connector	Material	Rating	
N280-20N-BK	SFP+	SFP+	50 cm	-	-	10 Gbps	Passive	Black	Black	PVC	-	
N280-01M-BK	SFP+	SFP+	1 m	-	-	10 Gbps	Passive	Black	Black	PVC	-	
N280-005-BK	SFP+	SFP+	1,52 m	-	-	10 Gbps	Passive	Black	Black	PVC	-	
N280-02M-BK	SFP+	SFP+	2 m	-	-	10 Gbps	Passive	Black	Black	PVC	-	Arista Broadcom
N280-03M-BK	SFP+	SFP+	3 m	-	-	10 Gbps	Passive	Black	Black	PVC	-	Cisco Dell-EMC
N280-03M-GN	SFP+	SFP+	3 m	-	-	10 Gbps	Passive	Green	Green	PVC	-	Emulex Extreme
N280-05M-BK	SFP+	SFP+	5 m	-	-	10 Gbps	Passive	Black	Black	PVC	-	Finisar
N280-06M-BK	SFP+	SFP+	6 m	-	-	10 Gbps	Passive	Black	Black	PVC	-	IBM Juniper QLogic
N280-07M-BK	SFP+	SFP+	7 m	-	-	10 Gbps	Passive	Black	Black	PVC	-	Voltaire
N280-01M-28-BK	SFP28	SFP28	1 m	-	-	25 Gbps	Passive	Black	Black	PVC	CM	
N280-02M-28-BK	SFP28	SFP28	2 m	-	-	25 Gbps	Passive	Black	Black	PVC	CM	Arista
N280-03M-28-BK	SFP28	SFP28	3 m	-	-	25 Gbps	Passive	Black	Black	PVC	CM	Cisco
N280-04M-28-BK	SFP28	SFP28	4 m	-	-	25 Gbps	Passive	Black	Black	PVC	CM	Dell
N280-05M-28-BK	SFP28	SFP28	5 m	-	-	25 Gbps	Passive	Black	Black	PVC	CM	Juniper
N281-03M-BK	QSFP+	4x SFP+	3 m	-	-	40 Gbps	Passive	Black	Black	PVC	-	Cisco
N282-01M-BK	QSFP+	QSFP+	1 m	-	-	40 Gbps	Passive	Black	Black	PVC	-	Cisco
N282-02M-BK	QSFP+	QSFP+	2 m	-	-	40 Gbps	Passive	Black	Black	PVC	-	Cisco
N282-03M-BK	QSFP+	QSFP+	3 m	-	-	40 Gbps	Passive	Black	Black	PVC	-	Cisco
N282-20N-28-BK	QSFP+	QSFP+	50cm	-	-	100 Gbps	Passive	Black	Black	PVC	-	Cisco
N282-01M-28-BK	QSFP+	QSFP+	1 m	-	-	100 Gbps	Passive	Black	Black	PVC	-	Cisco
N282-02M-28-BK	QSFP+	QSFP+	2 m	-	-	100 Gbps	Passive	Black	Black	PVC	-	Cisco
N282-03M-28-BK	QSFP+	QSFP+	3 m	-	-	100 Gbps	Passive	Black	Black	PVC	-	Cisco
N28H-10M-AQ	QSFP28	QSFP28	10 m	OM3	8	100 Gbps	-	Aqua	Aqua	PVC	OFNP	-

Power Cords

Connects a PC or server to a PDU or UPS system in a data rack or cabinet.



Key points:

- Fully VDE-compatible for European IT applications
- Ideal replacement for worn-out or missing power cable

Ideal for:

- Data Center
- Server room
- PDU & ATS connection

Part number	Connectors		Length	Input		COLORS		PHYSICAL		Rack configuration
	Connector 1	Connector 2		Max Amps	Voltage Compatibility (VAC)	Power Cord	Plug Color	Cable Jacket Material	Power Cord Jacket Type	
P004-P5M-EU	C13	C14	50 cm	10 A	250 V	Black	Black	PVC	H05SW-F	PDU & ATS
P004-01M-EU	C13	C14	1 m	10 A	250 V	Black	Black	PVC	H05SW-F	PDU & ATS
P004-02M-EU	C13	C14	2 m	10 A	250 V	Black	Black	PVC	H05SW-F	PDU & ATS
P004-03M-EU	C13	C14	3 m	10 A	250 V	Black	Black	PVC	H05SW-F	-
P004-04M-EU	C13	C14	4 m	10 A	250 V	Black	Black	PVC	H05SW-F	-
P004-05M-EU	C13	C14	5 m	10 A	250 V	Black	Black	PVC	H05SW-F	-
P014-P15M-EU	C14	C5	15 cm	2.5 A	250 V	Black	Black	PVC	H05SW-F	-
P014-02M-EU	C14	C5	2 m	2.5 A	250 V	Black	Black	PVC	H05SW-F	-
P058-02M-EU	Schuko	C5	2 m	2.5 A	250 V	Black	Black	PVC	H05SW-F	-
P060-02M-UK	BS1363	C5	2 m	2.5 A	250 V	Black	Black	PVC	H05SW-F	-
P032-02M-EU	C20	C13	2 m	10 A	250 V	Black	Black	PVC	H05SW-F	-
P036-02M-EU	C20	C19	2 m	16 A	250 V	Black	Black	PVC	H05SW-F	PDU & ATS
P036-03M-EU	C20	C19	3 m	16 A	250 V	Black	Black	PVC	H05SW-F	-
P047-02M-EU	C14	C19	2 m	10 A	100-250 V	Black	Black	PVC	H05SW-F	-
P047-03M-EU	C14	C19	3 m	10 A	100-250 V	Black	Black	PVC	H05SW-F	-
P050-2P5M-EU	Schuko	C19	2.5m	16 A	250 V	Black	Black	PVC	H05SW-F	-
P052-2P5M-UK	BS1363	C19	2.5m	16 A	250 V	Black	Black	PVC	H05SW-F	-
P054-01M-EU	Schuko	C13	1 m	10 A	100-250 V	Black	Black	PVC	H05SW-F	-
P054-02M-EU	Schuko	C13	2 m	10 A	100-250 V	Black	Black	PVC	H05SW-F	-
P054-03M-EU	Schuko	C13	3 m	10 A	100-250 V	Black	Black	PVC	H05SW-F	-
P056-01M-UK	BS1363	C13	1 m	10 A	250 V	Black	Black	PVC	H05SW-F	-
P056-02M-UK	BS1363	C13	2 m	10 A	250 V	Black	Black	PVC	H05SW-F	-
P056-03M-UK	BS1363	C13	3 m	10 A	250 V	Black	Black	PVC	H05SW-F	-
P070-010	IEC 309	C19	3,05 m	16 A	250 V	Black	Blue/White	PVC	SJT	-

Splitter

P004-02M-2C13EU	C14	2x C13	2 m	10 A	250 V	Black	Black	PVC	H05SW-F	-
-----------------	-----	--------	-----	------	-------	-------	-------	-----	---------	---

Plug-Lock Inserts 100 Pack



Part number	Connector 1	Connector 2	Color
PLC13BK	C14	C13	Black
PLC14YW	C13	C14	Yellow
PLC19BK	C20	C19	Black
PLC20YW	C19	C20	Yellow



Work from anywhere (WFA), Retail & Education

Docking Station, Hubs & Switches
Display mounts
Power Solutions
USB Cables
USB Adapters
USB Extenders



Docking Stations

Expand the potential of your Windows laptop, smartphone or PC's USB-C or Thunderbolt 3 port.



Key points:

- Connects up to 3 displays at the same time: extended & mirror modes
- Get fast Power Delivery (PD) charging up to 100W
- Transfer data at up to USB 3.1 Gen 2 speeds (10 Gbps)
- International power adapters (BS 1363 U.K., CEE 7/7 Schuko EU)

Ideal for:

- SoHo (Small Office, Home Office)
- Mobility

Part number	Host Connector (M)	Display Max resolution supported	Video Ports			Data Ports			Storage		Audio port	Ethernet port	Color				
			VGA	Mini DP	DP	DVI	HDMI	USB-A 2.0	USB-A 3.1 Gen 1	USB-A 3.2 Gen 1				USB-C	USB-C PD Charging	SD	Micro SD
Single display																	
U442-DOCK11-S	USB-C	4K @ 30Hz	-	-	-	-	1	-	1	1	1	60W	1	1	-	1 Gbps	Silver
U442-DOCK3-B	USB-C	4K @ 30Hz	1	-	-	-	1	-	1	-	2	100W	1	1	-	1 Gbps	Black
U442-DOCK5D-GY⁽¹⁾	USB-C	4K @ 30Hz	-	-	-	-	1	-	-	3	1	100W	1	1	-	1 Gbps	Gray
U442-DOCK40-5	USB-C	8K @ 30Hz	-	-	-	-	1	-	-	3	1	100W	-	-	-	-	Gray
U442-DOCK40-6	USB-C	8K @ 30Hz	-	-	-	-	1	-	-	2	2	100W	-	-	-	1 Gbps	Gray
U442-DOCK14-MS⁽²⁾	USB-C	4K @ 30Hz	-	-	-	-	1	1	1	1	1	100W	-	-	-	1 Gbps	Black
U442-DOCK15-S⁽³⁾	USB-C	4K @ 30Hz	-	-	-	-	1	1	-	-	1	60W	1	1	1	-	Gray
Dual displays																	
U442-DOCK1	USB-C	4K @ 30Hz	1	1	-	-	1	-	-	-	-	100W	1	1	-	1 Gbps	Silver
U442-DOCK8-GG	USB-C	4K @ 30Hz	-	-	-	-	2	-	-	3	1	100W	1	1	1	-	Gray
U442-DOCK8G-GG	USB-C	4K @ 30Hz	-	-	-	-	2	-	-	3	-	100W	1	1	-	1 Gbps	Gray
MTB3-DOCK-04	Thunderbolt 3	4K @ 60Hz	-	-	1	-	1	-	-	2	1	60W	-	-	1	1 Gbps	Black
Triple displays																	
U442-DOCK12-S	USB-C	Full HD 1080p	1	-	-	-	2	-	-	1	-	60W	-	-	-	-	Silver
U442-DOCK7D-B⁽¹⁾	USB-C	4K @ 30Hz	1	1	-	-	1	-	1	1	2	100W	1	1	1	1 Gbps	Black
U442-DOCK16-B	USB-C	4K @ 30Hz	1	1	-	-	1	-	-	2	1	60W	-	-	-	1 Gbps	Black
External Power Supply models																	
Dual displays																	
MTB3-DOCK-03INT	Thunderbolt 3	8K @ 30Hz	-	-	1	-	-	-	-	2	2	60W	Yes	Yes	1	40 Gbps	Gray
Triple displays																	
U442-DOCK4-INT	USB-C	4K @ 30Hz	1	-	1	-	1	2	1	1	1	100W	-	-	2	1 Gbps	Silver

⁽¹⁾ With Detachable Cord.

⁽²⁾ Dock for Microsoft Surface.

⁽³⁾ Dock with Removable Clip - For Laptops and Tablets.

Hubs & Switches

Connect up to 8 USB devices via a single USB port on your desktop, laptop, or tablet.



Key points:

- USB data transfer rates up to 10 Gbps
- International power adapters (BS 1363 U.K., CEE 7/7 Schuko EU)

Ideal for:

- SoHo (Small Office, Home Office)
- Mobility

Part number	Host Connector (M)	Data ports						Storage		Ethernet port	Color
		USB-A2.0	USB-A3.1 Gen 1	USB-A3.2 Gen 1	USB-B	USB-C	USB-C PD Charging	SD	Micro SD		
USB hubs											
U360-004-4A-AL	USB-A	-	4	-	-	-	-	-	-	-	Black
U360-004-SLIM	USB-A	-	4	-	-	-	-	-	-	-	Black
U460-003-3A1GB	USB-C	-	3	-	-	-	-	-	-	1 Gbps	Black
U460-003-3AM	USB-C	-	3	-	-	-	-	1	1	-	White
U460-003-3AMB	USB-C	-	3	-	-	-	-	1	1	-	Black
U460-003-3AGALC	USB-C	-	-	-	-	3	100W	-	-	1 Gbps	Gray
U460-003-3AGB-C	USB-C	-	3	-	-	1	60W	-	-	1 Gbps	Black
U460-003-3AG-C	USB-C	-	3	-	-	1	60W	-	-	1 Gbps	White
U460-004-2A2C	USB-C	-	2	-	-	2	-	-	-	-	White
U460-004-2A2CB	USB-C	-	2	-	-	2	-	-	-	-	Black
U460-004-2A2C-2	USB-C	-	-	2	-	2	-	-	-	-	Black
U460-004-4A-AL	USB-C	-	4	-	-	-	-	-	-	-	Black
U460-004-4AB-C	USB-C	-	4	-	-	1	60W	-	-	-	Black
U460-004-4A-C	USB-C	-	4	-	-	-	60W	-	-	-	White
U460-004-4A-G2	USB-C	-	-	4	-	-	-	-	-	-	Black
With Laptop Stand											
U460-ST4-4A-C	USB-C	-	4	-	-	-	-	-	-	-	Silver
External Power Supply models											
U223-010-INT	USB-A	10	-	-	-	-	-	-	-	-	Black
U360-004-R-INT	USB-A	-	-	4	-	-	-	-	-	-	Black
U360-007-INT	USB-A	-	-	7	-	-	-	-	-	-	Black
U360-007C-2X3	USB-A	5	-	2	-	-	-	-	-	-	White
U360-010C-2X3	USB-A	8	-	2	-	-	-	-	-	-	White

Multiport Adapters

Adds USB-A, USB-C PD charging and memory card ports to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, MacBook, Chromebook, smartphone or PC.





Key points:

- Gain USB-A or USB-C ports for connecting to peripherals
- HD or UHD (4K) video output
- Extended and Mirror modes for AVV models

Ideal for:

- SoHo (Small Office, Home Office)
- Mobility

Part number	Host Connector (M)	Max resolution supported	Data Ports										Ethernet port	Color		
			Video Ports					Storage								
			VGA	Mini DP	DP	DVI	HDMI	USB-A 2.0	USB-A 3.1 Gen 1	USB-A 3.2 Gen 1	USB-C	USB-C PD Charging			SD	Micro SD
Single display																
U444-06N-VGU-C	USB-C	Full HD 1080p	1	-	-	-	-	-	-	1	1	60W	-	-	1 Gbps	White
U444-06N-DGU-C	USB-C	Full HD 1080p	-	-	1	-	-	-	-	1	1	60W	-	-	-	White
U444-06N-HGUB-C	USB-C	Full HD 1080p	-	-	-	1	-	-	-	1	1	60W	-	-	1 Gbps	Black
U444-06N-HGU-C	USB-C	Full HD 1080p	-	-	-	1	-	-	-	1	1	60W	-	-	1 Gbps	White
U444-06N-HU-C	USB-C	Full HD 1080p	-	-	-	1	-	1	-	1	-	60W	-	-	-	White
U444-06N-HV4GU	USB-C	4K @ 30Hz	-	-	-	1	-	-	-	1	-	-	-	-	1 Gbps	White
U444-06N-HV4GUB	USB-C	4K @ 30Hz	-	-	-	1	-	-	-	1	-	-	-	-	1 Gbps	Black
U444-06N-H4GUBC	USB-C	4K @ 30Hz	-	-	-	1	-	-	-	1	1	60W	-	-	1 Gbps	White
U444-06N-H4GU-C	USB-C	4K @ 30Hz	-	-	-	1	-	-	-	1	1	60W	-	-	1 Gbps	Black
U444-T6N-H4GUBC	USB-C	4K @ 30Hz	-	-	-	1	-	-	-	1	1	100W	-	-	1 Gbps	Black
U444-06N-H3UC2	USB-C	4K @ 60Hz	-	-	-	1	-	3	-	1	-	100W	-	-	-	Black
U444-06N-H4UBC2	USB-C	4K @ 60Hz	-	-	-	1	-	-	-	1	1	100W	-	-	-	Black
External Power Supply models																
U444-06N-VU-C	USB-C	Full HD 1080p	1	-	-	-	-	-	1	-	1	60W	-	-	-	White
U444-06N-H4K6WC	USB-C	4K @ 60Hz	-	-	-	1	-	-	-	1	-	60W	-	-	-	White

Part number	Host Connector (M)	Display Max resolution supported	Data Ports										Storage	Ethernet port	Color		
			Video Ports					Data Ports									
			VGA	Mini DP	DP	DVI	HDMI	USB-A 2.0	USB-A 3.1 Gen 1	USB-A 3.2 Gen 1	USB-C	USB-C PD Charging				SD	Micro SD
Dual Display 																	
U444-2H-MST4K6	USB-C	4K @ 60Hz	-	-	-	-	2	-	-	-	1	-	-	-	-	-	Black
U444-2DP-MST4K6	USB-C	8K @ 30HZ	-	-	2	-	-	-	-	-	1	-	-	-	-	-	Black
MTB4-HUB3-01	Thunderbolt 4	8K @ 30Hz	-	-	-	-	-	-	-	1	3	60W	-	-	-	-	Gray
Triple Display 																	
U444-06N-HVDPW	USB-C	4K @ 30Hz	1	-	1	-	1	-	1	-	1	-	-	-	-	-	White
U360-004-R-INT	USB-A	-	-	-	-	-	-	-	-	4	-	-	-	-	-	-	Black
U360-007-AL-INT	USB-A	-	-	-	-	-	-	-	-	7	-	-	-	-	-	-	Black
U360-007-INT	USB-A	-	-	-	-	-	-	-	-	7	-	-	-	-	-	-	Black
U223-010-INT	USB-A	-	-	-	-	-	-	10	-	-	-	-	-	-	-	-	Black

What are you looking for?
Find the right Docking Station, Multiports adapter or Hubs & Switches thanks to our online configurator.



Height-Adjustable Workstations

Sit-stand workstation transforms your desk space into an ergonomic working environment without modifying the surface.



Key points:

- Desktop & Wall mounting location
- Fixed and Mobile Workstations
- Height-adjustable models
- Single display configuration
- Integrated Thin-Client Mount and Cable Management




Ideal for:

- Healthcare
- Commercial
- Industrial
- Office settings

Part number	Screen size		Mounting Location	VESA Pattern (mm)		Max Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color	
	Min	Max		Min	Max						
WWSS1332C	13"	32"	Desktop	Desk Clamps & Grommets	75x75 mm	100x100 mm	8 kg	Full	Swivel: 180° Rotate: 360°	Yes	Silver
WWSSD3622	-	-	Desktop	Freestanding	-	-	15 kg	-	-	Yes	Black
WWSS1327RWTC	13"	27"	Wall	-	75x75 mm	100x100 mm	8 kg	Full	Tilt: -15/+15 Swivel: -90/+90 Rotate: 360°	Yes	Silver
WWSS1332W	13"	32"	Wall	-	75x75 mm	100x100 mm	8 kg	Full	Swivel: 180° Rotate: 360°	Yes	Silver
Mobile Workstations											
WWSS1DWSTAA	-	-	Floor	-	75x75 mm	100x100 mm	7 kg	Swivel Tilt	Swivel: 360° Tilt: 60°	Yes	Ivory
WWSS2DWSTAA(1)	-	-	Floor	-	-	-	20 kg	-	-	-	Ivory
WWSSRSTAA	-	-	Floor	-	-	-	20 kg	-	-	-	Ivory

(1) Mobile Workstation with 2x Adjustable Shelves, 2x Metal Drawers.

Accessories

	Part number	Accessory Type	Screen size		Mounting Location	VESA Pattern (mm)		Max Weight Capacity	Motion	Degrees of Motion
			Min	Max		Min	Max			
	DMA1327SD	Dual Bar Mount	13"	27"	Desktop Desk Clamp	75x75 mm	100x100 mm	10 kg	Full	Tilt: 15/+15° Rotate: 360°
	DMATC	Display mount Adapter Kit	-	-	Wall	75x75 mm	100x100 mm	5 kg	Fixed	-
	DMCCASTER	Locking Caster Kit for Rolling TV/Monitor Carts - Heavy Duty, Swivel, 4 in. Diameter, 4 Casters								

Desktop Monitor Mounts

Get an ergonomic sit-stand workstation without modifying the entire work surface.







Key points:

- Monitor stand with heavy-duty base remains stable on your desk during adjustment
- Durable steel construction blends into any décor and supports up to 12 kg per monitor

Ideal for:

- Healthcare
- Commercial
- SoHo (Small Office, Home Office)
- Office configuration

Part number	Screen size (")		Mounting Location	VESA Pattern (mm)		Max Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
	Min	Max		Min	Max					
Single Display 										
DDR1327SE	13"	27"	Freestanding	75x75 mm	100x100 mm	10 kg	Full	Tilt: -45/+45° Swivel: 180° Rotate: 360°	Yes	Black
DDV1727S	17"	27"	Freestanding	75x75 mm	100x100 mm	6 kg	Swivel Tilt	Tilt: -20/+60° Swivel: 30° Rotate: 360°	Yes	Black
DDR1327SFC	13"	27"	Desk Clamp	75x75 mm	100x100 mm	10 kg	Full Flex Arm	Tilt: -15/+15° Swivel: 180° Rotate: 360°	Yes	Black
DDR1732NBMTAA	17"	32"	Desk Clamp	75x75 mm	100x100 mm	6 kg	Full-motion arms	Swivel: 180° Rotate: 360°	Yes	Silver
DDR1732SC	17"	32"	Desk Clamp	75x75 mm	100x100 mm	8 kg	Swivel Tilt	Tilt: -10/+10° Swivel: 10° Rotate: 10°	Yes	Black
DDR1327S	13"	27"	Desk Clamps & Grommets	75x75 mm	100x100 mm	9 kg	Full-motion arms	Tilt: -40/+90° Swivel: 180° Rotate: 360°	Yes	Black
DDR1732SAL	17"	32"	Desk Clamps & Grommets	75x75 mm	100x100 mm	9 kg	Full-motion arms	Tilt: -90/+90° Swivel: 90° Rotate: 90°	Yes	Silver
Dual Displays 										
DDR1527SDC	15"	27"	Freestanding	75x75 mm	100x100 mm	8 kg	Full	Tilt: -20/+20° Swivel: 20° Rotate: 360°	Yes	Black
DDR1327SDD	13"	27"	Freestanding	75x75 mm	100x100 mm	12 kg	Full	Tilt: -45/+45° Swivel: 180° Rotate: 360°	Yes	Black
DDR1327SDFC-1	13"	27"	Desk Clamp	75x75 mm	100x100 mm	8 kg	Full	Tilt: -30/+30° Swivel: 180° Rotate: 360° (head)	Yes	Black
DDR1727DC	17"	27"	Desk Clamps & Grommets	75x75 mm	100x100 mm	7 kg	Swivel Tilt	Tilt: -10/+10° Swivel: 10° Rotate: 360°	Yes	Black
DDR1732DAL	17"	32"	Desk Clamps & Grommets	75x75 mm	100x100 mm	9 kg	Full	Tilt: -90/+90° Swivel: 90° Rotate: 90°	Yes	Silver
Triple Displays 										
DDR1730TAL	17"	30"	Desk Clamps & Grommets	75x75 mm	100x100 mm	7 kg	Full	Tilt: -90/+90° Swivel: 90° Rotate: 90°	Yes	Silver
Quad Displays 										
DDR1327MQ	13"	27"	Freestanding	75x75 mm	100x100 mm	8 kg	Full	-45/+45° Tilt 180° Swivel 360° Rotate	-	Black

Desktop Charging Stations

USB charger keeps electronic devices, including tablets, smartphones and laptops, at full capacity via USB connection.



Key points:

- Charge anywhere AC power is available - no computer required
- Charge Up to 10 Devices at the Same Time
- 14 Brackets are adjustable to accommodate number and size of devices being charged
- Protect against overheating, overcurrent and overcharging

Ideal for:

- Healthcare
- Commercial
- SoHo (Small Office, Home Office)
- Office configuration

Part number	Device Compatibility	Number of devices	Charging Method	Connections		Total Charging Amps/Watts	Input Plug Type	Input Plug Type Details
				Ports type	Number of Charging ports			
U280-010-ST-CEE	Phone Tablet Amazon Kindle	Up to 10	USB	USB-A	10x 2.4A	8A / 96W	-	C5 to CEE 7/7 Schuko Power

Desktop KVM Switches

Controls up to 4 desktop or notebook computers using one centralized video monitor and USB keyboard/mouse.



Key points:

- Controls 2 or 4 desktop or notebook computers using one centralized monitor and USB keyboard/mouse
- Connect USB 3.0 peripherals, such as hard drives and webcams, and share them between computers

Ideal for:

- Healthcare
- Digital Signage
- SoHo (Small Office, Home Office)
- Office open space

Part number	Number of ports	Concurrent Users	PC/Server Connections		Video			Cables/Cable Kits/SIUs
			Side A	Side B	Ports	Details	Max resolution supported	
B004-DP2UA2-K	2	1	2x DisplayPort (F) 2x 3.5mm (F) 2x USB-B (F)	DisplayPort (F) 3.5mm (F) 2x USB-A (F)	-	DP 1.2	4K @60Hz	Included
B004-DPUA2-K	2	1	2x DisplayPort (F) 2x USB-B 3.0 (F) 4x 3.5mm (F)	DisplayPort (F) 2x USB-A 3.0 (F) 2x USB-A (F) 2x 3.5mm (F)	-	DP 1.1	2K @60Hz	Included
B004-DPUA4-K	4	1	4x DisplayPort (F) 4x USB-B 3.0 (F) 8x 3.5mm (F)	DisplayPort (F) 2x USB-A 3.0 (F) 2x USB-A (F) 2x 3.5mm (F)	-	DP 1.1	2K @60Hz	Included
B004-VUA2-K-R	2	1	2x HD15 (F)	HD15 (F) 2x USB-A (F) 2x 3.5mm (F) 2x USB Mini-B (F)	3x HD15 (F)	-	2048x1436 px @60Hz	Included
B005-DPUA2-K	2	1	3x 3.5mm (F) 2x USB-A 3.0 (F)	2x USB-A (F) HDMI (F) 3x DisplayPort (F) 2x USB-B 3.0 (F) 6x 3.5mm (F) 3.5mm x 1.35mm	-	DP 1.4 HDCP 1.4; 2.2	4K @60Hz	Included
B005-DPUA4	4	1	3x 3.5mm (F) 2x USB-A 3.0 (F)	2x USB-A (F) HDMI (F) 4x USB-B 3.0 (F) 5x DisplayPort (F) 10x 3.5mm (F) 3.5mm x 1.35mm	-	DP 1.4 HDCP 1.4; 2.2	4K @60Hz	P785-DPKITxx
B005-HUA2-K	2	1	(3) 3.5MM (F) (2) USB 3.0 A (F)	(2) USB-A (F) (3) HDMI (F) (6) 3.5MM (F) (2) USB 3.0 B (F) 3.5mm x 1.35mm	-	HDCP 1.4; 2.2	4K	Included
B005-HUA4	4	1	(3) 3.5MM (F) (2) USB 3.0 A (F)	(2) USB A (F) (5) HDMI (F) (4) USB 3.0 B (F) (10) 3.5MM (F)	-	HDCP 1.4; 2.2	4K	P785-HKITxx
B032-DPUA2	2	1					4K	Built-in cables
B032-HUA2	2	1		HDMI, USB			1920x1200	Built-in cables
B032-VU1	1	1		VGA, USB			1920x1200	Built-in cables
B032-VU2	2	1		VGA, USB			2048x1536	Built-in cables



Looking for more KVM Switches?

Go to the IT Infrastructure section, page 19.

USB-A 2.0 Cables

Make the connection between a USB device and your computer's USB port.



Key points:

- All USB port types from 31 cm up to 4,57 m
- Data Transfer rate: up to 480 Mbps
- Heavy-Duty models with Aramid Fiber jacket
- MFi-Certified for Broad Device Compatibility / RoHS compliant

Ideal for:

- Commercial
- Office settings

Part number	connections		Cable type	Connector Style	Length	PLATING		Cable Jacket Color
	Connector A	Connector B				Connector	Contact	
U021-003	USB-A (M)	USB-B (M)	Passive	Straight	91 cm	Gold	Gold	Gray
U022-006	USB-A (M)	USB-B (M)	Passive	Straight	1,83 m	Gold	Gold	Black
U022-006-BE	USB-A (M)	USB-B (M)	Passive	Straight	1,83 m	Gold	Gold	Beige
U022-010	USB-A (M)	USB-B (M)	Passive	Straight	3,05 m	Gold	Gold	Black
U022-010-BE	USB-A (M)	USB-B (M)	Passive	Straight	3,05 m	Gold	Gold	Beige
U022-010-COIL	USB-A (M)	USB-B (M)	Passive	Coiled Cable	3,05 m	Gold	Gold	Black
U022-015	USB-A (M)	USB-B (M)	Passive	Straight	4,57 m	Gold	Gold	Black
U023-003	USB-A (M)	USB-B (M)	Passive	Ferrite Chokes	91 cm	Gold	Gold	Black
U023-006	USB-A (M)	USB-B (M)	Passive	Ferrite Chokes	1,83 m	Gold	Gold	Black
U030-003	USB-A (M)	USB Mini-B 5 Pin (M)	Passive	Straight	91 cm	Gold	Gold	Black
U030-006	USB-A (M)	USB Mini-B 5 Pin (M)	Passive	Straight	1,83 m	Gold	Gold	Black
U052-06N	USB-A (M)	Micro USB-B (M)	Passive	Straight	15,24 cm	Nickel	Gold	
U050-003	USB-A (M)	Micro USB-B (M)	Passive	Straight	91 cm	Nickel	Gold	Black
U050-006	USB-A (M)	Micro USB-B (M)	Passive	Straight	1,83 m	Nickel	Gold	Black
U050-010	USB-A (M)	Micro USB-B (M)	Passive	Straight	3,05 m	Nickel	Gold	Black
U038-003	USB-A (M)	USB-C (M)	Passive	Straight	91 cm	Nickel	Gold	Black
U038-003-FL	USB-A (M)	USB-C (M)	Passive	Flat	91 cm	Nickel	Gold	Black
U038-C13	USB-A (M)	USB-C (M)	Passive	USB-IF certified	3,96 m	Nickel	Gold	Black
U038-006	USB-A (M)	USB-C (M)	Passive	Straight	1,83 m	Nickel	Gold	Black
U038-006-FL	USB-A (M)	USB-C (M)	Passive	Flat	1,83 m	Nickel	Gold	Black
Angled								
U038-003-CRA	USB-A (M)	USB-C (M)	Passive	Right-Angled	91 cm	Nickel	Gold	Black
U038-006-CRA	USB-A (M)	USB-C (M)	Passive	Right-Angled	1,83 m	Nickel	Gold	Black
All-in-one cables								
M101-006-LMC-BK	USB-A (M)	Lightning (M) Micro USB-B (M) USB-C (M)	Passive	Straight	1,83 m	Nickel	Gold	Black
Heavy Duty (Aramid Fiber)								
U050-006-GY-MAX	USB-A (M)	Micro USB-B (M)	Passive	Straight	1,83 m	Nickel	Gold	Dark Gray / Black
U050-010-GY-MAX	USB-A (M)	Micro USB-B (M)	Passive	Straight	3,05 m	Nickel	Gold	Dark Gray / Black
U038-003-GY-MAX	USB-A (M)	USB-C (M)	Passive	Straight	91 cm	Nickel	Gold	Dark Gray / Black
U038-006-GY-MAX	USB-A (M)	USB-C (M)	Passive	Straight	1,83 m	Nickel	Gold	Dark Gray / Black
U038-010-GY-MAX	USB-A (M)	USB-C (M)	Passive	Straight	3,05 m	Nickel	Gold	Dark Gray / Black

USB-A 2.0 Reversible Cables

Reversible USB connector plugs in any direction.



Key points:

- High-speed USB or AC charging
- Convenient Syncing for updates and backups
- Steel enclosure and locks for comprehensive protection
- Clutter-reducing organization of devices and cables

Ideal for:

- Commercial
- Office settings

Part number	Connections		Cable type	Length	Cable Jacket Color	
	Connector A	Connector B				
UR020-003	USB-A	USB-A	Passive	91 cm	Black	
UR020-006	USB-A	USB-A	Passive	1,83m	Black	
UR020-010	USB-A	USB-A	Passive	3,05 m	Black	
UR022-001	USB-A	USB-B	Passive	31 cm	Black	
UR022-003	USB-A	USB-B	Passive	91 cm	Black	
UR022-006	USB-A	USB-B	Passive	1,83m	Black	
UR022-010	USB-A	USB-B	Passive	3,05 m	Black	
U024-06N-IDC	USB-A	4-PIN	Passive	15 cm	Black	
UR030-06N	USB-A	Mini-B	Passive	15,24 cm	Black	
UR030-001	USB-A	Mini-B	Passive	31 cm	Black	
UR030-003	USB-A	Mini-B	Passive	91 cm	Black	
UR030-006	USB-A	Mini-B	Passive	1,83m	Black	
UR050-003	USB-A	Micro-B	Passive	91 cm	Black	
UR050-003-WH	USB-A	Micro-B	Passive	91 cm	White	
Angled						
UR020-003-RA	USB-A	USB-A	Passive	Right/Left	91 cm	Black
UR020-006-RA	USB-A	USB-A	Right/Left	Right/Left	1,83m	Black
UR024-000-UP	USB-A	USB-A	-	Up	-	Black
UR030-006-LAB	USB-A	Mini-B	Passive	Left	1,83m	Black
UR030-003-RAB	USB-A	Mini-B	Passive	Right	91 cm	Black
UR030-006-RAB	USB-A	Mini-B	Passive	Right	1,83m	Black
UR050-003-RA	USB-A	Micro-B	Passive	Right/Left	91 cm	Black

USB-A 2.0 Extension Cables

Extend distances of the fast USB 2.0.



Key points:

- Male / Female cables
- Data Transfer rate: up to 480 Mbps
- RoHS compliant
- Gold plated connectors provide superior conductivity

Ideal for:

- Commercial
- Office settings
- WFA

Part number	Connections		Cable type	Length	Cable Jacket Color	
	Connector A	Connector B				
U024-001-KPA-BK	USB-A (M)	USB-A (F)	Passive	31cm	Black	
U024-003	USB-A	USB-A	Passive	91 cm	Black	
U024-006	USB-A	USB-A	Passive	1,83m	Black	
U024-006-BE	USB-A	USB-A	Passive	1,83m	Beige	
U024-010	USB-A	USB-A	Passive	3,05 m	Black	
U024-016	USB-A	USB-A	Passive	4,88m	Black	
Angled						
U005-10I	USB-A	USB-A	Passive	Right	25,4cm	Black
Reversible						
UR024-06N	USB-A	USB-A	Passive		15,24cm	Black
UR024-001	USB-A	USB-A	Passive		31 cm	Black
UR024-18N-RA	USB-A	USB-A	Passive	Right/Left	45,72cm	Black
UR024-006	USB-A	USB-A	Passive		1,83m	Black
UR024-010	USB-A	USB-A	Passive		3,05 m	Black

USB-C 2.0 Cables

Connect smartphones, computers, wall chargers and other USB-C devices.



Key points:

- RoHS, REACH & UKCA compliant

Ideal for:

- Commercial
- Office settings

Part number	Connections		Cable type	Length	Cable Jacket Color	
	Connector A	Connector B				
U040-006	USB-C	USB-B	Passive		1,83m	Black
U040-006-MICRO	USB-C	Micro-B	Passive		1,83m	Black
U040-003-C	USB-C	USB-C	Passive		91cm	Black
U040-003-C-5A	USB-C	USB-C	Passive	Up to 25A /100W	91cm	Black
U040-003-C-FL	USB-C	USB-C	Passive	Flat	91cm	Black
U040-006-C	USB-C	USB-C	Passive		1,83m	Black
U040-006-C-5A	USB-C	USB-C	Passive	Up to 25A /100W	1,83m	Black
U040-006-C-FL	USB-C	USB-C	Passive	Flat	1,83m	Black
U040-006-MINI	USB-C	Mini-B	Passive		1,83m	Black
U040-C13-C-5A	USB-C	USB-C	Passive		3,96m	Black
U040-C1M-C-5A	USB-C	USB-C	Passive		1m	Black
U040-C2M-C-5A	USB-C	USB-C	Passive		2m	Black
U040-C3M-C-5A	USB-C	USB-C	Passive		3m	Black
Angled						
U040-01M-C-RA	USB-C	USB-C	Passive	Right	1m	Black
U040-02M-C-RA	USB-C	USB-C	Passive	Right	2m	Black
U040-02M-C-5ARA	USB-C	USB-C	Passive	Right Up to 25A /100W	2m	Black

Lightning Cables

Charges and synchronizes your Apple iPhone, iPad or iPod using the USB port on your computer or wall/car charger.



Key points:

- MFi-Certified for Broad Device Compatibility
- USB port types from 25 cm up to 3,05 m
- Angled cables
- RoHS, REACH & UKCA compliant

Ideal for:

- Commercial
- Office settings

Part number	Connections		Cable type	Length	Cable Jacket Color
	Connector A	Connector B			
M100-10N-BK	USB-A	Lightning	Passive	25cm	Black
M100-003-BK	USB-A	Lightning	Passive	91 cm	Black
M100-003-WH	USB-A	Lightning	Passive	91 cm	White
M100-004COIL-BK	USB-A	Lightning	Passive	Coiled 1,22m	Black
M100-006-BK	USB-A	Lightning	Passive	1,83m	Black
M100-010-BK	USB-A	Lightning	Passive	3,05 m	Black
M100-010-WH	USB-A	Lightning	Passive	3,05 m	White
M102-003-WH	USB-C	Lightning	Passive	91 cm	White
M102-01M-BK	USB-C	Lightning	Passive	1m	Black
M102-02M-BK	USB-C	Lightning	Passive	2m	Black
M102-03M-BK	USB-C	Lightning	Passive	3m	Black
M102-01M-WH	USB-C	Lightning	Passive	1m	White
M102-02M-WH	USB-C	Lightning	Passive	2m	White

Angled

M100-003-LRA-WH	USB-A	Lightning	Passive	Right	91 cm	White
M100-006-LRA-WH	USB-A	Lightning	Passive	Left	1,83m	White

Heavy-duty (Aramid fiber)

M100-001-GY-MAX	USB-A	Lightning	Passive		31 cm	Dark Gray / Black
M100-003-HD	USB-A	Lightning	Passive		91 cm	Black / White
M100-003-GY-MAX	USB-A	Lightning	Passive		91 cm	Dark Gray / Black
M100-006-HD	USB-A	Lightning	Passive		1,83m	Black / White
M100-006-GY-MAX	USB-A	Lightning	Passive		1,83m	Dark Gray / Black
M100-010-HD	USB-A	Lightning	Passive		3,05 m	Black / White
M100-010-GY-MAX	USB-A	Lightning	Passive		3,05 m	Dark Gray / Black
M102-010-HD	USB-C	Lightning	Passive		3,05 m	Black / White

Pack of 10 units

M100-10N-BK-10	USB-A	Lightning	Passive		25cm	Black
----------------	-------	-----------	---------	--	------	-------

USB 3.1 Gen 1 Cables

Connects peripherals and patch bays with female USB-A ports to your computer, laptop or other compatible USB 3.0 device.



Key points:

- Thunderbolt 3 Compatible
- Up to 5 Gbps
- RoHS, REACH & UKCA compliant

Ideal for:

- Commercial
- Office settings

Part number	Connections		Cable type	Length	Cable Jacket Color	
	Connector A	Connector B				
U320-003-BK	USB-A	USB-A	Passive	91 cm	Black	
U320-006-BK	USB-A	USB-A	Passive	1,83m	Black	
U322-003-BK	USB-A	USB-B	Passive	91 cm	Black	
U322-006-BK	USB-A	USB-B	Passive	1,83m	Black	
U322-010	USB-A	USB-B	Passive	3,05 m	Blue	
U322-010-BK	USB-A	USB-B	Passive	3,05 m	Black	
U322-015	USB-A	USB-B	Passive	4,57m	Blue	
U322-015-BK	USB-A	USB-B	Passive	4,57m	Black	
U325-006	USB-A	USB-A	Panel Mount Couplers	1,83m	Black	
U325-010	USB-A	USB-A	Panel Mount Couplers	3,05 m	Black	
U325-015	USB-A	USB-A	Panel Mount Couplers	4,57m	Black	
U326-001-BK	USB-A	Micro-B	Passive	30cm	Black	
U326-003	USB-A	Micro-B	Passive	91 cm	Blue	
U326-003-BK	USB-A	Micro-B	Passive	91 cm	Black	
U326-006	USB-A	Micro-B	Passive	1,83m	Blue	
U326-006-BK	USB-A	Micro-B	Passive	1,83m	Black	
U328-025	USB-A	USB-B	Active Repeater	7,62m	Black	
U328-025-1	USB-B	2x USB-A	Active Repeater	7,62m	Black	
U328-036	USB-A	USB-B	Active Repeater	10,97m	Black	
U420-003	USB-C	USB-C	Passive	91 cm	Black	
U420-006	USB-C	USB-C	Passive	1,83m	Black	
U420-C06	USB-C	USB-C	Passive	1,83m	Black	
U420-006-5A	USB-C	USB-C	Passive	5A / 100W	1,83m	Black
U420-010	USB-C	USB-C	Passive	3,05 m	Black	
U428-06N-F	USB-C (M)	USB-A (F)	Passive	Pigtail	15,24cm	Black
U428-C6N-F	USB-C (M)	USB-A (F)	Passive	Pigtail / USB-IF	15,24cm	Black
U428-20N	USB-C	USB-A	Passive		50,8cm	Black
U428-003	USB-C	USB-A	Passive		91 cm	Black
U428-006	USB-C	USB-A	Passive		1,83m	Black
Angled						
U420-001-RA	USB-C (M) Right Angle	USB-C (M)	Passive		30cm	Black
U420-01M-RA	USB-C (M) Right Angle	USB-C (M)	Passive		1m	Black
U420-02M-RA	USB-C (M) Right Angle	USB-C (M)	Passive		2m	Black
U428-003-CRA	USB-C (M) Right Angle	USB-A (M)	Passive		91 cm	Black
U428-06N-F-CRA	USB-C (M) Right Angle	USB-A (F)	Passive	Pigtail	15,24cm	Black

USB 3.2 Gen 2 Cables

USB 3.2 to USB cable connects a smartphone or other USB-C device to the port on your computer, wall charger or car charger.



Key points:

- Thunderbolt 3 Compatible
- Up to 10 Gbps
- RoHS, REACH & UKCA compliant

Ideal for:

- Commercial
- Office settings

Part number	Connections		Cable type		Length	Cable Jacket Color
	Connector A	Connector B				
U420-20N-G2-5A	USB-C (M)	USB-C (M)	Passive	5A / 100W	50,8 cm	Black
U420-003-G2-5A	USB-C (M)	USB-C (M)	Passive	5A / 100W	91 cm	Black
U420-C03-G2-5A	USB-C (M)	USB-C (M)	Passive	5A / 100W USB-IF	91 cm	Black
U422-003-G2	USB-C (M)	USB-B (M)	Passive		91 cm	Black
U426-003-G2	USB-C (M)	Micro-B (M)	Passive		91 cm	Black
U428-20N-G2	USB-C (M)	USB-A (M)	Passive		50,8 cm	Black
U428-003-G2	USB-C (M)	USB-A (M)	Passive		91 cm	Black
U428-C03-G2	USB-C (M)	USB-A (M)	Passive		91 cm	Black

Plenum-Rated Fiber Active Optical Cable

U328F-15M	USB-A	USB-B	Active (AOC)		15m	Black
U328F-20M	USB-A	USB-B	Active (AOC)		20m	Black
U328F-30M	USB-A	USB-B	Active (AOC)		30m	Black
U420F-10M-V	USB-C (M)	USB-C (M)	Active (AOC) Backward Compatible 4K @ 60 Hz		10 m	Black
U420F-15M-V	USB-C (M)	USB-C (M)	Active (AOC) Backward Compatible 4K @ 60 Hz		15 m	Black
U420F-30M-V	USB-C (M)	USB-C (M)	Active (AOC) Backward Compatible 4K @ 60 Hz		30 m	Black
U420F-10M-D3	USB-C (M)	USB-C (M)	Active (AOC) Data only		10 m	Black
U420F-15M-D3	USB-C (M)	USB-C (M)	Active (AOC) Data only		15 m	Black
U420F-20M-D3	USB-C (M)	USB-C (M)	Active (AOC) Data only		20 m	Black
U420F-30M-D3	USB-C (M)	USB-C (M)	Active (AOC) Data only		30 m	Black
U420F-10M-D321	USB-C (M)	USB-C (M)	Active (AOC) Backward Compatible		10 m	Black
U420F-15M-D321	USB-C (M)	USB-C (M)	Active (AOC) Backward Compatible		15 m	Black

Angled

U420-01M-G25ARA	USB-C (M) Right Angle	USB-C (M)	Passive	5A / 100W	1 m	Black
-----------------	-----------------------	-----------	---------	-----------	-----	-------

USB-C 3.0 Extension Cables

High-speed USB extension cable extends the distance between two USB devices.



Key points:

- USB-C Male / Female cables
- Up to 5 Gbps (3.1 Gen 1) & up to 10 Gbps (3.2 Gen 2)
- RoHS, REACH & UKCA compliant

Ideal for:

- Commercial
- Office settings

Part number	Connections		Cable type	Length	Cable Jacket Color
	Connector A	Connector B			
3.1 Gen 1 USB cable					
U324-003-BK	USB-A	USB-A	Active Extension Cable	91cm	Black
U330-05M-C2C	USB-C	USB-C	Active Extension Cable	5m	Black
U330F-10M-G1	USB-A	USB-A Micro-B	Active Extension Cable	10m	Black
U330F-15M-G1	USB-A	USB-A Micro-B	Active Extension Cable	15m	Black
U330F-20M-G1	USB-A	USB-A Micro-B	Active Extension Cable	20m	Black
U330F-30M-G1	USB-A	USB-A Micro-B	Active Extension Cable	30m	Black
U330F-50M-G1	USB-A	USB-A Micro-B	Active Extension Cable	50m	Black
U421-003	USB-C	USB-C	Extension Cable	91 cm	Black
U421-006	USB-C	USB-C	Extension Cable	1,83m	Black
3.2 Gen 2 USB cable					
U330-05M-C2A-G2	USB-C	USB-A	Active Extension Cable	5m	Black
U421-20N-G2	USB-C	USB-C	Passive	50cm	Black
U421-20N-G2-RA	USB-C	USB-C	Passive	50cm	Black
U428F-10M-D3	USB-A	USB-C	Active (AOC)	10m	Black
U428F-10M-D321	USB-A	USB-C	Active (AOC) Backward Compatible	10m	Black
U428F-15M-D3	USB-A	USB-C	Active (AOC)	15m	Black
U428F-15M-D321	USB-A	USB-C	Active (AOC) Backward Compatible	15m	Black
U428F-20M-D3	USB-A	USB-C	Active (AOC)	20m	Black
U428F-30M-D3	USB-A	USB-C	Active (AOC)	30m	Black

Thunderbolt Cables

Connects 2 Thunderbolt 3 devices, including MacBooks and Chromebooks, for charging them or transmitting 4K video at 20 or 40 Gbps speeds.



Key points:

- Compatible with all USB-C and Thunderbolt 3 devices
- Provide 5A (100W) power output for charging and powering large-capacity mobile devices
- Reversible Thunderbolt 3 plugs connect in either direction for immediate no-fuss use

Ideal for:

- Apple's devices
- Commercial
- Office settings

Part number	Connections		Cable				Video		Color
	Connector A	Connector B	Type	Data Transfer Rate	Power Delivery	Length	Max Supported Video Resolution	DP	
MTB3-00M5-5A-B	Thunderbolt 3 (Type-C (M))	Thunderbolt 3 (Type-C (M))	Passive	20 Gbps	100 W	50 cm	4K x 2K @ 60 Hz	1.2	Black
MTB3-01M5-5A-B	Thunderbolt 3 (Type-C (M))	Thunderbolt 3 (Type-C (M))	Passive	20 Gbps	100 W	1,5 m	4K x 2K @ 60 Hz	1.2	Black
MTB3-01M-5A-B	Thunderbolt 3 (Type-C (M))	Thunderbolt 3 (Type-C (M))	Passive	20 Gbps	100 W	1 m	4K x 2K @ 60 Hz	1.2	Black
MTB3-02M-5A-B	Thunderbolt 3 (Type-C (M))	Thunderbolt 3 (Type-C (M))	Passive	20 Gbps	100 W	2 m	4K x 2K @ 60 Hz	1.2	Black

USB Couplers

Converts a standard USB port into a more convenient down-angled USB port in tight spaces, such as behind furniture or against a wall.



Key points:

- Supports USB 3.0 SuperSpeed data transfer rates up to 5 Gbps—10x faster than USB 2.0
- Durable one-piece molded adapter fits easily in pocket or bag for connecting anywhere
- Plug-and-play

Ideal for:

- Powering computers
- Printers
- Home/office peripherals

Part number	Connections				Angled
	Connector A	Connector B	USB generation	Data transfer rate (up to)	
U324-000-DN	USB-A (M)	USB-A (F)	3.0	5 Gbps	Down
U324-000-UP	USB-A (M)	USB-A (F)	3.0	5 Gbps	Up
U420-000-F-UD	USB-C (M)	USB-C (F)	3.0	10 Gbps	Right

USB Adapters

Easily connect your PC, laptop or tablet to a Gigabit Ethernet network, Serial, Audio, Video or Memory card devices.



Key points:

- Data transfer speeds up to 5 Gbps—10 times faster than USB 2.0
- Gold-plated contacts for maximum conductivity and minimum data loss
- Backward compatible with previous USB generations

Ideal for:

- Office configuration
- SoHo

Part number	Connections		VIDEO				Cable		
	Connector A	Connector B	USB generation	Data transfer rate (up to)	Max Supported Video Resolution	HDCP	DP	Type	Cable Length (m)
Serial / Ethernet									
USA-19HS	USB-A (M)	DB89 (M)	2.0	480 Mbps	-	-	-	-	91 cm
USA-19HS-C	USB-C (M)	DB89 (M)		230 Kbps	-	-	-	-	91 cm
U209-005-C	USB-C (M)	DB89 (M)	2.0	480 Mbps	-	-	-	-	1,5 m
U209-005-COM	USB-A (M)	DB89 (M)	2.0	480 Mbps	-	-	-	-	1,5 m
U209-005-DB25	USB-A (M)	DB89 (M)	2.0	480 Mbps	-	-	-	-	1,5 m
U209-006-2	USB-A (M)	2x DB89 (M)	2.0	480 Mbps	-	-	-	-	1,83 m
U209-006-RJ45-X	USB-A (M)	RJ45 (M)	2.0	480 Mbps	-	-	-	-	1,83 m
U209-006-RJ45XC	USB-C (M)	RJ45 (M)	2.0	480 Mbps	-	-	-	-	1,83 m
U209-18N-NULL	USB-A (M)	DB89 (F)	2.0	480 Mbps	-	-	-	-	45,72 cm
USB									
U261-001-BT4	USB-A (M)	-	2.0	480 Mbps	-	-	-	Bluetooth 4.0	-
U261-001-BT5	USB-A (M)	-	2.0	480 Mbps	-	-	-	Bluetooth 5.0	-
U329-000	USB-A (M)	USB-C (F)	3.0	5 Gbps	-	-	-	-	-
U329-000-10G	USB-A (M)	USB-C (F)	3.0	10 Gbps	-	-	-	-	-
U428-000-F	USB-C (M)	USB-A (F)	3.0	5 Gbps	-	-	-	-	-
UR024-000-RA	Reversible USB-A (M)	USB-A (M)	2.0	480 Mbps	-	-	-	Right angle	-
Ethernet (Cat5/5e, Cat6, Cat6a)									
U336-000-GB-AL	USB-A (M)	RJ45 (F)	3.0	5 Gbps	-	-	-	-	Pigtail
U336-000-GBW	USB-A (M)	RJ45 (F)	3.0	5 Gbps	-	-	-	-	Pigtail
U336-U03-GB	USB-A (M)	RJ45 (F)	3.0	5 Gbps	-	-	-	-	30 cm
U436-06N-GB	USB-C (M)	RJ45 (F)	3.0	5 Gbps	-	-	-	-	Pigtail
U436-06N-GB-C	USB-C (M)	USB-C (F) RJ45 (F)	3.0	5 Gbps	-	-	-	-	Pigtail
U436-06N-GBW	USB-C (M)	RJ45 (F)	3.0	5 Gbps	-	-	-	-	Pigtail
U436-06N-GBW-RA	USB-C (M)	RJ45 (F)	3.0	5 Gbps	-	-	-	Right Angle	Pigtail
Fiber									
U336-MMF-1G-LC	USB-A (M)	LC (F)	3.0	5 Gbps	-	-	-	Multimode	550 m

Memory Card Readers

U338-06N-SATA-B	USB-A (M)	22 PIN SATA + POWER (F)	3.0	5 Gbps	-	-	-	-	Pigtail
U352-000-MD-AL	USB-A (M) SD (M)	Micro SD (M) CF (F)	3.0	5 Gbps	-	-	-	-	Pigtail
U352-000-SD	USB-A (M)	Micro SD (F) SD (F)	3.0	5 Gbps	-	-	-	-	-
U352-000-SD-R	USB-A (M)	SD (F)	3.0	5 Gbps	-	-	-	-	-
U352-06N-SD	USB-A (M)	Micro SD (F) SD (F)	3.0	5 Gbps	-	-	-	-	Pigtail
U452-000-SD-A	USB-A (M) USB-C (M)	SD (F) Micro SD (F)	3.0	5 Gbps	-	-	-	-	-
U452-003	USB-C (M) SD (F)	Micro SD (F) CF (F)	3.0	5 Gbps	-	-	-	-	Pigtail

IDE/EIDE

U338-000	USB-A (M)	22 PIN SATA + POWER (F) 40 POS. SOCKET(F)	3.0	5 Gbps	-	-	-	-	-
U338-06N	USB-A (M)	7 PIN SATA(M) 40 POS. SOCKET(F) 44 Header IDC(F)	3.0	5 Gbps	-	-	-	-	-

Audio (Stereo)

U437-002	USB-C (M)	1x 3.5MM (F) 1x 3.5MM (F)	2.0	480 Mbps	-	-	-	-	27,3 cm
-----------------	-----------	------------------------------	-----	----------	---	---	---	---	---------

Video

U344-001-VGA	USB-A (M)	HD15 (M)	3.0	5 Gbps	2048 x 1152 @ 60 Hz	-	-	-	Pigtail
U444-06N-DP4K6B	USB-C (M)	DisplayPort (F)	3.0	5 Gbps	4K @ 60Hz	2.2	1.3	-	Pigtail
U444-06N-DP4K6W	USB-C (M)	DisplayPort (F)	3.0	5 Gbps	4K @ 60Hz	2.2	1.3	-	Pigtail
U444-06N-DP8B	USB-C (M)	DisplayPort (F) 1.2	3.0	5 Gbps	8K @ 30Hz	1.4 2.2	1.2 1.4	Active	Pigtail
U444-06N-HD4K6B	USB-C (M)	HDMI (F)	3.0	5 Gbps	(4K x 2K) @ 60Hz	2.2	-	-	Pigtail
U444-06N-HD4K6W	USB-C (M)	HDMI (F)	3.0	5 Gbps	4K @ 60Hz	2.2	-	-	Pigtail
U444-06N-HD8KW	USB-C (M)	HDMI (F)	3.0	5 Gbps	8K @ 30Hz	1.4 2.3	1.4	-	Pigtail
U444-06N-HDR4-B	USB-C (M)	HDMI (F)	3.0	5 Gbps	4K @ 60Hz	2.2	-	Active	Pigtail
U444-06N-HDR-B	USB-C (M)	HDMI (F)	3.0	5 Gbps	4K @ 60Hz	2.2	-	Active	Pigtail
U444-06N-MDP8W	USB-C (M)	DisplayPort (F)	3.0	5 Gbps	8K @ 30Hz	1.4 2.2	1.2 1.4	Active	Pigtail
U444-003-D	USB-C (M)	DVI-D Single Link (M)	3.0	5 Gbps	1920 x 1200 (1080p)	-	-	-	91 cm
U444-003-DP	USB-C (M)	DisplayPort (M)	3.0	5 Gbps	4K @ 60Hz	1.3	1.2	Active	91 cm
U444-003-DP-BE	USB-C (M)	DisplayPort (M)	3.0	5 Gbps	4K @ 60Hz	2.2	1.2	Passive	91 cm
U444-003-DP-BD	USB-C (M)	DisplayPort (M) 1.2	3.0	5 Gbps	4K @ 60Hz	2.2	1.2	Active	91 cm
U444-003-H	USB-C (M)	HDMI (M)	3.0	5 Gbps	4K @ 30Hz	1.4	-	Active	91 cm
U444-003-H4K6BE	USB-C (M)	HDMI (M)	3.0	5 Gbps	(4K x 2K) @ 60Hz	2.2	-	Passive	91 cm
U444-003-HBE	USB-C (M)	HDMI (M)	3.0	5 Gbps	(4K x 2K) @ 60Hz	1.4	-	Passive	91 cm
U444-006-V	USB-C (M)	HD15 (M)	3.0	5 Gbps	1920 x 1200 (1080p)	-	-	Passive	1,83 m
U444-006-D	USB-C (M)	DVI-D Dual-Link (M) (Wired to DVI-D Single Link)	3.0	5 Gbps	1920 x 1200 (1080p)	-	1.3	Active	1,83 m

U444-006-DP	USB-C (M)	DisplayPort (M)	3.0	5 Gbps	4K @ 60Hz	1.3	1.2	Active	1,83 m
U444-006-DP-BD	USB-C (M)	DisplayPort (M)	3.0	5 Gbps	4K @ 60Hz	2.2	1.2	Active	1,83 m
U444-006-DP-BE	USB-C (M)	DisplayPort (M)	3.0	5 Gbps	4K @ 60Hz	2.2	1.2	Passive	1,83 m
U444-006-H	USB-C (M)	HDMI (M)	3.0	5 Gbps	4K @ 30Hz	1.4	-	Active	1,83 m
U444-006-H4K6BM	USB-C (M)	HDMI (M)	3.0	5 Gbps	4K @ 60Hz	2.2	-	Active	1,83 m
U444-006-H4K6WE	USB-C (M)	HDMI (M)	3.0	5 Gbps	(4K x 2K) @ 60Hz	1.4 2.2	-	Passive	1,83 m
U444-006-HBE	USB-C (M)	HDMI (M)	3.0	5 Gbps	(4K x 2K) @ 30Hz	1.4	-	Passive	1,83 m
U444-006-HWE	USB-C (M)	HDMI (M)	3.0	5 Gbps	(4K x 2K) @ 30Hz	1.4	-	Passive	1,83 m
U444-006-MDP	USB-C (M)	Mini DisplayPort (M)	3.0	5 Gbps	4K @ 60Hz	1.3	1.2	Active	1,83 m
U444-009-H4K6BE	USB-C (M)	HDMI (M)	3.0	5 Gbps	(4K x 2K) @ 60Hz	1.4 2.2	-	Passive	2,7 m
U444-010-H4K6BM	USB-C (M)	HDMI (M)	3.0	5 Gbps	4K @ 60Hz	2.2	-	Active	3,1 m
U444-015-H4K6BM	USB-C (M)	HDMI (M)	3.0	5 Gbps	4K @ 60Hz	2.2	-	Active	4,6 m
U444-016-H	USB-C (M)	HDMI (M)	3.0	5 Gbps	4K @ 30Hz	1.4	-	Active	4,9 m

With alternate mode - DP 1.2

U444-06N-DVI-AM	USB-C (M)	DVI-D Dual Link (F) (Wired to DVI-D Single-Link)	3.0	5 Gbps	1920 x 1080 (1080p) @ 60 Hz	1.2	-	-	Pigtail
U444-06N-DVIBAM	USB-C (M)	DVI-D Dual Link (F) (Wired to DVI-D Single-Link)	3.0	5 Gbps	1920 x 1080 (1080p) @ 60 Hz	1.2	-	-	Pigtail
U444-06N-HD-AM	USB-C (M)	HDMI (F)	3.0	5 Gbps	4K @ 24/25/30Hz	1.4	-	-	Pigtail
U444-06N-HDB-AM	USB-C (M)	HDMI (F)	3.0	5 Gbps	4K @ 24/25/30Hz	1.4	1.2	-	Pigtail
U444-06N-MDP-AL	USB-C (M)	Mini DisplayPort (F)	3.0	5 Gbps	4K @ 60Hz	2.2	1.2	-	Pigtail
U444-06N-VB-AM	USB-C (M)	HD15 (F)	3.0	5 Gbps	1920 x 1200 (1080p) @ 60Hz	-	1.2	-	Pigtail
U444-06N-VGA-AM	USB-C (M)	HD15 (F)	3.0	5 Gbps	1920 x 1200 (1080p) @ 60Hz	-	1.2	-	Pigtail

USB Panel Mount

Combine USB ports with universal keystone jacks or panels.



Key points:

- Extra versatility for installing in tight spaces
- Professional, clutter-free look

Ideal for:

- Motherboard
- Podium
- Kiosk

Part number	Connections		Cable			
	Connector A	Connector B	USB generation	Data transfer rate	Type	Cable Length (m)
Cables						
U024-06N-PM	USB-A (M)	USB-A (F) - Panel Mount	2.0	Up to 480 Mbps	Passive	15,24 cm
U025-001-PM	USB-B (M)	USB-B (F) - Panel Mount	2.0	Up to 480 Mbps	Passive	31 cm
U324-001-APM	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	Passive	31 cm
U324-001-KPA-BK	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	Passive Angled connector	31 cm
U324-003-KJ	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	Passive	91 cm
Keystone/Panel Mount Coupler						
U060-000-KP-BK	USB-A (F)	USB-A (F)	2.0	Up to 480 Mbps	-	-
U325-000-KP-BK	USB-A (F)	USB-A (F)	3.0	Up to 5 Gbps	-	-
U325-001-KPA-BK	USB-A (F)	USB-A (F)	3.0	Up to 5 Gbps	Angled connector	31 cm
Panels						
U324-006	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	Passive	1,83 m
U324-006-BK	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	Passive	1,83 m
U324-006-DSK1	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	Passive	1,83 m
U324-006-DSK2	USB-A (M)	2x USB-A (F)	3.0	Up to 5 Gbps	Passive	1,83 m
U324-010	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	Passive	3,05 m
U324-016	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	Passive	4,88 m
U324-06N-BK	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	Passive	15,24 cm

USB Extenders

Connects your home/office PC or laptop to a webcam, printer, hard drive or other USB peripheral located up to 50 m away.



Key points:

- Daisy-chain 2 cables
- Backward compatible with previous USB generations

Ideal for:

- Lecture halls
- Conference rooms
- Webcam applications

Part number	Connections				Cable			Number of Ports	Power Source Type
	Connector A	Connector B	USB generation	Data transfer rate	Max distance	Type	Cable Length (m)		
Over Ethernet Cable									
B202-150	USB-A (M) RJ45 (F)	USB-A (M) RJ45 (F)	2.0	Up to 480 Mbps	45,72 m	Passive	-	1	USB
B203-101-PNPINT	USB-A (M) RJ45 (F)	USB-A (M) RJ45 (F)	2.0	Up to 480 Mbps	50 m	Passive	-	1	Int AC Adapter
B203-101-POC	USB-A (M) RJ45 (F) Micro USB-B (F)	RJ45 (F)	2.0	Up to 480 Mbps	50 m	Passive	-	1	USB
B203-104-PNP	USB-A (M) RJ45 (F)	4x USB-A (F) RJ45 (F)	2.0	Up to 480 Mbps	50 m	Passive	-	4	USB
B203-104-POC	4x USB-A (F) RJ45 (F) Micro USB-B (F)	RJ45 (F)	2.0	Up to 480 Mbps	50 m	Passive	-	4	USB
Extension Repeater Cable									
U026-016	USB-A (M)	USB-A (F)	2.0	Up to 480 Mbps	-	Active	4,88 m	-	USB
U026-025	USB-A (M)	USB-A (F)	2.0	Up to 480 Mbps	-	Active	7,62 m	-	USB
U026-10M	USB-A (M)	USB-A (F)	2.0	Up to 480 Mbps	-	Active	10 m	-	USB
U026-15M	USB-A (M)	USB-A (F)	2.0	Up to 480 Mbps	-	Active	15 m	-	USB
U026-20M	USB-A (M)	USB-A (F)	2.0	Up to 480 Mbps	-	Active	20 m	-	USB
U042-025	USB-A (M)	USB-B (M)	2.0	Up to 480 Mbps	-	Active	7,62 m	-	USB
U042-030	USB-A (M)	USB-B (M)	2.0	Up to 480 Mbps	-	Active	9,14 m	-	USB
U042-036	USB-A (M)	USB-B (M)	2.0	Up to 480 Mbps	-	Active	10,97 m	-	USB
U042-050	USB-A (M)	USB-B (M)	2.0	Up to 480 Mbps	-	Active	15,24 m	-	USB
U330-05M	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	-	Active	5 m	-	USB
U330-10M	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	-	Active	10 m	-	USB
U330-10M-1	USB-A (M) USB-A (F)	USB-A (M)	3.0	Up to 5 Gbps	-	Active	10 m	-	USB
U330-10M-AL	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	-	Active	10 m	-	USB
U330-15M	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	-	Active	15 m	-	USB
U330-20M	USB-A (M)	USB-A (F)	3.0	Up to 5 Gbps	-	Active	20 m	-	USB

A professional control room or broadcast studio. The room features a desk with a control console, multiple large monitors displaying various video feeds, and several speakers mounted on the wall. The lighting is dim, with the primary light source being the screens and the control console.

Pro AV & Digital Signage

Video Splitters & Multiviewers

Video Extenders

Display Mounts

Audio Video Cables

Audio Video Adapter Cables

Video Adapters

Video Couplers

Audio Video Panel Mount

VGA Splitters

XGA/UXGA Monitor "Y" Splitter cable provides an inexpensive alternative for splitting the video signal from your PC's VGA port to two high-resolution monitors that use standard 15-pin plugs.



Key points:

- Splits the VGA/XVGA signal providing simultaneous display of the same image on two monitors
- Two monitors display the image from one PC
- Inexpensive solution for presentations
- Molded, double-shielded construction for maximum EMI/RFI protection

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Input x Output	Resolution	Cable		Length
	Connector A	Connector B			Type		
P516-001	HD15 (M)	2x HD15 (F)	1 x 2	Up to 800x600px	Passive		31 cm
P516-001-HR	HD15 (M)	2x HD15 (F)	1 x 2	Up to 1600 x 1200px	Passive		31 cm
P516-006-HR	HD15 (M)	2x HD15 (F)	1 x 2	Up to 1600 x 1200px	Passive		1,83 m

DVI Splitters

DVI splitter transmits 1080p video with audio from a DVI-D source to two DVI-D display devices past the 4.88 m distance limitation.



Key points:

- Superior molded connectors for long life use
- Supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p (60Hz)
- Easy plug-and-play operation for immediate connection right from the box

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Input x Output	Resolution	Number of ports	Cable		Daisy-chainable Cascadable
	Connector A	Connector B				Type	Length	
B116-002A-INT	DVI-D (F) 3.5MM (M)	2x DVI-D (F) 2x 3.5MM (M)	1 x 2	1920 x 1200px	2	-	-	Up to 3 levels
P564-001	DVI-D Dual Link (M)	2x DVI-D Dual Link (M) (Wired to DVI-D Single Link)	1 x 2	Up to 1920 x 1080px	-	Passive	31 cm	-
P564-06N-DV	DVI-I Dual Link (M)	DVI-I Dual Link (F)	1 x 2	Full HD @ 60Hz	-	Passive	15,24 cm	-
P576-001	DM559 (M)	2x DVI-I Dual Link (F)	1 x 2	Up to 2048 X 1536px	-	Passive	31 cm	-

DisplayPort Splitters

Displays the same image on 2 monitors, extends the desktop across both, or combines both into one large monitor.



Key points:

- Supports video resolutions up to 1080p @ 60 Hz (1920 x 1080)
- Compact enough for easy carrying in backpack or laptop bag
- Plug and play—no software or drivers required

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Input x Output	Resolution	Length	Number of ports
	Connector A	Connector B				
B157-002-HD	DisplayPort (M) 1.2 / Micro USB-B (F)	2x HDMI (F)	1 x 2	Full HD @ 60Hz	-	2
B157-002-VGA	DisplayPort (M) 1.2 / Micro USB-B (F)	2x HD15 (F)	1 x 2	Full HD @ 60Hz	-	2

HDMI Splitters

Transmit 4K video and audio from one HDMI source to up to 8 HDMI displays at the same time.



Key points:

- Support up to 4K @60Hz video resolutions
- Carries High Dynamic Range (HDR) signals for rich contrast and expanded color accuracy
- Power over Cable (PoC) technology provides power to receivers via Cat6 cable

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Input x Output	Video		Number of ports	Daisy-chainable cascadable	Int AC Adapter
	Connector A	Connector B		Max Resolution	HDCP			
B118-002-HDR-V2	HDMI (M)	2x HDMI (F) Micro USB-B (F)	1 x 2	4K @ 60Hz	2.2	2		-
B118-002-UHD-2	HDMI (F)	2x HDMI (F)	1 x 2	4K @ 60Hz	2.2	2		Yes
B118-002-UHDINT	HDMI (M)	2x HDMI (F)	1 x 2	4K @ 30Hz	1.4	2	Yes	Yes
B118-004-HDR	HDMI (F)	4x HDMI (F)	1 x 4	4K @ 60Hz	2.2	4		Yes
B118-004-UHD-2	HDMI (F)	4x HDMI (F)	1 x 4	4K @ 60Hz	2.2	4		Yes

Over Cat6 Cable (Max Signal Range: 70 m)

B127A-002-BH	HDMI (F) 2x RJ45 (F)	HDMI (F)	1 x 2	4K x 2K @ 60Hz	1.4 / 2.2	2 displays	-	Yes
B127A-002-BHPH2	HDMI (F) / 2x RJ45 (F)	2x HDMI (M) / 2x RJ45 (F)	1 x 2	4K @ 60Hz	1.4 / 2.2	2 displays	-	Yes
B127A-004-BH	HDMI (F)	HDMI (F) / 4x RJ45 (F)	1 x 4	4K @ 60Hz	1.4 / 2.2	4	-	Yes
B127A-008-BH	HDMI (F)	HDMI (F) / 8x RJ45 (F)	1 x 8	4K x 2K @ 60Hz	2.2	10	-	Yes
B127M-004-H	HDMI (F)	HDMI (F) / 4x RJ45 (F)	1 x 4	4K @ 60Hz		4 displays	-	Yes

VGA Switches

Optimal solution for connecting two computers to one monitor or two monitors to one computer.



Key points:

- 2-port HD15 VGA/SVGA Push-Button Switch
- Connects two computers to one monitor or two monitors to one computer
- Fully-shielded rugged metal case with front-panel push button switch

Ideal for:

- Restaurant
- Lecture Halls
- Conference room

Part number	Connections			Max Resolution	Number of Ports	Power Source Type
	Connector A	Connector B	Input x Output			
B112-002-R	2x HD12 (F)	HD15 (F)	2 x 1	1920 x 1080 @ 60Hz	2	Silver

DisplayPort Switches

Connects 4 different audio/video source devices (HDMI/DP/USB-C/VGA) to one HDMI display, eliminating the need for multiple adapters.



Key points:

- 4-in-1 Multi-Format Presentation Adapter Allows Convenient Connection to an HDMI Display
- HDMI, DisplayPort and USB-C cables support true 4K resolutions @ 60 Hz (4:4:4)
- USB-C PD 3.0 port supports 20V 5A (100W) power output for charging host device
- Plug-and-play

Ideal for:

- Restaurant
- Lecture Halls
- Conference room

Part number	Connections			Video				Number of Ports	Power Source Type
	Connector A	Connector B	Input x Output	Number of Monitors	Max Resolution	HDCP	DP		
B321-4X1-HDVC	HDMI (M) USB-A (M) USB-C (M)DB15 (M)	DisplayPort (M) HDMI (M) USB-C (M)	4 x 1	1	HDMI/DP/USB Type-C: 4096 x 2160 @ 60Hz VGA: 1920 x 1080 @ 60Hz 3D Video Supported	2.2	1.2a	1	USB

HDMI Switches

Shares 4K video/audio from up to 5 video/audio sources.



Key points:

- Transmits Crystal-Clear 4K Video with Multi-Channel Audio, HDR and 4:4:4 Color
- Extends a 4K A/V Transmission up to 70 m...or more
- Plug-and-Play Operation for Quick Setup and Immediate Use

Ideal for:

- Restaurant
- Lecture Halls
- Conference room

Part number	Connections		Video				HDCP	DP	Number of Ports	Power Source Type	Form Factor
	Connector A	Connector B	Input x Output	Number of Monitors	Max Resolution						
B118-2X4-4K-A	4x HDMI (F) Micro-USB-B (F)	2x HDMI (M) Stereo RCA (2x RCA) (RW)	2 x 4	2	4K @ 60Hz 3D Video Supported	2.2	-	4	Int AC Adapter	-	
B119-003-UHD-MN	3x HDMI (F)	HDMI (F)	3 x 1	1	4K @ 30 Hz 3D Video Supported	1.4	-	3	USB	-	
B119-005-UHD	5x HDMI (F)	HDMI (F)	5 x 1	1	4K @ 60 Hz 3D Video Supported	2.2	-	5	Int AC Adapter	-	
B302-4HX4H-4K	3.5MM (F) DB89 (F) 4x HDMI (F) RJ45 (F)	4x 3.5MM (F) 4x HDMI (F)	4 x 4	4	4K @ 60Hz 3D Video Supported	2.2	-	4	Int AC Adapter	-	

Over Cat6 Cable

B127A-4X4-BH4PH	4x HDMI (F) RJ45 (F) 3.5MM (F)	HDMI (F) RJ45 (F) Toslink (F)	4 x 1	4	4K @ 60 Hz 3D Video Supported	2.2	-	4	Int AC Adapter	Wall Plate/ Box
B320-4X1-MHB-K	2x 3.5MM (F) DB89 (F) DisplayPort (F) HD15 (F) HDMI (F) RJ45 (F) 2x USB-C (F)	HDMI (M) RJ45 (M)	4 x 1	1	HDMI/DP/USB Type-C: 4096 x 2160 @60Hz VGA: 1920 x 1080 @60Hz	2.2	1.2a	4	Int AC Adapter	-
B320-4X1-MHE-K	2x 3.5MM (F) DB89 (F) DisplayPort (F) HD15 (F) HDMI (F) RJ45 (F) 2x USB-C (F)	HDMI (M) RJ45 (M)	4 x 1	1	HDMI/DP/USB Type-C: 4096 x 2160 @60Hz VGA: 1920 x 1080 @60Hz	2.2	1.2a	4	Int AC Adapter	-

Wireless Video Extenders

Allows you to control your IR-enabled device from 200 m away without it being in direct line of sight.



Key points:

- IR pass through allows use of the source's remote while near the display with no latency
- Accepts IR signal frequencies from 20–60 kHz: compatible with all your IR devices
- Durable aluminum housings dissipate heat to keep units functioning at their peak

Ideal for:

- Restaurant
- Lecture Halls
- Conference room

Part number	Connections		Power Source Type
	Connector A	Connector B	
B164-101-WIR	3,5MM (F)	3,5MM (F)	USB

VGA Extenders

Allows VGA display devices to be connected up to 152 m away from the source computer, well beyond the standard VGA cable range.



Key points:

- Extends a 1920 x 1440 (60 Hz) signal up to 106 m, or a 1024 x 768 (60 Hz) signal up to 152 m
- USB-powered...no external AC power needed
- Built-in VGA dongles...no need for additional VGA cables
- Uses readily available Cat5e or Cat6 solid conductor cable

Ideal for:

- Restaurant
- Lecture Halls
- Conference room

Part number	Connections		Video			Power Source Type
	Connector A	Connector B	Max Resolution	Number of Displays	Number of Ports	
B130-101-U	HD15 (M) RJ45 (F) USB-A (M)	HD15 (M) RJ45 (F)	1920 x 1440 @ 60Hz	1	1	USB

DisplayPort Extenders

Extend 4k DisplayPort signals up to 70m away.



Key points:

- Uses readily available Cat5e or Cat6 solid conductor cable
- Supports UHD resolutions up to 4K @ 30 Hz (4:4:4) for crystal-clear video
- Power over Cable (PoC) technology provides power to either unit via Cat6 cable
- Plug-and-play operation with no software required for easy, immediate installation

Ideal for:

- Restaurants
- Schools
- Offices
- Digital Signage

Part number	Connections		Video				Number of Ports	Daisy-chainable Cascadable	Power Source Type
	Connector A	Connector B	Number of Monitors	Max Resolution	HDCP	DP			
Signal booster									
B127A-010-H	RJ45 (F)	RJ45 (F)	-	4K x 2K @ 60Hz	1.4 2.2	1.2	1	-	USB
Extender Kit									
B127A-111-BDTD	DisplayPort (F) RJ45 (F)	2x RJ45 (F) DisplayPort (F) Toslink (F)	1	4K @ 30 Hz	1.4 2.2	1.2a	-	4	Int AC Adapter
B127A-111-BDTH	DisplayPort (F) HDMI (F) RJ45 (F)	HDMI (F) 2x RJ45 (F) Toslink	2	4K @ 60 Hz	2.2	1.2a	-	4	Int AC Adapter
Over Cat6 Cable									
B127A-1A1-BDBD	DisplayPort (F) HDMI (F) RJ45 (F) 2x 3.5MM (F) Micro USB-B (F)	DisplayPort (F) RJ45 (F) 2x USB-A (F) Toslink (F) 3.5MM (F) Toslink (F)	2	4K @ 30 Hz	2.2	1.2a	-	-	Int AC Adapter
B127A-1A1-BDBH	DisplayPort (F) HDMI (F) RJ45 (F) 2x 3.5MM (F) Micro USB-B (F)	HDMI (F) RJ45 (F) 2x USB-A (F) Toslink (F) 2x 3.5MM (F)	1	4K @ 60 Hz	1.4 2.2	1.2a	-	-	Int AC Adapter
B127A-1A1-BDFH	DisplayPort (F) HDMI (F) RJ45 (F)	HDMI (F) RJ45 (F)	1	4K @ 60 Hz	1.4 2.2	1.2a	-	-	Int AC Adapter
B127F-1A1-SM-DD	Micro USB-B (F) DisplayPort (F) HDMI (F) LC (F)	2x USB-A (F) DisplayPort (F) LC (F)	2	4K @ 30 Hz	1.4 2.2	1.2a	-	-	Int AC Adapter
B150-1A1-HDMI	DisplayPort (M) RJ45 (F) Micro USB-B (F)	HDMI (F) RJ45 (F) Micro USB-B (F)	1	1920 x 1080 @ 60Hz	1.3	1.2	1	-	USB
Over cat6 cable & wallplate form factor									
B127A-1A1-BDFH	DisplayPort (F) HDMI (F) RJ45 (F)	HDMI (F) RJ45 (F)	1	4K @ 60 Hz	1.4 2.2	1.2a	-	-	Int AC Adapter

HDMI Video Extenders

Extend 4K Audio/video signals over Cat5e/6 cable up to 70m away.



Key points:

- Transmits Crystal-Clear 4K Video with Multi-Channel Audio, HDR and 4:4:4 Color
- Pig tail or box models for flexible installation
- Power over Cable (PoC) technology provides power to the receiver via Cat6 cable (in select models)

Ideal for:

- Restaurant
- Lecture Halls
- Conference room

Part number	Connections		Video				Number of Ports	Daisy-chainable Cascadable	Power Source Type
	Connector A	Connector B	Number of Monitors	Max Resolution	HDCP	Max Signal range			
Signal booster									
B122-000	HDMI (F) Micro USB-B (F)	HDMI (F)	1	1920 x 1200 (1080p) Video Supported	1.4	45 m	1	-	USB
B122-000-4K6	HDMI (F) Micro USB-B (F)	HDMI (F)	1	4K @ 60Hz 3D Video Supported	2.2	15 m	-	-	USB
B122-000-60	HDMI (F) Micro USB-B (F)	HDMI (F)	1	1920 x 1200 (1080p) Video Supported	1.4	38 m	-	-	USB
B123-001-60	HDMI (M) Micro USB-B (F)	HDMI (F)	1	1920 x 1200 (1080p) Video Supported	1.4	38 m	1	-	USB
Over Cat6 Cable									
B013-HU-4K	RJ45 (F) HDMI (F) 2x USB-A (F)	RJ45 (F) HDMI (F) 2x USB-A (F)	1	4k @ 30Hz	1.4	70 m	-	-	Int AC Adapters
B126-1A0-U	Micro USB-B (F) RJ45 (F)	HDMI (M)	1	1920 x 1200 (1080p) Video Supported	1.4	38 m	1	-	USB
B126-1A1-U	HDMI (M) Micro USB-B (F) RJ45 (F)	HDMI (M) Micro USB-B (F) RJ45 (F)	1	1920 x 1200 (1080p) Video Supported	1.4	38 m	-	-	USB
B126-1P0	RJ45 (F) Micro USB-B (F)	HDMI (M)	1	1920 x 1200 (1080p) Video Supported	1.4	30 m	1	-	USB
B126-1P1M-U-POC	HDMI (M) Micro USB-B (F) RJ45 (F)	Micro USB-B (F) RJ45 (F)	1	1920 x 1200 (1080p) Video Supported	1.4	30 m	2	Yes*	USB
B127A-004-BHPH3	2x HDMI (F) 4x RJ45 (F)	3x RJ45 (F) 3x HDMI (M)	4	4K @ 60Hz Video Supported	1.4.2.2	70 m	4	-	Int AC Adapters
B127A-110-BH	RJ45 (F) 3.5MM (F)	HDMI (F) RJ45 (F) 3.5MM (F) Toslink (F)	1	4K @ 60Hz Video Supported	1.4.2.2	70 m	-	-	Int AC Adapters
B127A-111-BH	2x HDMI (F) RJ45 (F) 2x 3.5MM (F)	2x RJ45 (F) HDMI (F) 2x 3.5MM (F) Toslink (F)	1	4K @ 60Hz Video Supported	1.4.2.2	70 m	-	-	Int AC Adapters
B127A-1A0-BH	RJ45 (F) HDMI (F)	Toslink (F)	1	4K @ 60Hz Video Supported	1.4.2.2	70 m	-	-	Transmitter end only
B127A-1A0-FH	RJ45 (F)	HDMI (F)	1	4K x 2K @ 60 Hz Video supported	1.4.2.2	70 m	-	-	Transmitter end only

Part number	Connections		Video				Number of Ports	Daisy-chainable Cascadable	Power Source Type	Form Factor
	Connector A	Connector B	Number of Monitors	Max Resolution	HDCP	Max Signal range				
B127A-1A1-BCBH	2x USB-C (F) HDMI (F) RJ45 (F) 2x 3.5MM (F) Micro USB-B (F) HDMI (F)	HDMI (F) RJ45 (F) 2x USB-A (F) Toslink (F) 2x 3.5MM 2x USB-A (F)	1	4K @ 60Hz Video Supported	1.4 2.2	70 m	-	-	USB	-
B127A-1A1-BHBH	2x HDMI (F) RJ45 (F) 2x 3.5MM (F) Micro USB-B (F)	HDMI (F) RJ45 (F) 2x USB-A (F) Toslink (F) 2x3.5MM (F) 2x USB-A (F)	1	4K @ 60Hz Video Supported	2.2	70 m	-	-	Int AC Adapters	-
B127A-1A1-BHFH	2x HDMI (F) RJ45 (F)	HDMI (F)	2	4K @ 60Hz Video Supported	1.4 2.2	70 m	-	-	Int AC Adapters	Wallplate
B127A-1A1-BHPH	2x HDMI (F) RJ45 (F) 2x 3.5MM (F)	HDMI (M) RJ45 (F)	1	4K @ 60Hz Video Supported	2.2	70 m	-	-	Int AC Adapters	-
B127A-1A1-FHFH	2x HDMI (F) RJ45 (F) 2x 3.5MM (F)	HDMI (F) RJ45 (F) 2x 3.5MM (F)	2	4K x 2K @ 60 Hz	2.2	70 m	-	-	Int AC Adapters	Wallplate
B127A-1P0-PH	RJ45 (F)	HDMI (F)	1	4K x 2K @ 60 Hz	1.4 2.2	70 m	-	-	Transmitter end only**	-
B127A-2A0-FH	RJ45 (F)	2x HDMI (F)	2	4K @ 60Hz Video Supported	1.4 2.2	70 m	-	-	Transmitter or Receiver (Optional)	Wallplate
B127A-2A1-BHBH	2x HDMI (F) RJ45 (F)	2x HDMI (F) RJ45 (F)	2	4K @ 60Hz Video Supported	1.4 2.2	70 m	-	-	Int AC Adapters	-
B127A-4X2-BH2PH	2x HDMI (F)	4x RJ45 (F)	2	4K @ 60Hz Video Supported	2.2	70 m	-	-	Int AC Adapters	Rackmountable
B127E-1A1-HH	2x HDMI (F) RJ45 (F)	HDMI (F) RJ45 (F) 2x USB-A (F)	1	4K @ 60Hz Video Supported	2.2	100 m	-	-	Int AC Adapters	-
B127F-1A1-MM-HH	Micro USB-B (F) 2x HDMI (F) LC (F)	2x USB-A (F) HDMI (F) LC (F)	1	4K @ 60Hz Video Supported	2.2	300 m	-	-	Int AC Adapters	-
B127M-101-H	2x HDMI(f) RJ45 (F)	HDMI (F) RJ45 (F)	1	4K @ 60Hz Video Supported	1.4 2.2	70 m	-	-	Int AC Adapters	-
Pass-Through Wallplate										
P166-001-P	HDMI (F)	HDMI (F)	1	2560 x 1440 @ 60 Hz	1.3	15 m	-	-	-	Wallplate
P167-000	HDMI (F)	HDMI (F)	1	920 x 1080 (1080p) Video Supported	1.3	70 m	-	-	-	Wallplate

*Optional

Wall Mounts

Low-profile mount hangs a flat-panel television, monitor or other display on the wall.



Key points:

- Security Wall Mount Hangs Your Flat-Panel or Curved-Screen TV or Monitor on the Wall
- Optimize viewing angles
- Horizontal adjustment compensates for off-center wall studs.
- Fixed / Swivel / Tilt / Rotate models
- Increase available desk/table space in office applications.

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Screen size		VESA Pattern (mm)		Max Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
	Min	Max	Min	Max					
Fixed									
DWF1327M	13"	27"	50x50	200x200	40 kg	Fixed	-	-	Black
DWF3770L	37"	70"	300x200	800x400	65 kg	Fixed	-	-	Black
DWF4585X	45"	85"	200x200	800x400	91 kg	Fixed	-	-	Black
DWF60100XX	60"	100"	200x200	900x600	159 kg	Fixed	-	-	Black
Tilt									
DWT1327S	13"	27"	75x75	100x100	40 kg	Tilt	-15/+10 Tilt	-	Black
DWT2655XP	26"	55"	200x200	400x400	75 kg	Tilt	-10/+10 Tilt	-	Black
DWT3770X	37"	70"	200x200	800x400	91 kg	Tilt	-10/+0 Tilt	-	Black
DWT4585X	45"	85"	200x200	800x400	91 kg	Tilt	-10/+10 Tilt	-	Black
DWT60100XX	60"	100"	100x100	1000x800	159 kg	Tilt	-15/+15 Tilt	-	Black
Full									
DWM1327SE	13"	27"	75x75	100x100	15 kg	Full	-15/+15 Tilt 180 Swivel	-	Black
DWM1327SP	13"	27"	75x75	100x100	15 kg	Full	-15/+15 Tilt 180 Swivel -2/+2 Level Adjustment	-	Black / Silver
DMC1342S	13"	42"	100x100	200x200	20 kg	Full	-15/+15 Tilt 180 Swivel -3/+3 Level Adjustment	Yes	Black / Silver
DWM1742MA	17"	42"	75x75	200x200	35 kg	Full	-15/+15 Tilt 180 Swivel -3/+3 Level Adjustment	-	Black
DWM1742MN	17"	42"	75x75	200x200	52 kg	Full	-15/+15 Tilt 80 Swivel -4/+4 Level Adjustment	-	Black
DWM1742S	17"	42"	100x100	200x200	20 kg	Full	-15/+15 Tilt 180 Swivel -3/+3 Level Adjustment	-	Black / Silver
DWM2355S	23"	55"	75x75	400x400	23 kg	Full	-15/+15 Tilt 180 Swivel	-	Black
DWM2655M	26"	55"	100x100	400x400	50 kg	Full	-15/+15 Tilt 120 Swivel -5/+5 Level Adjustment	-	Black
DWM3770X	37"	70"	100x100	600x400	75 kg	Full	-15/+15 Tilt 120 Swivel -3/+3 Level Adjustment	-	Black
DMWC3770M	37"	70"	100x100	600x400	45 kg	Full	90 Swivel -8/+5 Level Adjustment	-	Black
DWM60100XX	60"	100"	100x100	600x400	75 kg	Full	-15/+15 Tilt 120 Swivel -3/+3 Level Adjustment	-	Black

Part number	Screen size		VESA Pattern (mm)		Max Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
	Min	Max	Min	Max					
Pop-Out									
DMVWSC4570XUL	45"	70"	200x200	600x400	70 kg	Fixed	-	-	Black
Heavy-Duty									
DWFSC3255MUL	32"	55"	200x200	400x400	68 kg	Fixed	-	-	Black
DWFSC3780MUL	37"	80"	300x200	600x400	91 kg	Fixed	-	-	Black
DWT2670XE	26"	70"	50x50	400x400	75 kg	Tilt	-8/+0 Tilt	-	Black
DWT3280X	32"	80"	150x100	600x400	75 kg	Tilt	-8/+0 Tilt	-	Black
DWT3780XUL	37"	80"	200x200	800x400	75 kg	Tilt	-10/+0 Tilt	-	Black
DWTWSC4555M	45"	55"	200x100	400x600	50 kg	Tilt	-	-	Black
DWTSC3255MUL	32"	55"	200x200	400x400	68 kg	Tilt	-15/+10 Tilt	-	Black
DWTSC3780MUL	37"	80"	300x200	600x400	91 kg	Tilt	-10/+5 Tilt	-	Black
Outdoor									
DWM3270XOUT	32"	70"	200x200	400x400	50 kg	Full	-20/+10 Tilt 180° Swivel -3/+3 Level Adjustment	No	Black
DWM3780XOUT	37"	80"	200x200	600x400	50 kg	Full	-20/+10 Tilt 180° Swivel -3/+3 Level Adjustment		Black

What are you looking for?
Find the right solutions through our mount finder.



TV Stands and Carts

Height-adjustable mobile cart with upscale, professional look lets you smoothly roll your display from one room to another.



Key points:

- Durable aluminum/steel frame blends into any room décor
- Adjustable feet levelers provide a stable and safe foundation
- Cable management clips keep cords organized and prevent cable clutter
- Single display models

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Screen size		VESA Pattern (mm)		Max Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
	Min	Max	Min	Max					
Single display									
DMC1342S	13"	42"	75x75	200x200	20 kg	Tilt	0/+10 Tilt	Yes	Black
DMCS3770L	37"	70"	200x200	600x400	40 kg	Tilt	-10/+10 Tilt	Yes	Black
Rotating Portrait/Landscape									
DMCS3270XP	32"	70"	200x200	600x400	68 kg	Full	360° Rotate	Yes	Black / Silver
DMCS3770ROT	37"	70"	200x200	600x400	70 kg	Full	360° Rotate	Yes	Black
Wide Legs									
DMCS4265WL	42"	65"	100x100	600x400	60 kg	Fixed	-	Yes	Black
DMCS5585WL	55"	85"	100x100	1000x600	90 kg	Fixed	-	Yes	Black
DMCS60100XX	60"	100"	200x200	1000x600	100 kg	Tilt	-10/+5 Tilt	Yes	Black / Silver
DMCS60105XXDD	60"	105"	200x200	1000x600	150 kg	Fixed	-	Yes	Black
Premier Series									
DMCS3255SG62	32"	55"	75x75	400x400	59 kg	Fixed	-45/+45 Tilt	Yes	Black / Silver
DMCS3255SG62W	32"	55"	75x75	400x400	59 kg	Fixed	-45/+45 Tilt	Yes	White
DMCS3770SG75	37"	70"	100x100	600x400	79 kg	Fixed	-45/+45 Tilt	Yes	Black / Silver
DMCS3770SG75W	37"	70"	100x100	600x400	79 kg	Fixed	-45/+45 Tilt	Yes	White

Tablet & Smartphone Mounts

Suspends a digital projector from the ceiling, which saves valuable wall and floor space.



Key points:

- Mount tablets or smartphones for hands-free viewing
- Choose from desktop stands, wall mounts and floor stands

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Devices	Max Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
DMTBS911	Tablet	1 kg	Full	-90/+90 Tilt	No	Black / Silver
DMTBD413	Smartphone Tablet	1 kg	Full	-160/+210 Tilt -52/+52 Swivel 180° Rotate	Yes Flexible Long-Arm	White
DMTBS13(1)	Tablet	1 kg	-	-	-	White

⁽¹⁾ Secure freestanding tablet mount.

Ceiling Mounts

Suspends a digital projector from the ceiling, which saaves valuable wall and floor space.



Key points:

- Universal design fits most projector brands
- Quick-release feature allows easy projector maintenance

Ideal for:

- Office
- Classroom
- Conference room

Part number	Max Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
DUNVPJT	24,9 kg	Full	-20/+20 Tilt 360° Swivel	No	Black

Mobile Workstations

Mobile Workstation with Monitor Mount - For 17" to 32" Displays, Height Adjustable



Key points:

- All-in-one workstation you can roll from room to room.
- -15° to +15° tilt adjustment improves viewing angles
- Swivel casters allow easy rolling over thresholds

Ideal for:

- Office
- Hospital & Clinic
- Classroom

Part number	Screen size		VESA Pattern (mm)		Max Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
	Min	Max	Min	Max					
DMCS1732S	17"	32"	75x75	100x100	8 kg	Tilt	-30/+30 Tilt	Yes	Black

Rolling Desks

Mobile standing desk is an all-in-one workstation you can roll anywhere.



Key points:

- Allows transitions between sitting and standing to promote wellness
- Casters allow easy rolling from room to room
- Printer and CPU shelves support

Ideal for:

- Office
- Hospital & Clinic
- Classroom

Part number	Number of displays	Number of Shelves	Max Weight Capacity	Height adjustable	Color
WWSSRC	1	4	15 kg	No	Black / Silver
WWSSRDSTC	1	3	Monitor shelf: 8 kg Keyboard shelf: 2 kg	Yes	Black / Silver

Audio Cables

Connect a device with a 3.5 mm jack to a sound system with RCA inputs or a sound system with RCA inputs to a device with a 3.5 mm jack.



Key points:

- Perfect for your PC, notebook, MP3 player or iPod
- Molded cable with built-in strain relief

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Cable		Length	Angled	Color	
	Connector A	Connector B	Technology	Type			Cable Jacket	
A102-01M	Toslink (M)	Toslink (M)	Toslink/SPDIF Stereo Audio	Passive	1 m	-	Black	Black
A102-02M	Toslink (M)	Toslink (M)	Toslink/SPDIF Stereo Audio	Passive	2 m	-	Black	Black
A102-03M	Toslink (M)	Toslink (M)	Toslink/SPDIF Stereo Audio	Passive	3 m	-	Black	Black
A102-04M	Toslink (M)	Toslink (M)	Toslink/SPDIF Stereo Audio	Passive	4 m	-	Black	Black
P312-001	3.5MM (M)	3.5MM (M)	Stereo Audio	Passive	31 cm	-	Black	Black
P312-006	3.5MM (M)	3.5MM (M)	Stereo Audio	Passive	1,83 m	-	Black	Black
P312-006-RA	3.5MM (M)	3.5MM (M)	Stereo Audio	Passive	1,83 m	Right	Black	Black
P312-010	3.5MM (M)	3.5MM (M)	Stereo Audio	Passive	3,05 m	-	Black	Black
P312-012	3.5MM (M)	3.5MM (M)	Stereo Audio	Passive	3,66 m	-	Black	Black
P312-015	3.5MM (M)	3.5MM (M)	Stereo Audio	Passive	4,57 m	-	Black	Black
P312-025	3.5MM (M)	3.5MM (M)	Stereo Audio	Passive	7,62 m	-	Black	Black
P313-06N-WH	3.5MM (M)	2x 3.5MM (F)	Stereo Audio	Passive	15 m	-	White	White
P313-001	3.5MM (M)	2x 3.5MM (F)	Stereo Audio	Passive	31 cm	-	Black	Black
Extension Cable								
P311-006	3.5MM (M)	3.5MM (F)	Stereo Audio	Passive	1,83 m	-	Black	Black
P311-010	3.5MM (M)	3.5MM (F)	Stereo Audio	Passive	3,05 m	-	Black	Black
P311-025	3.5MM (M)	3.5MM (F)	Stereo Audio	Passive	7,62 m	-	Black	Black

VGA Cables

Allows Connection Between VGA-Enabled Computer and Monitor.



Key points:

- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold plated connectors and gold plated copper contacts ensure excellent conductivity

Ideal for:

- WFA / Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Cable		Length	Angled	Color
	Connector A	Connector B	Technology	Type			
P500-010	HD15 (M)	HD15 (F)	Coax, VGA/SVGA	Passive	3,05 m	-	Black
P500-025	HD15 (M)	HD15 (F)	Coax, VGA/SVGA	Passive	7,62 m	-	Black
P502-001	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	31 cm	-	Black
P502-003	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	91 cm	-	Black
P502-003-RA	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	91 cm	Right	Black
P502-003-SM	HD15 (M) - Low profile	HD15 (M) - Low profile	Coax, VGA/SVGA	Passive	91 cm	-	Black
P502-006	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	1,83 m	-	Black
P502-006-RA	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	1,83 m	Right	Black
P502-006-SM	HD15 (M) - Low profile	HD15 (M) - Low profile	Coax, VGA/SVGA	Passive	1,83 m	-	Black
P502-010	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	3,05 m	-	Black
P502-015	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	4,57 m	-	Black
P502-020	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	6,09 m	-	Black
P502-025	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	7,62 m	-	Black
P502-025-SM	HD15 (M) - Low profile	HD15 (M) - Low profile	Coax, VGA/SVGA	Passive	7,62 m	-	Black
P502-030	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	9,14 m	-	Black
P502-035	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	10,67 m	-	Black
P502-050	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	15,24 m	-	Black
P502-100	HD15 (M)	HD15 (M)	Coax, VGA/SVGA	Passive	30,5 m	-	Black
P504-006	HD15 (M) + 3.5MM(M)	HD15 (M) + 3.5MM(M)	Coax, VGA/SVGA Stereo Audio	Passive	1,83 m	-	Black
P504-010	HD15 (M) + 3.5MM(M)	HD15 (M) + 3.5MM(M)	Coax, VGA/SVGA Stereo Audio	Passive	3,05 m	-	Black
P504-015	HD15 (M) + 3.5MM(M)	HD15 (M) + 3.5MM(M)	Coax, VGA/SVGA Stereo Audio	Passive	4,57 m	-	Black
P504-025	HD15 (M) + 3.5MM(M)	HD15 (M) + 3.5MM(M)	Coax, VGA/SVGA Stereo Audio	Passive	7,62 m	-	Black
P512-006	HD15 (M)	HD15 (M)	VGA/SVGA	Passive	1,83 m	-	Black
P512-010	HD15 (M)	HD15 (M)	VGA/SVGA	Passive	3,05 m	-	Black
P512-015	HD15 (M)	HD15 (M)	VGA/SVGA	Passive	4,57 m	-	Black
Extension Cable							
P510-006	HD15 (M)	HD15 (F)	VGA/SVGA	Passive	1,83 m	-	Black

DVI Cables

Deliver the high performance and high bandwidth needed for today's digital video displays.



Key points:

- Superior molded cables with foil/braid shielding for maximum EMI/RFI protection
- Compatible with Flat Panel Displays, Digital CRT Displays and Projectors
- Provides bandwidth for resolutions up to 2560 x 1600

Ideal for:

- WFA / Office
- Hospital & Clinic
- Classroom
- Event / Tradeshow

Part number	Connections		Cable	Length	Color
	Connector A	Connector B	Type		
P560-003	DVI-D Dual Link (M)	DVI-D Dual Link (M)	Passive	91 cm	Black
P560-006	DVI-D Dual Link (M)	DVI-D Dual Link (M)	Passive	1,83 m	Black
P560-010	DVI-D Dual Link (M)	DVI-D Dual Link (M)	Passive	3,05 m	Black
P560-015	DVI-D Dual Link (M)	DVI-D Dual Link (M)	Passive	4,57 m	Black
P560-020	DVI-D Dual Link (M)	DVI-D Dual Link (M)	Passive	6,09 m	Black
P560-025	DVI-D Dual Link (M)	DVI-D Dual Link (M)	Passive	7,62 m	Black
P560-050	DVI-D Dual Link (M)	DVI-D Dual Link (M)	Passive	15,24 m	Black
P561-18N	DVI-D Single Link (M)	DVI-D Single Link (M)	Passive	45,72 cm	Black
P561-003	DVI-D Single Link (M)	DVI-D Single Link (M)	Passive	91 cm	Black
P561-006	DVI-D Single Link (M)	DVI-D Single Link (M)	Passive	1,83 m	Black
P561-006-SLI	DVI-I Single Link (M)	DVI-I Single Link (M)	Passive	1,83 m	Black
P561-010	DVI-D Single Link (M)	DVI-D Single Link (M)	Passive	3,05 m	Black
P561-015	DVI-D Single Link (M)	DVI-D Single Link (M)	Passive	4,57 m	Black
P561-050	DVI-D Single Link (M)	DVI-D Single Link (M)	Passive	15,24 m	Black

Extension Cable

P562-006	DVI-D Dual Link (M)	DVI-D Dual Link (M)	Passive	1,83 m	Black
P562-006-SL	DVI-D Single Link (M)	DVI-D Dual Link (F)	Passive	1,83 m	Black
P562-010	DVI-D Dual Link (M)	DVI-D Dual Link (M)	Passive	3,05 m	Black

DisplayPort Cables

High-speed cable connects A/V components up to an 8K display in your digital signage application, auditorium or security system.



Key points:

- Digital Video and Audio in one cable
- From 31 cm up to 15,24 m
- DisplayPort 1.2 4K @60Hz / DisplayPort 1.4 @ 30Hz & 60Hz
- Supports High Definition Content Protection (HDCP)

Ideal for:

- WFA / Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Cable	Max Supported Video Resolution	Length	Latching connector	Color
	Connector A	Connector B	Type				
P580-001	DisplayPort 1.2 (M)	DisplayPort 1.2 (M)	Passive - Bidirectional	4k @ 60Hz	31 cm	Yes	Black
P580-001-V4	DisplayPort 1.4 (M)	DisplayPort 1.4 (M)	Passive - Bidirectional	8K @30 Hz	31 cm	Yes	Black
P580-003	DisplayPort 1.2 (M)	DisplayPort 1.2 (M)	Passive - Bidirectional	4k @ 60Hz	91 cm	Yes	Black
P580-003-8K6	DisplayPort 1.4 (M)	DisplayPort 1.4 (M)	Passive - Bidirectional	8K @60 Hz	91 cm	Yes	Black/Blue
P580-003-V4	DisplayPort 1.4 (M)	DisplayPort 1.4 (M)	Passive - Bidirectional	8K @30 Hz	91 cm	Yes	Black
P580-006	DisplayPort 1.2 (M)	DisplayPort 1.2 (M)	Passive - Bidirectional	4k @ 60Hz	91 cm	Yes	Black
P580-006-8K6	DisplayPort 1.4 (M)	DisplayPort 1.4 (M)	Passive - Bidirectional	8K @60 Hz	1,83 m	Yes	Black/Blue
P580-006-V4	DisplayPort 1.4 (M)	DisplayPort 1.4 (M)	Passive - Bidirectional	8K @30 Hz	1,83 m	Yes	Black
P580-009-8K6	DisplayPort 1.4 (M)	DisplayPort 1.4 (M)	Passive - Bidirectional	8K @60 Hz	2,7 m	Yes	Black/Blue
P580-010	DisplayPort 1.2 (M)	DisplayPort 1.2 (M)	Passive - Bidirectional	4k @ 60Hz	3,1 m	Yes	Black
P580-010-V4	DisplayPort 1.4 (M)	DisplayPort 1.4 (M)	Passive - Bidirectional	8K @30 Hz	3,1 m	Yes	Black
P580-015	DisplayPort 1.2 (M)	DisplayPort 1.2 (M)	Passive - Bidirectional	4k @ 60Hz	4,57 m	Yes	Black
P580-015-V4	DisplayPort 1.4 (M)	DisplayPort 1.4 (M)	Passive - Bidirectional	8K @30 Hz	4,57 m	Yes	Black
P580-020	DisplayPort 1.2 (M)	DisplayPort 1.2 (M)	Passive - Bidirectional	4k @ 60Hz	6,09 m	Yes	Black
P580-025	DisplayPort 1.2 (M)	DisplayPort 1.2 (M)	Passive - Bidirectional	4k @ 60Hz	7,62 m	Yes	Black
P580-030	DisplayPort 1.2 (M)	DisplayPort 1.2 (M)	Passive - Bidirectional	4k @ 60Hz	9,14 m	Yes	Black
P580-050	DisplayPort 1.2 (M)	DisplayPort 1.2 (M)	Passive - Bidirectional	4k @ 60Hz	15,24 m	Yes	Black
P580F3-10M-8K6	DisplayPort (M)	DisplayPort (M)	Active Optical Cable (AOC)	8k @ 60Hz	10 m	Yes	Black
P580F3-15M-8K6	DisplayPort (M)	DisplayPort (M)	Active Optical Cable (AOC)	8k @ 60Hz	15 m	Yes	Black
P580F3-20M-8K6	DisplayPort (M)	DisplayPort (M)	Active Optical Cable (AOC)	8k @ 60Hz	20 m	Yes	Black
P580F3-25M-8K6	DisplayPort (M)	DisplayPort (M)	Active Optical Cable (AOC)	8k @ 60Hz	25 m	Yes	Black
P580F3-30M-8K6	DisplayPort (M)	DisplayPort (M)	Active Optical Cable (AOC)	8k @ 60Hz	30 m	Yes	Black
P580-003-8K6-2	DisplayPort 2.1 (M)	DisplayPort 2.1 (M)	Passive	8k @ 60Hz	91 cm	Yes	Black
P580-006-8K6-2	DisplayPort 2.1 (M)	DisplayPort 2.1 (M)	Passive	8k @ 60Hz	1,83 m	Yes	Black

Extension Cable

P579-006	DisplayPort (M)	DisplayPort (F)	Passive	4K @ 60Hz	1,83 m	Yes	Black
P579-010	DisplayPort (M)	DisplayPort (F)	Passive	4K @ 60Hz	3,05 m	Yes	Black
P579-010-4K6	DisplayPort (M)	DisplayPort (F)	Passive / Active Repeater	4K @ 60Hz	3,05 m	Yes	Black/Gray
P579-015	DisplayPort (M)	DisplayPort (F)	Passive	4K @ 60Hz	4,57 m	Yes	Black
P579-015-4K6	DisplayPort (M)	DisplayPort (F)	Passive / Active Repeater	4K @ 60Hz	4,57 m	Yes	Black/Gray
P579-020-4K6	DisplayPort (M)	DisplayPort (F)	Passive / Active Repeater	4K @ 60Hz	6,1 m	Yes	Black/Gray
P579-009-8K6	DisplayPort 1.4 (M)	DisplayPort 1.4 (M)	Passive / Active Repeater	8k @ 60Hz	2,7 m	Yes	Black/Blue

HDMI Cables

Transmits digital audio/video and Ethernet signals from an HDMI source to a 4K-enabled television, projector or monitor.



Key points:

- Supports UHD video resolutions up to 8K
- Premium foil and braid shielding protects against EMI/RFI noise

Ideal for:

- WFA / Office
- Classroom
- Conference room
- Trade show
- Theater

Part number	Connections		Cable		HDCP Spec	Max Supported Video Resolution	Length	Color
	Connector A	Connector B	Type					
P568-003	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @30 Hz	91 cm	Black
P568-003-8K6	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	8K @60 Hz	91 cm	Black
P568-006	HDMI (M)	HDMI (M)	Passive - Bidirectional		1.3	4K @30 Hz	1,83 m	Black
P568-006-8K6	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	8K @60 Hz	1,83 m	Black
P568-006-BK-GRP	HDMI (M)	HDMI (M)	Passive - Bidirectional	Gripping connectors 3D Video Supported	1.4 2.2	4K @30 Hz	1,83 m	Black
P568-006-RA	HDMI (M)	HDMI (M)	Passive - Bidirectional	Right-Angled	1.4 2.2	Full HD	1,83 m	Black
P568-006-RA2	HDMI (M)	HDMI (M)	Passive - Bidirectional	2 Right-Angled	1.4 2.2	Full HD	1,83 m	Black
P568-010	HDMI (M)	HDMI (M)	Passive - Bidirectional		1.3	4K @30 Hz	3,05 m	Black
P568-010-8K6	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	8K @60 Hz	3,05 m	Black
P568-010-BK-GRP	HDMI (M)	HDMI (M)	Passive - Bidirectional	Gripping connectors 3D Video Supported	1.4 2.2	4K @30 Hz	3,05 m	Black
P568-012	HDMI (M)	HDMI (M)	Passive - Bidirectional		1.4 2.2	4K @30 Hz	3,66 m	Black

Part number	Connections		Cable		HDCP Spec	Max Supported Video Resolution	Length	Color
	Connector A	Connector B	Type					
P568-01M-2A	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @60Hz	1 m	Black/Gray
P568-02M-2A	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @60Hz	2 m	Black/Gray
P568-03M-2A	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @60Hz	3 m	Black/Gray
P568-016	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @30 Hz	4,88 m	Black
P568-020	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @30 Hz	6,09 m	Black
P568-025	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @30 Hz	7,62 m	Black
P568-025-BK-GRP	HDMI (M)	HDMI (M)	Passive - Bidirectional	Gripping connectors 3D Video Supported	1.4 2.2	4K @30 Hz	7,62 m	Black
P568-030	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @30 Hz	9,14 m	Black
P568-035	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @30 Hz	10,67 m	Black
P568-040	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported Ethernet Supported	1.4 2.2	4K @30 Hz	12,19 m	Black
P568-050	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @30 Hz	15,24 m	Black
P568-100	HDMI (M)	HDMI (M)	Passive - Bidirectional	3D Video Supported	1.4 2.2	4K @30 Hz	15,24 m	Black

HDMI Fiber Active Optical Cable (AOC)

P568-05M-FBR	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	1.4 2.2	4K @60Hz	5 m	Black
P568-10M-FBR	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	1.4 2.2	4K @60Hz	10 m	Black
P568-15M-FBR	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	1.4 2.2	4K @60Hz	15 m	Black
P568-20M-FBR	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	1.4 2.2	4K @60Hz	20 m	Black
P568-30M-FBR	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	1.4 2.2	4K @60Hz	30 m	Black
P568-40M-FBR	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	1.4 2.2	4K @60Hz	40 m	Black
P568-50M-FBR	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	1.4 2.2	4K @60Hz	50 m	Black
P568-60M-FBR	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	1.4 2.2	4K @60Hz	60 m	Black
P568-100M-FBR	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	1.4 2.2	4K @60Hz	100 m	Black
P568F-10M-8K6	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	2.3	8K @60Hz	10 m	Black
P568F-15M-8K6	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	2.3	8K @60Hz	15 m	Black
P568F-20M-8K6	HDMI (M)	HDMI (M)	Active Optical Cable (AOC)	3D Video Supported	2.3	8K @60Hz	20 m	Black

Part number	Connections		Cable	Max Supported Video Resolution	Length	Color	
	Connector A	Connector B	Type				
P569-003	HDMI (M)	HDMI (M)	Passive - Bidirectional	4K @30 Hz	91 cm	Black	
P569-006	HDMI (M)	HDMI (M)	Passive - Bidirectional	4K @30 Hz	1,83 m	Black	
P569-006-CERT	HDMI (M)	HDMI (M)	Passive - Bidirectional	Gripping connector	4K @60 Hz	1,83 m	Black/ Burgundy
P569-006-LOCK	HDMI (M)	HDMI (M)	Passive - Bidirectional	Locking connector	4K @30 Hz	1,83 m	Black
P569-010	HDMI (M)	HDMI (M)	Passive - Bidirectional		4K @30 Hz	3,05 m	Black
P569-010-CERT	HDMI (M)	HDMI (M)	Passive - Bidirectional	Gripping connector	4K @60 Hz	3,05 m	Black/ Burgundy
P569-015-CERT	HDMI (M)	HDMI (M)	Passive - Bidirectional	Gripping connector	4K @60 Hz	3,05 m	Black/ Burgundy
P569-020	HDMI (M)	HDMI (M)	Passive - Bidirectional		4K @30 Hz	6,09 m	Black
P569-025	HDMI (M)	HDMI (M)	Passive - Bidirectional		4K @30 Hz	7,62 m	Black
P569-050	HDMI (M)	HDMI (M)	Passive - Bidirectional		4K @30 Hz	15,24 m	Black
P570-003-MICRO	Micro HDMI (M)	HDMI (M)	Passive - Bidirectional	Ethernet	Full HD	91 cm	Black
P570-006-MICRO	Micro HDMI (M)	HDMI (M)	Passive - Bidirectional	Ethernet	Full HD	1,83 m	Black
P571-006-MINI	Mini HDMI (M)	HDMI (M)	Passive - Bidirectional		4K @30 Hz	1,83 m	Black
P571-010-MINI	Mini HDMI (M)	HDMI (M)	Passive - Bidirectional		4K @30 Hz	3,05 m	Black
P572-006	Mini HDMI (M)	Mini HDMI (M)	Passive - Bidirectional		Full HD	1,83 m	Black

Extension Cables

P569-006-2B-MF	HDMI (M)	HDMI (F)	Passive - Bidirectional		4k @ 60Hz	91 cm	Beige/Black
P569-006-MF	HDMI (M)	HDMI (F)	Passive - Bidirectional		4k @ 30Hz	91 cm	Black
P569-010-2B-MF	HDMI (M)	HDMI (F)	Passive - Bidirectional		4k @ 60Hz	3,05 m	Beige/Black
P569-020-2B-MF	HDMI (M)	HDMI (F)	Passive - Bidirectional		4k @ 60Hz	6,09 m	Beige/Black

Accessories

Part number	Description
P568-000-LOCK	HDMI Cable Lock - Clamp/Tie/Screw



Audio Adapter Cables

Connect a device with a 3.5 mm jack to a sound system with RCA inputs or a sound system with RCA inputs to a device with a 3.5 mm jack.



Key points:

- Perfect for your PC, notebook, MP3 player or iPod
- Molded cable with built-in strain relief

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Cable		Length	Cable Jacket		Color	
	Connector A	Connector B	Technology	Type		Material	Rating	Cable Jacket	
P314-006	3.5MM (M)	2x RCA (M)	Stereo Audio	Passive	1,83 m	PVC	VW-1	Black	Black
P314-012	3.5MM (M)	2x RCA (M)	Stereo Audio	Passive	3,7 m	PVC	VW-1	Black	Black
P315-06N	3.5MM (M)	2x RCA (F)	Stereo Audio	Passive	15,2 cm	PVC	VW-1	Black	Black
P316-06N	3.5MM (F)	2x RCA (M)	Stereo Audio	Passive	15,2 cm	PVC	VW-1	Black	Black
P318-006-MF	3.5MM 4-POSITION (F)	3.5MM (M)	Stereo Audio	Passive	1,83 m	PVC	VW-1	Black	Black
P318-06N-FMM	3.5MM 4-POSITION (F)	2x 3.5MM (M)	Stereo Audio	Passive	15,2 cm	PVC	VW-1	Black	Black
P318-06N-MFF	3.5MM (F)	2x 3.5MM (F)	Stereo Audio	Passive		PVC	VW-1	Black	Black

HDMI Adapter Cables

Connects your device's USB-C ,Thunderbolt 3, Micro USB-B or VGA port to an HDMI monitor or TV.



Key points:

Ideal for:

- WFA
- Office
- Hospital & Clinic
- Classroom
- Event / Tradeshow

Part number	Connections			Cable Type	Max Supported Video Resolution	Length	Cable Jacket		Color
	Connector A	Connector B	Connector C				Material	Rating	
P566-003-VGA	HDMI (M)	HD15 (M) - Low profile Micro USB-B (F)	-	Active	Full HD	91 cm	PVC	VW-1	Black
P566-003-VGA-A	HDMI (M)	HD15 (M) - Low profile	Micro USB-B (F)	Active	Full HD	91 cm	PVC	VW-1	Black
P566-006-VGA	HDMI (M)	HD15 (M) - Low profile Micro USB-B (F)	-	Active	Full HD	1,83 cm	PVC	VW-1	Black
P566-006-VGA-A	HDMI (M)	HD15 (M) - Low profile	Micro USB-B (F)	Active	Full HD	1,83 cm	PVC	VW-1	Black
P566-010-VGA	HDMI (M)	HD15 (M) - Low profile Micro USB-B (F)	-	Active	Full HD	3,1m	PVC	VW-1	Black
P566-015-VGA	HDMI (M)	HD15 (M) - Low profile Micro USB-B (F)	-	Active	Full HD	4,6 m	PVC	VW-1	Black
P566-015-VGA-A	HDMI (M)	HD15 (M) - Low profile	Micro USB-B (F)	Active	Full HD	4,6 m	PVC	VW-1	Black
U444-006-H4K6BE	USB-C (M)	HDMI (M)	-	Passive	HDMI: 3840 x 2160 4096 x 2160 (4K x 2K) @ 60Hz	1,83 m	PVC	VW-1	Black
U444-006-HDR2BE	USB-C (M)	HDMI (F)	-	Active	4K @ 60Hz	1,83 m	TPE	-	Black
U444F3-10M-H4K6	USB-C (M)	HDMI (M)	-	Active	4K @ 60Hz	10 m	PVC	CL3	Black
U444F3-15M-H4K6	USB-C (M)	HDMI (M)	-	Active	4K @ 60Hz	15 m	PVC	CL3	Black
U444F3-20M-H4K6	USB-C (M)	HDMI (M)	-	Active	4K @ 60Hz	20 m	PVC	CL3	Black
U444F3-30M-H4K6	USB-C (M)	HDMI (M)	-	Active	4K @ 60Hz	30 m	PVC	CL3	Black
U444F3-50M-H4K6	USB-C (M)	HDMI (M)	-	Active	4K @ 60Hz	50 m	PVC	CL3	Black

DVI Adapter Cables

Creates a pure bi-directional digital connection between a DVI-enabled source and an HDMI-enabled display or an HDMI-enabled source and DVI-enabled display.



Key points:

- Premium double shielded digital video cable protects against EMI/RFI noise.
- Gold plated connectors and contacts provide optimal signal transfer.
- Supports high-def video resolutions up to 1920 x 1080 @60Hz (1080p).
- Supports a bandwidth up to 5Gbps

Ideal for:

- WFA
- Office
- Hospital & Clinic
- Classroom
- Event / Tradeshow

Part number	Connections		Cable Type	Length	Cable Jacket		Color Cable Jacket
	Connector A	Connector B			Material	Rating	
P120-000	DVI-A(M)	HD15 (F)	-	Adapter	-	-	-
P130-08N	DVI-D Single Link (M)	HDMI (F)	Passive	21 cm			
P556-003	DVI-A(M)	HD15 (M)	Passive	91 cm	PVC	VW-1	Black
P556-006	DVI-A(M)	HD15 (M)	Passive	1,83 m	PVC	VW-1	Black
P556-010	DVI-A(M)	HD15 (M)	Passive	3,1 m	PVC	VW-1	Black
P566-003-MINI	Mini HDMI (M)	DVI-D Single Link (M)	Passive	91 cm	PVC	VW-1	Black
P566-006-MINI	Mini HDMI (M)	DVI-D Single Link (M)	Passive	1,83 m	PVC	VW-1	Black
P566-003	HDMI (M)	DVI-D Single Link (M)	Passive	91 cm	PVC	VW-1	Black
P566-006	HDMI (M)	DVI-D Single Link (M)	Passive	1,83 m	PVC	VW-1	Black
P566-010	HDMI (M)	DVI-D Single Link (M)	Passive	3,1 m	PVC	VW-1	Black
P566-012	HDMI (M)	DVI-D Single Link (M)	Passive	3,7 m	PVC	VW-1	Black
P566-016	HDMI (M)	DVI-D Single Link (M)	Passive	4,9 m	PVC	VW-1	Black
P566-020	HDMI (M)	DVI-D Single Link (M)	Passive	6,1 m	PVC	VW-1	Black
P566-030	HDMI (M)	DVI-D Single Link (M)	Passive	9,1 m	PVC	VW-1	Black

DisplayPort Adapter Cables

Connects a DisplayPort monitor or projector to the HDMI or VGA port on the A/V source.



Key points:

- cd

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Cable		Length	Cable Jacket		Color
	Connector A	Connector B	Type	Max Supported Video Resolution		Material	Rating	
P567-01M	HDMI (M)	DisplayPort (M)/USB-A (M)	Active	4K @ 30Hz	1 m	PVC	VW-1	Black
P567-02M	HDMI (M)	DisplayPort (M)/USB-A (M)	Active	4K @ 30Hz	2 m	PVC	VW-1	Black
P581-003	DisplayPort (M)	DVI-D Single Link (M)	Passive	Full HD	91 cm	PVC	VW-1	Black
P581-003-V2	DisplayPort (M)	DVI-D Single Link (M)	Active	Full HD	91 cm	PVC	VW-1	Black
P581-003-VGA-V2	DisplayPort (M)	HD15 (M)	Active	Full HD	91 cm	PVC	VW-1	Black
P581-006	DisplayPort (M)	DVI-D Single Link (M)	Passive	Full HD	1,83 m	PVC	VW-1	Black
P581-006-V2	DisplayPort (M)	DVI-D Single Link (M)	Active	Full HD	1,83 m	PVC	VW-1	Black
P581-006-VGA-V2	DisplayPort (M)	HD15 (M)	Active	Full HD	1,83 m	PVC	VW-1	Black
P581-010	DisplayPort (M)	DVI-D Single Link (M)	Passive	Full HD	3,1 m	PVC	VW-1	Black
P581-010-VGA-V2	DisplayPort (M)	HD15 (M)	Active	Full HD	3,1 m	PVC	VW-1	Black
P582-003	DisplayPort (M) 1.2	HDMI (M)	Passive	Full HD	91 cm	PVC	VW-1	Black
P582-003-HD-V2A	DisplayPort (M) 1.2	HDMI (M)	Active	4K @ 60Hz	91 cm	PVC	VW-1	Black
P582-003-HD-V4A	DisplayPort (M) 1.4	HDMI (M)	Active	4K @ 60Hz	91 cm	PVC	VW-1	Black
P582-003-V2	DisplayPort (M) 1.2	HDMI (M)	Passive	4K @ 60Hz	91 cm	PVC	VW-1	Black
P582-003-V2-ACT	DisplayPort (M) 1.2	HDMI (M)	Active	4K @ 60Hz	91 cm	PVC	VW-1	Black
P582-006	DisplayPort (M) 1.2	HDMI (M)	Passive	Full HD	1,83 m	PVC	VW-1	Black
P582-006-HD-V2A	DisplayPort (M) 1.2	HDMI (M)	Active	4K @ 60Hz	1,83 m	PVC	VW-1	Black
P582-006-HD-V4A	DisplayPort (M) 1.4	HDMI (M)	Active	4K @ 60Hz	1,83 m	PVC	VW-1	Black
P582-006-V2	DisplayPort (M) 1.2	HDMI (M)	Passive	4K @ 60Hz	1,83 m	PVC	VW-1	Black
P582-006-V2-ACT	DisplayPort (M) 1.2	HDMI (M)	Active	4K @ 60Hz	1,83 m	PVC	VW-1	Black
P582-010	DisplayPort (M) 1.2	HDMI (M)	Passive	Full HD	3,05 m	PVC	VW-1	Black
P582-010-4K6AE	DisplayPort (M) 1.2	HDMI (M) Gripping	Active	4K @ 60Hz	3,05 m	PVC	VW-1	Black
P582-010-HD-V2A	DisplayPort (M) 1.2	HDMI (M)	Active	4K @ 60Hz	3,05 m	PVC	VW-1	Black
P582-010-HD-V4A	DisplayPort (M) 1.4	HDMI (M)	Active	4K @ 60Hz	3,05 m	PVC	VW-1	Black
P582-015	DisplayPort (M) 1.2	HDMI (M)	Passive	Full HD	4,6 m	PVC	VW-1	Black
P582-015-HD-V2A	DisplayPort (M) 1.2	HDMI (M)	Active	4K @ 60Hz	4,6 m	PVC	VW-1	Black
P582-015-HD-V4A	DisplayPort (M) 1.4	HDMI (M)	Active	4K @ 60Hz	4,6 m	PVC	VW-1	Black
P582-020	DisplayPort (M) 1.2	HDMI (M)	Passive	Full HD	6,1 m	PVC	VW-1	Black
P582-020-HD-V2A	DisplayPort (M) 1.2	HDMI (M)	Active	4K @ 60Hz	6,1 m	PVC	VW-1	Black
P582-020-HD-V4A	DisplayPort (M) 1.4	HDMI (M)	Active	4K @ 60Hz	6,1 m	PVC	VW-1	Black
P582-025	DisplayPort (M) 1.2	HDMI (M)	Passive	Full HD		PVC	VW-1	Black

Part number	Connections		Cable		Length	Cable Jacket		Color
	Connector A	Connector B	Type	Max Supported Video Resolution		Material	Rating	
P583-003-BK	DisplayPort (M)	Mini DisplayPort (M)	Passive Bidirectional	4K @ 60Hz	91 cm	PVC	VW-1	Black
P583-006	DisplayPort (M)	Mini DisplayPort (M)	Passive Bidirectional	4K @ 60Hz	1,8 m	PVC	VW-1	White
P583-006-BK	DisplayPort (M)	Mini DisplayPort (M)	Passive Bidirectional	4K @ 60Hz	1,8 m	PVC	VW-1	Black
P583-010	DisplayPort (M)	Mini DisplayPort (M)	Passive Bidirectional	4K @ 60Hz	3,05 m	PVC	VW-1	White
P583-010-BK	DisplayPort (M)	Mini DisplayPort (M)	Passive Bidirectional	4K @ 60Hz	3,05 m	PVC	VW-1	Black
P586-003-DVI-V2	Mini DisplayPort (M) 1.2	DVI-D Dual-Link (M) (wired to DVI-D Single Link)	Active	Full HD	91 cm	PVC	VW-1	Black
P586-003-HDMI	Mini DisplayPort (M)	HDMI (M)	Active	Full HD	91 cm	PVC	VW-1	Black
P586-003-HD-V4A	Mini DisplayPort (M) 1.4	HDMI (M)	Active	4K @ 60Hz	91 cm	PVC	VW-1	Black
P586-006-DVI	Mini DisplayPort (M) 1.2	DVI-D Single Link (M)	Passive	Full HD	1,8 m	PVC	VW-1	Black
P586-006-DVI-V2	Mini DisplayPort (M) 1.2	DVI-D Dual-Link (M) (wired to DVI-D Single Link)	Active	Full HD	1,8 m	PVC	VW-1	Black
P586-006-HDMI	Mini DisplayPort (M)	HDMI (M)	Active	Full HD	1,8 m	PVC	VW-1	Black
P586-006-HD-V2A	Mini DisplayPort (M)	HDMI (M)	Active	4K @ 60Hz	1,8 m	PVC	VW-1	Black
P586-006-HD-V4A	Mini DisplayPort (M) 1.4	HDMI (M)	Active	4K @ 60Hz	1,8 m	PVC	VW-1	Black
P586-006-VGA	Mini DisplayPort (M)	HD15 (M)	Active	Full HD	1,8 m	PVC	VW-1	Black
P586-010-VGA-V2	Mini DisplayPort (M) 1.2	HD15 (M)	Active	Full HD	3,05 m	PVC	VW-1	Black
P586-012-HDMI	Mini DisplayPort (M)	HDMI (M)	Active	Full HD	3,6 m	PVC	VW-1	Black
P586-015-HD-V2A	Mini DisplayPort (M)	HDMI (M)	Active	4K @ 60Hz	4,6m	PVC	VW-1	Black

DVI Adapters

Convert a DVI digital signal to VGA, Micro-HDMI or HDMI analog to provide compatibility between a monitor and a computer with DVI output.



Key points:

- Compact size for installation in tight spaces
- View presentations, Videos or pictures on a DVI monitor or projector
- Fully shielded and molded construction

Ideal for:

- Office
- Classroom
- Co-nference room
- Trade show
- Lobbies

Part number	Connections		Max Supported Video Resolution	Length	Color
	Connector A	Connector B			
P118-000	DVI-D Dual Link (M)	DVI-I Dual Link (F)		-	Beige
P120-06N-ACT	DVI-D Single Link (M) USB-A (M)	HD15 (F)	1920 x 1080 (1080p)	15,24 cm	Black
P120-08N	DVI-I Dual Link (M)	HD15 (F)	1920 x 1200 (1080p)	20,32 cm	Black
P132-08N	DVI-I Dual Link (F) (Wired to DVI-D Single Link)	HDMI (M)		20,32 cm	Black

DisplayPort Adapters

Connects a DisplayPort output to an HDMI, DVI or VGA monitor.



Key points:

- Keep using your existing HDMI, DVI or VGA monitor

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Max Supported Video Resolution	Length
	Connector A	Connector B		
P126-000	DVI-I (F)	HD15 (M)	-	-
P130-000	DVI-D Single Link (F)	HDMI (F)	Full HD	-
P132-000	DVI-D Dual Link (F)	HDMI (M)	-	-
P134-000	DisplayPort (M) 1.2	DVI-D Dual Link (F) (Wired to DVI-D Single Link)	Full HD - 1920 x 1200 (1080p)	15,24 cm
P134-000-VGA-V2	DisplayPort (M) 1.2	HD15 (F)	Full HD - 1920 x 1200 (1080p)	-
P134-001-GC	DisplayPort (M) 1.1	DVI-D Dual Link (F) (Wired to DVI-D Single Link)	Full HD - 1920 x 1200 (1080p)	31 cm
P134-003	DisplayPort (M)	DVI-I (F)	Full HD - 1920 x 1200 (1080p)	91 cm
P134-06N-DVI-V2	DisplayPort (M) 1.2	DVI-I Dual Link (F) (Wired to DVI-D Single Link)	HD - 1920 x 1080 (1080p)	15,24 cm
P134-06N-MDP	DisplayPort (M)	Mini DisplayPort (F)	4K x 2K @ 60 Hz	15,24 cm
P134-06N-VGA	DisplayPort (M) 1.2	HD15 (F)	Full HD - 1920 x 1200 (1080p)	15,24 cm
P134-06N-VGA-V2	DisplayPort (M) 1.2	HD15 (F)	HD - 1920 x 1080 (1080p)	15,24 cm
P136-000	DisplayPort (M)	HDMI (F)	HD - 1920 x 1080 (1080p)	15,24 cm
P136-000-1	DisplayPort (M)	HDMI (F)	Full HD - 1920 x 1200 (1080p)	-
P136-000-UHD-V2	DisplayPort (M) 1.2	HDMI (F) 1.4	4K x 2K @ 24/30 Hz	-
P136-001	DisplayPort (M)	HDMI (F)	Full HD - 1920 x 1200 (1080p)	31 cm
P136-06N-H2V2	DisplayPort (M) 1.2	HDMI (F)	4K @ 60 Hz	15,24 cm
P136-06N-H2V2LB	DisplayPort (M) 1.2	HDMI (F)	4K @ 60 Hz	15,24 cm
P136-06N-HDV-4K	DisplayPort (M)	DVI-I Dual Link (F) (Wired to DVI-D Single Link)	4K @ 30 Hz	15,24 cm
P136-06N-HDV4K6	DisplayPort (M)	DVI-D Single Link (F) HD15 (F) / HDMI (F)	4K @ 60 Hz	15,24 cm
P136-06N-HV-V2	DisplayPort (M) 1.2	HD15 (F) HDMI (F)	Full HD - 1920 x 1200 (1080p)	15,24 cm
P136-06N-UHD-V2	DisplayPort (M) 1.2	HDMI (F)	4K @ 30 Hz	15,24 cm

Part number	Connections		Max Supported Video Resolution	Length	Color
	Connector A	Connector B			
P137-06N-DVI	Mini DisplayPort (M)	DVI-I (F)	Full HD - 1920 x 1200 (1080p)	15,24 cm	White
P137-06N-DVI-V2	Mini DisplayPort (M)	DVI-I Dual Link (F) (Wired to DVI-D Single Link)	1920 x 1080 (1080p)	15,24 cm	White
P137-06N-HD4K6B				15,24 cm	
P137-06N-HDMI				15,24 cm	
P137-06N-HDR-W				15,24 cm	
P137-06N-HD-UHD				15,24 cm	
P137-06N-HDV-4K				15,24 cm	
P137-06N-HDVW				15,24 cm	
P137-06N-HV-V2W				15,24 cm	
P137-06N-VGA				15,24 cm	
P137-06N-VGA-V2				15,24 cm	
P137-06N-VGAV2B				15,24 cm	
P139-06N-DP				15,24 cm	
P139-06N-DP4K6B				15,24 cm	
50 Pack					
P136-06N-HVV2BP	DisplayPort (M) 1.2	HD15 (F) HDMI (F)	Full HD - 1920 x 1200 (1080p)	15,24 cm	

HDMI Adapters

Connect a PC, laptop or ultrabook with a HDMI port to a VGA display and speakers



Key points:

- Supports video resolutions up to 1920 x 1200 (WUXGA)
- Supports 3.5 mm. Mini Stereo Audio
- Supports 2-channel analog audio output
- Plug-and-Play

Ideal for:

- Office
- Classroom
- Conference room
- Trade show
- Lobbies

Part number	Connections		Video	HDCP	Cable		Int AC Adapter	Color
	Connector A	Connector B			Length	ANGLED		
P116-003-HD-U	HD15 (M) USB-A (M)	HDMI (F)	1920 x 1200 (1080p)		15,24 cm	-	Yes	Black
P130-000-AUDIO	HDMI (F)	HDMI (F) Toslink (F) 3.5MM (F) RCA (F)	4k x 2K @30 Hz	1.3	-	-	-	Black
P130-06N-AUDIO	HDMI (F)	HDMI (F) Toslink (M) 3.5MM (F) Micro USB-B (F)	4k x 2K @30 Hz	1.4	15,24 cm	-	-	Black
P131-000	HDMI (M)	HD15 (F)	1920 x 1200 (1080p)		-	-	-	Black/Blue
P131-000-A	HDMI (M)	3.5MM (F) HD15 (F) Micro USB-B (F)	1920 x 1200 (1080p)	1.4	-	-	-	Black
P131-000-A-DISP	HD15 (M)	3.5MM (F) HDMI (F) Micro USB-B (F)	1920 x 1200 (1080p)	1.4	-	-	-	Black
P131-06N	HDMI (M) HD15 (F)	3.5MM (F)	1920 x 1200 (1080p)		15,24 cm	-	-	Black
P131-06N-2VA-U	HDMI (M)	2x HD15 (F) 2x 3.5MM (F) HD15 (F)	1920 x 1200 (1080p)		15,24 cm	-	-	Black
P131-06N-MICROA	Micro-HDMI (M)	HD15 (F) 3.5MM (F)	1920 x 1200 (1080p)		15,24 cm	-	-	Black
P131-06N-MINI	Mini-HDMI (M)	HD15 (M)	1920 x 1200 (1080p)		15,24 cm	-	-	Black
P142-000-MICRO	Micro-HDMI (M)	HDMI (F)	1920 x 1200 (1080p)		-	-	-	Black
P142-000-MINI	Mini-HDMI (M)	HDMI (F)	1920 x 1200 (1080p)		-	-	-	Black
P142-000-UD	HDMI (F)	HDMI (M) - Swivel				Up / Down	-	Black
P142-000-UP	HDMI (F)	HDMI (M)				Up	-	Black
P142-06N-MICRO	HDMI (F)	Micro-HDMI (M)					-	Black

Video Couplers

Connects two video cables to create one longer cable.



Key points:

- Change Male ended DVI cable to Female
- Extend up to 2 HDMI, DisplayPort or DVI cables

Ideal for:

-
- Conference room

Part number	Product Type	Connections		Video			Color
		Connector A	Connector B	Max Supported Video Resolution	HDCP	DP	
P162-000	Coupler Gender Changer	DVI-I (F)	DVI-I (F)		-	-	Beige
P164-000	Coupler Gender Changer	HDMI (F)	HDMI (F)			-	Black
P164-000-8K6	Coupler Gender Changer	HDMI (F)	HDMI (F)	8k @ 60Hz	1.4 2.2	-	Black
P164-000-KP-BK	Keystone/Panel-Mount Coupler	HDMI (F)	HDMI (F)	4k @ 60Hz		-	Black
P164-000-KPBK8K	Keystone/Panel-Mount Coupler	HDMI (F)	HDMI (F)	8k @ 60Hz	1.4 2.2	-	Black
P168-000	Coupler Gender Changer	DisplayPort (F)	DisplayPort (F)		2.2	1.2	Black
P310-000	Coupler Gender Changer	3.5MM (F)	3.5MM (F)		-	-	Black

Patch Panels & Accessories

Manages and organizes network cables in a variety of applications, including audio/video, voice, Ethernet and USB.



Key points:

- 48 blank cutouts compatible with all keystone jacks, including RJ45 and HDMI
- Ideal for Ethernet, voice, audio/video and USB applications for home or office
- Numbered ports allow easy identification of jacks and cabling

Ideal for:

- Server room
- Data Center
- IP room

Part number	Number of Ports	Height (U)	Product Type	Technology				Cable	
				Cat5/5e	Cat6	Cat6a	Cat8	Connector A (Front)	Connector B (Rear)
N062-048-KJ	48	1U	Blank Patch Panels	Yes	Yes	Yes	-	-	-
P169-000-KPA-BK	-	-	Keystone Jacks	-	-	-	-	DisplayPort (F)	Mini DisplayPort (F)
P569-003-MF-APM	-	-	Cables	-	-	-	-	HDMI (F) - Panel mount	HDMI (M)

A background image showing a yellow industrial robot arm in the foreground on the left, and a person's hand holding a tablet displaying a control interface on the right. The scene is set in a factory or industrial environment with blurred lights and machinery in the background.

Industrial-grade IT solutions

Server Racks & Cabinets

Copper Network Cables

Fiber Network Cables

Industrial Switches

Transceivers

PoE Injectors

USB Solutions

AV Solutions

Power over Ethernet (PoE)

SmartRack Industrial Enclosures

Locking metal enclosure protects your outdoor equipment against theft, damage, tampering, and excess moisture and debris.



Key points:

- NEMA 4 enclosure provides protection against water, ice, snow and other moisture
- Includes metal and plastic backplates to accommodate a wide range of equipment
- Comes fully assembled and ready for wall or pole mounting using included hardware

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/ Logistics facilities
- Dusty, outdoor IT installations

Part number	Dimensions (cm)					Static load (Kg)	Doors			Mounting rails	Cable entry	Color
	Height		Width (cm)	Depth			Front	Rear	Side panels			
	U	(cm)		Rack Depth	(cm)							
Surface-Mount Enclosures												
SRIN4101010	-	25	25	Mid	25	91	Solid	Solid	Yes			Gray
SRIN410106	-	25	25	Shallow	15	91	Solid	Solid	Yes			Gray
SRIN410146	-	25	35	Shallow	15	91	Solid	Solid	Yes			Gray
SRIN4101410	-	25	35	Mid	25	91	Solid	Solid	Yes			Gray
SRIN412126	-	30	30	Shallow	15	91	Solid	Solid	Yes			Gray
SRIN4121210	-	30	30	Mid	25	91	Solid	Solid	Yes			Gray
SRIN414146	-	35	35	Shallow	15	91	Solid	Solid	Yes			Gray
SRIN4141410	-	35	35	Mid	25	91	Solid	Solid	Yes	Plastic and metal mounting panel, document holder	Bottom cutout with removable cover	Gray
SRIN418186	-	45	45	Shallow	15	91	Solid	Solid	Yes			Gray
SRIN4181810	-	45	45	Mid	25	91	Solid	Solid	Yes			Gray
SRIN410106R	-	25	25	Shallow	15	91	Solid	Solid	Yes			Red
SRIN4101410R	-	25	35	Mid	25	91	Solid	Solid	Yes			Red
SRIN4121210R	-	30	30	Mid	25	91	Solid	Solid	Yes			Red
SRIN4181810R	-	45	45	Mid	25	91	Solid	Solid	Yes			Red
SRIN410106Y	-	25	25		15	91	Solid	Solid	Yes			Yellow
SRIN4101410Y	-	25	35		25	91	Solid	Solid	Yes			Yellow
Wall-Mount Enclosures												
SRN4G6U	6	34	61	Shallow	47	91	Solid	Yes	Yes			Gray
SRN4G6UDP	6	34	61	Deep	59	91	Solid	Solid	Yes			Gray
SRN4G9US	9	48	61	Mid	76	91	Solid	Solid	Yes			Gray
SRN4G9USDP	9	48	61	Deep	86	91	Solid	Solid	Yes			Gray
SRN4G12U	12	61	61	Mid	64	91	Solid	Solid	Yes	Adjustable equipment mounting rail (10-32)		Gray
SRN4G12US	12	61	61	Shallow	76	91	Solid	Solid	Yes			Gray
SRN4G12USDP	12	61	61	Deep	86	91	Solid	Solid	Yes			Gray
SRX12UBFFD	12	64	60	Mid	98	453	Solid	Solid	Yes			Black
SRN4G12UHD	12	65	61	Mid	92	91	Vented	Vented	Yes			Gray
SRN4G18UHD	18	91	61	Mid	92	91	Solid	Solid	Yes			Gray

Cat5e Copper Cables

Connects Gigabit Ethernet equipment in industrial environments that require protection against dust and moisture.



Key points:

- IP68 Rating Denotes Resistance to Dust and Water
- Heavy Shielding Protects Your Network Data from Destructive Line Noise
- Supports Power over Ethernet (PoE) to Cut Down on Power Supplies

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Shielding		Length	Network compatibility	Cable Jacket Material	Cable Jacket Rating	Conductor material	Color
	Cable shielding	Conductor shielding						
Molded								
N206-PC03-IND	Yes	STP	1 m	1 Gbps	PBT	CMX	Stranded Copper	Black
N206-PC10-IND	Yes	STP	3,05 m	1 Gbps	PBT	CMX	Stranded Copper	Black
N206-PC16-IND	Yes	STP	4,88 m	1 Gbps	PBT	CMX	Stranded Copper	Black
N206-PC23-IND	Yes	STP	7,01 m	1 Gbps	PBT	CMX	Stranded Copper	Black
N206-PC33-IND	Yes	STP	10,05 m	1 Gbps	PBT	CMX	Stranded Copper	Black
N206-PC50-IND	Yes	STP	15,24 m	1 Gbps	PBT	CMX	Stranded Copper	Black

Cat6 Copper Cables

Connects Gigabit Ethernet and PoE equipment in industrial environments that require protection against dust and moisture.



Key points:

- IP68-rated to resist dust and endure immersion in 1.5 m of water up to 60 min.
- Supports power over ethernet to save your money and give you more installation choices

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Shielding		Length	Network compatibility	Cable Jacket Material	Cable Jacket Rating	Conductor material	Color
	Cable shielding	Conductor shielding						
Molded								
N200P-003BL-IND	No	UTP	91 cm	1 Gbps	PVC	CMR-LP/LP5	Solid Copper	Black
N200P-010BL-IND	No	UTP	3,05 m	1 Gbps	PVC	CMR-LP/LP5	Solid Copper	Black
N200P-016BL-IND	No	UTP	4,88 m	1 Gbps	PVC	CMR-LP/LP5	Solid Copper	Black
N200P-023BL-IND	No	UTP	7,01 m	1 Gbps	PVC	CMR-LP/LP5	Solid Copper	Black
N200P-033BL-IND	No	UTP	10,05 m	1 Gbps	PVC	CMR-LP/LP5	Solid Copper	Black
N200P-050BL-IND	No	UTP	15,24 m	1 Gbps	PVC	CMR-LP/LP5	Solid Copper	Black

M12 X-Code Cat6 Copper Cables

Connects Gigabit Ethernet network equipment in industrial and other harsh environments subject to vibration, humidity and extreme temperatures.



Key points:

- IP68-rated to resist dust and endure immersion in 1.5 m of water up to 60 min.
- Supports 60W PoE to save you expense and effort of powering PoE devices individually
- UL CMR-LP certified to meet high-temperature safety standards in PoE applications

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Connections		Shielding				Length	Network compatibility	Jacket Rating	Conductor material	Color
	Connector A	Connector B	Cable	Conductor							
NM12-601-01M-BL	M12 X-Code	M12 X-Code	No	UTP	-	-	1 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-601-02M-BL	M12 X-Code	M12 X-Code	No	UTP	-	-	2 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-601-03M-BL	M12 X-Code	M12 X-Code	No	UTP	-	-	3 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-601-05M-BL	M12 X-Code	M12 X-Code	No	UTP	-	-	5 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-601-10M-BL	M12 X-Code	M12 X-Code	No	UTP	-	-	10 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-602-01M-BL	M12 X-Code	RJ45	No	UTP	-	-	1 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-602-02M-BL	M12 X-Code	RJ45	No	UTP	-	-	2 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-602-03M-BL	M12 X-Code	RJ45	No	UTP	-	-	3 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-602-05M-BL	M12 X-Code	RJ45	No	UTP	-	-	5 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-602-10M-BL	M12 X-Code	RJ45	No	UTP	-	-	10 m	1 Gbps	CMR-LP	Solid Copper	Blue
Right Angled											
NM12-603-01M-BL	M12 X-Code	M12 X-Code	No	UTP	-	-	1 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-603-02M-BL	M12 X-Code	M12 X-Code	No	UTP	-	-	2 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-603-03M-BL	M12 X-Code	M12 X-Code	No	UTP	-	-	3 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-603-05M-BL	M12 X-Code	M12 X-Code	No	UTP	-	-	5 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-603-10M-BL	M12 X-Code	M12 X-Code	No	UTP	-	-	10 m	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-604-01M-BL	M12 X-Code	RJ45	No	UTP	-	-	1 Gbps	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-604-02M-BL	M12 X-Code	RJ45	No	UTP	-	-	1 Gbps	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-604-03M-BL	M12 X-Code	RJ45	No	UTP	-	-	1 Gbps	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-604-05M-BL	M12 X-Code	RJ45	No	UTP	-	-	1 Gbps	1 Gbps	CMR-LP	Solid Copper	Blue
NM12-604-10M-BL	M12 X-Code	RJ45	No	UTP	-	-	1 Gbps	1 Gbps	CMR-LP	Solid Copper	Blue

M12 X-Code Cat6a Copper Cables

Connects Gigabit Ethernet network equipment in industrial and other harsh environments subject to vibration, humidity and extreme temperatures.



Key points:

- Designed to withstand vibration, moisture and extreme temperatures in harsh environments
- IP68-rated to resist dust and endure immersion in 1.5 m of water up to 60 min.
- Supports 60W PoE to save you expense and effort of powering PoE devices individually
- UL CMR-LP certified to meet high-temperature safety standards in PoE applications
- Blue PVC jacket easy to identify quickly in field devices, controllers and switches

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Connections		Shielding				Length	Network compatibility	Jacket Rating	Conductor material	Color
	Connector A	Connector B	Cable	Conductor							
NM12-6A1-01M-BL	M12 X-Code	M12 X-Code	Yes	F/UTP	Foil	-	1 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A1-02M-BL	M12 X-Code	M12 X-Code	Yes	F/UTP	Foil	-	2 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A1-03M-BL	M12 X-Code	M12 X-Code	Yes	F/UTP	Foil	-	3 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A1-05M-BL	M12 X-Code	M12 X-Code	Yes	F/UTP	Foil	-	5 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A1-10M-BL	M12 X-Code	M12 X-Code	Yes	F/UTP	Foil	-	10 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A2-01M-BL	M12 X-Code	RJ45	Yes	F/UTP	Foil	-	1 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A2-02M-BL	M12 X-Code	RJ45	Yes	F/UTP	Foil	-	2 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A2-03M-BL	M12 X-Code	RJ45	Yes	F/UTP	Foil	-	3 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A2-05M-BL	M12 X-Code	RJ45	Yes	F/UTP	Foil	-	5 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A2-10M-BL	M12 X-Code	RJ45	Yes	F/UTP	Foil	-	10 m	10 Gbps	CMR-LP	Solid Copper	Blue
Right Angled											
NM12-6A3-01M-BL	M12 X-Code	M12 X-Code	Yes	F/UTP	Foil	-	1 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A3-02M-BL	M12 X-Code	M12 X-Code	Yes	F/UTP	Foil	-	2 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A3-03M-BL	M12 X-Code	M12 X-Code	Yes	F/UTP	Foil	-	3 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A3-05M-BL	M12 X-Code	M12 X-Code	Yes	F/UTP	Foil	-	5 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A3-10M-BL	M12 X-Code	M12 X-Code	Yes	F/UTP	Foil	-	10 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A4-01M-BL	M12 X-Code	RJ45	Yes	F/UTP	Foil	-	1 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A4-02M-BL	M12 X-Code	RJ45	Yes	F/UTP	Foil	-	2 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A4-03M-BL	M12 X-Code	RJ45	Yes	F/UTP	Foil	-	3 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A4-05M-BL	M12 X-Code	RJ45	Yes	F/UTP	Foil	-	5 m	10 Gbps	CMR-LP	Solid Copper	Blue
NM12-6A4-10M-BL	M12 X-Code	RJ45	Yes	F/UTP	Foil	-	10 m	10 Gbps	CMR-LP	Solid Copper	Blue

OM3 Multimode Fiber Patch Cables

Connects fiber optic Ethernet equipment in industrial environments that require protection against dust and moisture.



Key points:

- 10G Duplex Multimode Cable Designed for Outdoor or Harsh Indoor Environments
- IP68 Rating Denotes Resistance to Dust and Water
- Color-Coded to Avoid Misidentification That Can Cause Costly Downtime

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Connections		Length	Colors		Cable Jacket		Number of Fibers	Fiber Type	Endface Polish
	Connector A	Connector B		Cable Jacket	Connector	Material	Rating			
N820-01M-IND	LC	LC	1 m	Aqua	Beige	PVC	OFNR	2	50/125	PC
N820-02M-IND	LC	LC	2 m	Aqua	Beige	PVC	OFNR	2	50/125	PC
N820-05M-IND	LC	LC	5 m	Aqua	Beige	PVC	OFNR	2	50/125	PC
N820-10M-IND	LC	LC	10 m	Aqua	Beige	PVC	OFNR	2	50/125	PC

Industrial Network Switches

Industrial-grade switch expands Ethernet connectivity to factory floors and other environments with space constraints and wide temperature ranges.



Key points:

- Easy-to-read LEDs indicate connection and activity status for all 5 Ethernet ports
- Plug-and-play operation with no software or configuration required before use

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Number of ports		PoE+ Ports	Switching Capacity	Terminal block	Operating Temp. Range	USB & Console Ports	Mounting Support
	RJ45	SFP						
Unmanaged Fast Ethernet								
NFI-U05	5	-	-	1 Gbps	3-Pin, 12-48 VDC	-40° to 75°C	-	DIN/Wall Mount (Slots)
NFI-U08-1	8	-	-	1,6 Gbps	3-Pin, 18-30 VDC	-40° to 75°C	-	DIN/Wall Mount (Brackets)
NFI-U08-2	8	-	-	1,6 Gbps	2-Pin, 12-48 VDC	-40° to 75°C	-	DIN Mount
Unmanaged Gigabit Ethernet								
NGI-U08	8	-	-	16 Gbps	6-Pin, 9-57 VDC Redundant Power Inputs	-40° to 75°C	-	DIN Mount
NGI-U08C2	8	2 (Dedicated)	-	20 Gbps	6-Pin, 24-48 VDC Redundant Power Inputs	-40° to 75°C	-	DIN Mount
NGI-U16	16	-	-	32 Gbps	2-Pin, 12-48 VDC	-40° to 75°C	-	DIN Mount
Unmanaged Gigabit Ethernet with PoE								
NGI-U05POE4	5	0	4 (≤ 30W Each; ≤ 120W Total)	10 Gbps	2-Pin, 24-57 VDC	-10° to 60°C	-	DIN Mount
NGI-U05C2POE4	5	2 (Dedicated)	4 (≤ 30W Each; ≤ 120W Total)	14 Gbps	2-Pin, 24-57 VDC	-10° to 60°C	-	DIN Mount
NGI-U08C2POE8	8	2 (Dedicated)	8 (≤ 30W Each; ≤ 240W Total)	20 Gbps	6-Pin 24-57 VDC Redundant Power Inputs	-40° to 75°C	-	DIN Mount
Managed Gigabit Ethernet								
NGI-M04C2	4	2	-	12 Gbps	6-Pin 20-57 VDC Redundant Power Inputs	-40° to 75°C	-	DIN Mount
NGI-M05-C1	5	1	-	12 Gbps	6-Pin 20-57 VDC Redundant Power Inputs	-40° to 75°C	-	DIN Mount
NGI-M08C2	8	2	-	20 Gbps	6-Pin 24-48 VDC Redundant Power Inputs	-40° to 75°C	Yes	DIN Mount
NGI-M08C4POE8-2	8	4	8 (≤ 30W Each 120W/24VDC ; 240W/48VDC)	24 Gbps	6-Pin 24-57 VDC Redundant Power Inputs	-40° to 75°C	Yes	DIN Mount
NGI-M08POE8-L2	8	-	8 (≤ 30W Each 120W/24VDC ; 240W/48VDC)	16 Gbps	6-Pin 24-57 VDC Redundant Power Inputs	-40° to 75°C	Yes	DIN Mount
Lite Managed Ggabit Ethernet								
NGI-S04C2	4	2	-	12 Gbps	6-Pin 20-60 VDC Redundant Power Inputs	-10° to 60°C	-	DIN Mount
NGI-S05C2POE4	5	2	4 (≤ 30W Each 120W/24VDC ; 240W/48VDC)	14 Gbps	2-Pin	-10° to 60°C	-	DIN Mount
NGI-S08C2POE8	8	2	8 (≤ 30W Each 120W/24VDC ; 240W/48VDC)	20 Gbps	6-Pin 24-57 VDC Redundant Power Inputs	-10° to 60°C	-	DIN Mount
NGI-S16	16	-	-	32 Gbps	6-Pin 12-60 VDC Redundant Power Inputs	-10° to 60°C	-	

Transceivers

Industrial transceiver module links a Gigabit Ethernet network fiber cable to the SFP port on a switch, firewall or other network device.



Key points:

- Hot-swappable interface lets you install and uninstall without shutting down
- Supports bi-directional Gigabit Ethernet data transfer rates up to 1.25 Gbps

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Technology	Connections		Brand Compatibility	Data Transfer Rate	Transmission Distance	Operating Temp. Range
		Connector A	Connector B				
N2861-1P25GLXD1	Singlemode	SFP (M)	LC (F)	TRENDnet	1 Gbps	10 km	-40° to 85°C
N2861-1P25GSXD	Multimode	SFP (M)	LC (F)	TRENDnet	1 Gbps	550 m	-40° to 85°C

USB 3.1 Gen 1 Cables

Connects high-speed USB 3.0 equipment in industrial environments that require protection against dust and moisture.



Key points:

- Shielded USB 3.0 Cable Recommended for Outdoor or Harsh Indoor Environments
- IP68 Rating Denotes Resistance to Dust and Water
- Heavy Shielding Protects Your Network Data from Destructive Line Noise

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Connections		Cable type	Length	Cable Jacket Color
	Connector A	Connector B			
U325-003-IND	USB-A	USB-A	Passive	91 cm	Black
U325-006-IND	USB-A	USB-A	Passive	1,83 m	Black
U325-010-IND	USB-A	USB-A	Passive	3,05 m	Black
U325-013-IND	USB-A	USB-A	Passive	3,96 m	Black

USB Adapters

USB to serial converter lets you connect four 9-pin serial devices to your computer or laptop's USB-A port.



Key points:

- Connects Up to Four 9-Pin Serial Devices to Your Computer, Laptop or Tablet's USB-A Port
- Auto-detects and -switches RS-422 and RS-485 serial devices
- Rugged All-Metal Housing Designed to Last in Harsh Industrial Applications
- Operate serial-based medical instruments, such as bedside monitors

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Number of Ports	Connections		Power Consumption (Watts)	USB Specification	Driver Required	Length
		Connector A	Connector B				
U208-002-IND	2	USB-B (F)	2x DB9 (M)	4.5	USB 2.0 (up to 480 Mbps)	Yes	-
U208-004-IND	4	USB-B (F)	4x DB9 (M)	4.5	USB 2.0 (up to 480 Mbps)	Yes	-
U209-30N-IND	-	USB-A (M)	DB9 (M)	-	USB 2.0 (up to 480 Mbps)	Yes	76 cm

USB Hubs

Rugged industrial-grade hub adds 4 USB 2.0 ports to your computer for connecting industrial printers, sensors and other USB devices.



Key points:

- Rugged metal housing designed to withstand harsh warehouse and factory environments
- ESD protection to ± 15 kV cuts potential static damage to your connected peripherals
- Plug-and-play operation with no software required for easy, immediate installation

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Data Ports

Part number	Host connector	Data Ports						Gbps Ethernet	Power Source Type	ESD Protection	Operating Temp. Range	Mounting Support
		USB-A 2.0	USB 3.1 Gen 1	USB-A 3.2 Gen 1	USB-B	USB-C	USB-C PD Charging					
U223-004-IND	USB-A	4	-	-	-	-	480 Mbps	3-Pin Terminal Block	15KV	0° to 60°C	Wall/DIN	
U223-004-IND-1	USB-A	4	-	-	-	-	480 Mbps	3-Pin Terminal Block	15KV	0° to 60°C	Wall/DIN	
U223-007-IND	USB-A	7	-	-	-	-	480 Mbps	3-Pin Terminal Block	15KV	0° to 60°C	Wall/DIN	
U223-007-IND-1	USB-A	7	-	-	-	-	480 Mbps	3-Pin Terminal Block	15KV	0° to 60°C	Wall/DIN	
U360-004-IND	USB-A	-	4	-	-	-	5 Gbps	3-Pin Terminal Block	20KV	0° to 60°C	Wall/DIN	
U360-007-IND	USB-A	-	7	-	-	-	5 Gbps	3-Pin Terminal Block	20KV	0° to 60°C	Wall/DIN	
U360-010-IND	USB-A	-	10	-	-	-	5 Gbps	3-Pin Terminal Block	20KV	0° to 60°C	Wall/DIN	
U460-2A2C-IND	USB-C	-	-	2	-	2	10 Gbps	2-wire terminal block/LPS 12V DC-24V DC	15KV	0° to 50°C	-	
U460-4A3C-IND	USB-C	-	-	4	-	3	10 Gbps	2-wire terminal block/LPS 12V DC-24V DC	15KV	0° to 50°C	-	

USB Extenders

Industrial-grade transmitter/receiver combo connects a laptop or PC to as many USB peripherals up to 100 m away.



Key points:

- Supports USB 2.0 speeds up to 300 Mbps to ensure reliable data transfers
- Power over Cable (PoC) provides power to the transmitter via Cat5/6 cable
- Industrial-grade metal housings withstand harsh warehouse and factory environments

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Number of Ports	Gbps Ethernet	Transmission Distance	Power source	Power Over Cable	ESD Protection	Operating Temp. Range	Mounting Support
B203-101-IND	1	480 Mbps	45 m	AC Adapter	Yes	15KV	0° to 50°C	DIN
B203-101-IND-ER	1	300 Mbps	100 m	AC Adapter	Yes	15KV	0° to 40°C	DIN
B203-104-IND	4	480 Mbps	45 m	AC Adapter	Yes	15KV	0° to 40°C	DIN
B203-104-IND-ER	4	300 Mbps	100 m	AC Adapter	Yes	15KV	0° to 40°C	DIN

HDMI Cables

Connects high-speed 4K audio/video and Ethernet equipment in industrial environments that require protection against dust and moisture.



Key points:

- IP68-rated cable resists dust and endure immersion in 1.5 m of water up to 60 min*
- Supports UHD resolutions up to 4K (4:4:4) for crystal-clear video
- Carries High Dynamic Range (HDR) signals for rich contrast and expanded color accuracy
- Complies with HDCP 2.2 standards to display up-to-date 4K video content

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Max resolution supported	Connections		Length	Cable type	Signal Transmission	Operating Temp. Range	cable jacket		COLOR	
		Connector A	Connector B					Material	Rating	Cable Jacket	Connector
P569-003-IND	4K @60 Hz	HDMI	HDMI	91 cm	Passive	Bidirectional	-10° to 50°C	PVC	VW-1	Black	Black
P569-006-IND2	4K @60 Hz	HDMI	HDMI	1,83 m	Passive	Bidirectional	-10° to 50°C	PVC	VW-1	Black	Black
P569-012-IND	4K @60 Hz	HDMI	HDMI	3,66 m	Passive	Bidirectional	-10° to 50°C	PVC	VW-1	Black	Black
P569-012-IND2	4K @60 Hz	HDMI	HDMI	3,66 m	Passive	Bidirectional	-10° to 50°C	PVC	VW-1	Black	Black

Couplers

Connects Ethernet or fiber optic equipment in industrial environments that require protection against dust, debris and moisture.



Key points:

- Connect Ethernet, Fiber, USB or HDMI equipment in Industrial environments that require protection against dust, debris and moisture.

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Connections		Shielding				PoE Type	Color
	Connector A	Connector B	Cable shielding	Conductor shielding				
N206-BC01-IND	RJ45 (F)	RJ45 (F)	Yes	STP			Type 4 High-Power (100W, IEEE 802.3bt)	Black
N455-BC01-IND	Multimode LC (F)	Multimode LC (F)	-	-	-	-	-	Black
P569-000-FF-IND	HDMI (F)	HDMI (F)	-	-	-	-	-	Black
U325-000-IND	USB 3.0	USB 3.0	-	-	-	-	-	Black

PoE Injectors & Extenders

Industrial-grade PoE+ injectors uses existing Cat6 cable to supply up to 90W power + data up to 100m to a PoE device connected to a non-PoE switch.



Key points:

- Gigabit Extender Lets You Cascade Your Existing PoE/PoE+ Connection up to 400 M
- Supports Gigabit Ethernet data transfer speeds up to 1 Gbps
- Supports Power over Ethernet to Save You Money and Give You More Installation Choices
- Industrial-grade IP30 metal housing ready for DIN rairmounting with included

Ideal for:

- Manufacturing plants
- Production floors
- Warehouses/Logistics facilities
- Dusty, outdoor network or Digital Signage installations

Part number	Transmission Distance	Power Source	PoE Type	Max PoE budget	Mounting Support	Operating Temp. Range
Industrial Injectors						
NPOEI-60W-1G	Up to 100 m	Dual 24 – 57 VDC Terminal Block	Type 3 PoE++/UPoE (60W, IEEE 802.3bt)	60W	DIN-Rail Rackmount Wall-mount	-40° to 75°C
NPOEI-90W-1G	Up to 100 m	Dual 24 – 57 VDC Terminal Block	Type 4 PoE++/UPoE (100W, IEEE 802.3bt)	90W	DIN-Rail Rackmount Wall-mount	-40° to 75°C

Part number	Voltage Compatibility (VAC)	Input		Power Consumption (Watts)	Technology				Cable		PoE Type
		Frequency	Plug Type		Cat5/5e	Cat6	Cat6a	Cat8	Connector A	Connector B	
Injectors											
NPOE-30W-1G-INT	Up to 240V	50/60 Hz	BS1363 Schuko	30W	Yes	Yes	Yes	-	RJ45 (F)	RJ45 (F)	Type 2 PoE+ (30W)
Extenders											
NPOE-EXT-1G30	-	-	-	30W	Yes	Yes	Yes	-	RJ45 (F)	RJ45 (F)	Type 2 PoE+ (30W)
NPOE-EXT-1G30WP Water resistant (IP65)	-	-	-	30W	Yes	Yes	Yes	-	RJ45 (F)	RJ45 (F)	Type 2 PoE+ (30W)
NPOE-EXT-2X1G30 Water resistant (IP67)	-	-	-	95W	Yes	Yes	Yes	-	RJ45 (F)	2x RJ45 (F)	Type 4 PoE++ (100W)
Splitters											
NPOE-SPL-G-SVMU	5VDC	-	-	-	Yes	Yes	-	-	RJ45 (F)	RJ45 (M) Micro USB-B (M)	

WAP Enclosures

Locking enclosure protects your Wi-Fi access point against theft, damage or tampering inside offices, dorms and other indoor areas.



Key points:

- Wall-Mount enclosure secures and organizes your router/modem or wireless
- Access point Locks Securely to Help Prevent Damage, Tampering or Theft
- Easy to Mount with the Included Hardware

Ideal for:

- Telecommunications
- Server room
- Indoor or outdoor router/modem or Wi-Fi access point

Part number	Dimensions				Material of Construction	Colors	Compliance
	Height		Width	Depth			
	(U)	(cm)	(cm)	Max (cm)			
EN1111	0U	28,2 cm	28,2 cm	11,2 cm	ABS Plastic	White	RoHS
EN1309N4	0U	35,71 cm	25,1 cm	13,9 cm	UL 94 V-1 Classified PC Plastic	White	RoHS
EN1511N4LATCH	0U	38,6 cm	28,2 cm	10,1 cm	UL 94 V-1 Classified PC Plastic	White	NEMA 4/RoHS
EN1812	0U	45,5 cm	30,2 cm	12,9 cm	PC Plastic	White	RoHS
Accessories - Mounting Brackets							
ENBRKT	0U	6,5 cm	17,8 cm	21,8 cm	-	White	RoHS
ENBRKTCVR	0U	19,5 cm	24 cm	29 cm	-	White	RoHS



Healthcare

Power Solutions
Safe-IT Cables
Display Mounts

UPS Systems

Line-interactive UPS provides basic battery backup with UL 60601-1 compliance for use in medical facilities, including patient care areas.



Key points:

- IEC 60601-1 compliant
- Approved for Use in Patient Care Vicinities
- Lead acid & Lithium Battery Technology
- Breathe new life into your UPS: replacement battery cartridge available

Ideal for:

- Hospitals
- Medical centers
- Dr. clinics
- Patientcare facilities

no hyperlink

Part number	Battery	Output capacity	Nominal AC Voltage	Runtime (Half/Full Load)	Hospital-Grade AC Outlets (1)	Communication ports	AC Input Cord Length	AC Input Inlet
SMX700HG	SLA	700VA / 450W	230 V	36/14.5 min	6 (C13)	Serial & USB	15.2 cm	C14
SMX1200XLHG	SLA	1kVA / 750W	230 V	27.5/11 min. +	6 (C13)	Serial & USB	15.2 cm	C14
SMX700HGL	Lithium Iron	700VA / 450W	230 V	42/18 min	6 (C13)	Serial & USB	15.2 cm	C14
SMX1200XLHGL	Lithium Iron	1kVA / 750W	230 V	28/10 min. +	6 (C13)	Serial & USB	15.2 cm	C14

Replacement battery cartridge

RBC53L	UPS Replacement 36VDC Lithium-ion (LiFePO4) Battery Cartridge for Select Lithium-ion UPS
RBC36-SLT	UPS Replacement 36VDC Battery Cartridge for Select SLT UPS compatible with

⁽¹⁾ Backup runtimes vary with load, battery condition and other factors. Increase runtimes for "+" models by connecting optional external battery packs.

⁽²⁾ Lithium Iron Phosphate (LiFePO4) battery with a 10,000-cycle life (20-30 times the cycle life of traditional batteries).

Isolation Transformers

Transformer with full CAN/ES/IEC/EN 60601-1 listing offers line isolation, step-up and step-down capabilities, and continuous noise filtering in protecting medical electronic equipment used in patient-care vicinities.



Key points:

- Protects sensitive equipment from EMI/RFI line noise and surges
- Cumulative leakage current less than 100 µA
- Automatically shuts down all outlets in case of overload
- Line isolation, continuous noise filtering and 240 joules of AC surge protection
- Step-up, step-down or pass-through Dual-Voltage 115/230V operation

Ideal for:

- Hospitals
- Medical centers
- Dr. clinics
- Patientcare facilities
- Applications requiring dual-voltage step-up/down

Part number	Output	Nominal AC Voltage	Hospital-Grade AC Outlets (1)	AC Input Inlet
IS300HGDV	300W	115/230V	4 (C13)	C14
IS600HGDV	600W	115/230V	6 (C13)	C14
IS1000HGDV	1000W	115/230V	8 (C13)	C14
IS1800HGDV	1800W	115/230V	8 (C13)	C20

Power Inverter/Chargers

Power Inverter/Chargers for Mobile Medical Equipment, powers equipment used in healthcare facilities inside and outside patient care areas. 230V - IEC 60601-1



Key points:

- All-in-one inverter/charger/controller powers equipment on mobile medical carts
- Works with both SLA and LiFePhos batteries to best fit your power requirements
- Internal ATS powers connected equipment and recharges battery simultaneously
- Rugged Construction Sure to Stand Up to Demanding Environments

Ideal for:

- Hospitals
- Healthcare facilities

Part number	Output	Battery	Runtime ⁽¹⁾	Battery Charge	AC Outlets	Communication ports	Expandable Runtime
HCINT150SL	150W	SLA or LiFePhos 12VDC	up to 6 hours	Equal to discharge time (9-20A)	(1) C13	USB	Yes
HCINT350SNR	150W	SLA or	up to 6 hours	Equal to discharge time (9-20A)	(1) C13	USB	Yes

⁽¹⁾ Up to 6 hours typical runtime in standard configuration. Runtime varies depending on battery condition and load.

Accessories

Part number	Description
HCBATTERYCABLE	Power Cable Kit for Healthcare Power Modules/Inverters/Chargers, 3 ft. (0.91 m)
HCFLUSHRUI	Remote Control Module for Healthcare Products - for Medical Power Modules/Inverters/Chargers

Cat6a Safe-IT Copper Cables

Connects critical components, such as switches and servers, in 10G Ethernet networks, while also providing extra protection against bacteria.



Key points:

- Antibacterial material: connectors & PVC jacket
- Premium Cat6a cable rated for high-speed 10 Gbps communications
- Protects sensitive equipment from EMI/RFI line noise and surges
- Lifetime limited warranty

Ideal for:

- Schools
- Restaurants & Kitchens
- Shared offices spaces
- Hospitals

Part number	Shielding	Cable shielding	Pair shielding	Length	Network compatibility	Conductor material	Color	
Snagless								
N262AB-003-WH	Yes	S/FTP	Braiding	Foiled	91 cm	10Gbps	Stranded Copper	White
N262AB-005-WH	Yes	S/FTP	Braiding	Foiled	1,52 m	10Gbps	Stranded Copper	White
N262AB-007-WH	Yes	S/FTP	Braiding	Foiled	2,13 m	10Gbps	Stranded Copper	White
N262AB-010-WH	Yes	S/FTP	Braiding	Foiled	3,05 m	10Gbps	Stranded Copper	White
N262AB-014-WH	Yes	S/FTP	Braiding	Foiled	4,27 m	10Gbps	Stranded Copper	White
N262AB-020-WH	Yes	S/FTP	Braiding	Foiled	6,09 m	10Gbps	Stranded Copper	White
N262AB-025-WH	Yes	S/FTP	Braiding	Foiled	7,62 m	10Gbps	Stranded Copper	White

Safe-IT USB Cables

Supports a wide range of equipment and applications both inside and outside patient care vicinities.



Key points:

- Antibacterial material: connectors & PVC jacket
- Protects sensitive equipment from EMI/RFI line noise and surges
- MFI certified (Made for iPhone, iPad and iPod)

Ideal for:

- Schools
- Restaurants & Kitchens
- Shared offices spaces
- Hospitals

Part number	Connector A	Connector B	Length	Color
2.0 USB Generation cable (M/M)				
U022AB-006-WH	USB-A	USB-B	1,83 m	White
U022AB-010-WH	USB-A	USB-B	3,05m	White
U030AB-003-WH	USB-A	USB Mini-B	91 cm	White
U030AB-006-WH	USB-A	USB Mini-B	3,05 m	White
U050AB-003-WH	USB-A	Micro USB-B	91 cm	White
U050AB-006-WH	USB-A	Micro USB-B	3,05 m	White
U038AB-003-S-LB	USB-A	USB-C	91 cm	Light Blue
U038AB-006-S-LB	USB-A	USB-C	3,05 m	Light Blue
U040AB-006CS5LB ⁽¹⁾	USB-C	USB-C	1,83 m	Light Blue
Lightning cable (M/M)				
M100AB-003-S-LB	USB-A	Lightning	91 cm	Light Blue
M100AB-006-S-LB	USB-A	Lightning	3,05 m	Light Blue
M100AB-01M-WH	USB-A	Lightning	1 m	White
M100AB-02M-WH	USB-A	Lightning	2 m	White
M100AB-03M-WH	USB-A	Lightning	3 m	White
M102AB-003-S-LB	USB-C	Lightning	91 cm	Light Blue
M102AB-006-S-LB	USB-C	Lightning	3,05 m	Light Blue
M102AB-01M-WH	USB-C	Lightning	1 m	White
M102AB-02M-WH	USB-C	Lightning	2 m	White
All-in-one cable				
M101AB-004-LMCW	USB-A	Lightning, USB Micro-B & USB-C	1,2 m	White
Extension cable (M/F)				
U024AB-003-WH	USB-A	USB-A	91 cm	White
U024AB-006-WH	USB-A	USB-A	3,05 m	White

Safe-IT Audio Video Cables

HDMI cable with antibacterial properties connects audio/video components to a 4K display.



Key points:

- Antibacterial material: connectors & PVC jacket

Ideal for:

- Digital signage
- Retail
- WFA
- Hospitals

Part number	Connector A	Connector B	Max Supported Video Resolution	Chroma Sub Sampling	Length	Color
P566AB-006	HDMI	DVI-D	Full HD @ 60Hz	4:4:4	1,83 m	Black
P581AB-006	DisplayPort	DVI	Full HD	-	1,83 m	Black
P569AB-006⁽¹⁾	HDMI	HDMI	3840 x 2160 (4K) @ 30Hz	4:4:4	1,83 m	Black
P580AB-006	DisplayPort	DisplayPort	3840 x 2160 (4K) @ 60Hz	4:4:4	1,83 m	Black

⁽¹⁾ With Ethernet

Rolling TV Stands and Carts

HDMI cable with antibacterial properties connects audio/video components to a 4K display.



Key points:

- Antibacterial material: connectors & PVC jacket

Ideal for:

- Digital signage
- Retail
- WFA

Part number	Mounting Location	VESA Pattern (mm)		Number of Displays	Heavy-Duty	Maximum Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
		Min	Max							
DMCS3770AMUL	Floor	200x200	600x400	1	Yes	70 kg	Full	360°	Yes	Black
DMCS70120AMUL	Floor	200x200	1000x600	1	Yes	120 kg	Full	360°	Yes	Black
DMCS60100XXCK	Floor	200 x 200	1000x600	1	No	100 kg	Tilt	+5° to -10°	Yes	Silver

⁽¹⁾With Ethernet

Desktop Monitor Mounts

Supports a wide range of equipment and applications both inside and outside patient care vicinities.






Key points:

- Includes antimicrobial tape for the handle to help protect against bacteria and viruses

Ideal for:

- Digital signage
- Retail
- WFA
- Hospitals

Part number	Screen size		Mounting Location	VESA Pattern (mm)		Max Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
	Min	Max		Min	Max					
Single Display 										
DDV1732AM	17"	32"	Freestanding	75x75	100x100	7 kg	Full	-15/+15 Tilt -40/+40 Swivel	No	Black
DWMLARM1732AM	17"	32"	Wall	75x75	100x100	8 kg	Full	0/+90 Tilt 180° Swivel	Yes	White
Dual Displays 										
DDVD1727AM	17"	27"	Freestanding	75x75	100x100	6 kg	Full	-45/+45 Tilt -40/+40 Swivel	Yes	Black
DMPDD1735AM	17"	35"	Desk Clamps & Grommets	75x75	100x100	10 kg	Full	-22/+45 Tilt 32° Swivel 90° Rotate	Yes	Black
Triple Displays 										
DMPDT1732AM	17"	32"	Desk Clamps & Grommets	75x75	100x100	6 kg	Full	-22/+45 Tilt 32° Swivel 90° Rotate	Yes	Black

Workstations

Supports a wide range of equipment and applications both inside and outside patient care vicinities.



Key points:

- Antibacterial material: connectors & PVC jacket
- Protects sensitive equipment from EMI/RFI line noise and surges
- MFI certified (Made for iPhone, iPad and iPod)

Ideal for:

- Retail
- WFA
- Hospitals

Part number	Mounting Location	VESA Pattern (mm)		Number of Displays	Heavy-Duty	Maximum Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
		Min	Max							
WWSSDTAM	Desktop	-	-	1	No	13 kg	-	-	No	Black
WWSSFDSAM	Wall	-	-	1	No	10 kg	Fixed	-	Yes	Black

Clamp-On Monitor Risers

Desktop computer stand with antimicrobial protection lifts your monitor above your workstation surface to help ease eye and neck strain.



Key points:

- Clamps securely to a desk, table or shelf to clear valuable workspace
- Antimicrobial protection helps resist the growth of bacteria, viruses, fungi, mold and mildew
- Assembles easily in just a few minutes with all hardware included

Ideal for:

- Retail
- WFA
- Hospitals

Part number	Mounting Location	Desk Clamps	Number of Displays	Heavy-Duty	Wide platform	Maximum Weight Capacity	Motion	Degrees of Motion	Height adjustable	Color
WWSSCOS40AM	Desktop	Desk Clamps	1	No	1 m		Fixed	-	-	

Eaton's electrical business is a global leader with deep regional application expertise in power distribution and circuit protection; power quality, backup power and energy storage; control and automation; life safety and security; structural solutions; and harsh and hazardous environment solutions. Through end-to-end services, channel and an integrated digital platform & insights Eaton is powering what matters across industries and around the world, helping customers solve their most critical electrical power management challenges.

For more information, visit [Eaton.com](https://www.eaton.com)