

# Industrial Stainless Steel Monitor ETPM-E15

15" Full IP66/67 Stainless Steel Display

## Product Features:

- 15" TFT LCD
- True Flat Front Bezel Design
- Projected Capacitive / Resistive Touch
- Full IP66 Rating Stainless Steel Enclosure
- Tempered Glass Integrated (Optional)
- 1000nits High Brightness (Optional)



## Product Specifications:

|             |                                 |                                  |
|-------------|---------------------------------|----------------------------------|
| Display     | Model Name                      | ETPM-E15                         |
|             | Size/Type                       | 15" TFT                          |
|             | Resolution (pixels)             | 1024 x 768                       |
|             | Number of Colors                | 16.7m                            |
|             | Brightness (cd/m <sup>2</sup> ) | 350 Standard; 1000nits (opt.)    |
|             | Backlight lifetime              | 50,000hrs                        |
|             | Viewing Angle                   | 176°H/176°V                      |
| System      | VGA                             | 1 x VGA                          |
|             | USB                             | 1 x USB                          |
|             | HDMI                            | 1 x HDMI                         |
|             | OSD Control                     | 5 Keys on the rear side          |
|             | WIFI                            | NONE                             |
| Power       | Power Input                     | DC 12~36V                        |
|             | Power                           | IP67 Waterproof Connector        |
|             | Power Consumption               | 26.4W                            |
| Mechanical  | Construction                    | Stainless Steel Enclosure        |
|             | IP rating                       | IP66 / 67                        |
|             | Mounting                        | VESA mounting 75 x75 / 100 x 100 |
|             | Dimension (mm)                  | 393.4 x 310.4 x 64               |
|             | Net weight                      | 8kg                              |
| Environment | Operating Temp.                 | -20°~ 70°C                       |
|             | Storage Temp.                   | -20°~70°C                        |
|             | Storage humidity                | 10 to 90% @40°C, Non-condensing  |
|             | Certification                   | CE/FCC Class A                   |

Note: All Specifications are subject to change without prior notice!



